

## DECLARATION OF PERFORMANCE

No13-SC-S10

Product Type/Identification: Hydraulically pressed 35mm shot blast paving (X-Tex Textured Paving)

Intended Use: Trafficked paving area and roof coverings

Manufacturer: Stowell Concrete Ltd

Arnolds Way

Yatton

North Somerset

BS49 4QN

Email: [sales@stowellconcrete.co.uk](mailto:sales@stowellconcrete.co.uk)

Authorised Representative: Not Applicable

AVCP: System 4

Harmonised Standard: EN1339:2003


ETA: Not relevant

Declared Performance:

| Essential                 | Characteristics    | Performance                      | Harmonised Technical Specification |
|---------------------------|--------------------|----------------------------------|------------------------------------|
| Dimensions                | Length             | 600mm                            | EN1339:2003                        |
|                           | Width              | 600mm                            |                                    |
|                           | Thickness          | 35mm                             |                                    |
|                           | Tolerance category | 2                                |                                    |
| Bending strength          |                    | 3.5Mpa                           |                                    |
| Slip/skid resistance      |                    | Satisfactory                     |                                    |
| Reaction to fire          |                    | A1                               |                                    |
| External fire performance |                    | Satisfactory                     |                                    |
| Thermal conductivity      |                    | 1.52 ( $\lambda_{10, dry}$ )W/mK |                                    |
| Durability                |                    | Pass                             |                                    |
| Emission of Asbestos      |                    | No content                       |                                    |

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:



Vincent Stowell

Managing Director 18<sup>th</sup> August 2021

# DECLARATION OF PERFORMANCE

No13-SC-S11

Product Type/Identification: Hydraulically pressed 35mm shot blast paving (X-Tex Textured Paving)

Intended Use: Trafficked paving area and roof coverings

Manufacturer: Stowell Concrete Ltd

Arnolds Way

Yatton

North Somerset

BS49 4QN

Email: [sales@stowellconcrete.co.uk](mailto:sales@stowellconcrete.co.uk)

Authorised Representative: Not Applicable

AVCP: System 4

Harmonised Standard: EN1339:2003


ETA: Not relevant

Declared Performance:

| Essential                 | Characteristics    | Performance                      | Harmonised Technical Specification |
|---------------------------|--------------------|----------------------------------|------------------------------------|
| Dimensions                | Length             | 450mm                            | EN1339:2003                        |
|                           | Width              | 450mm                            |                                    |
|                           | Thickness          | 32mm                             |                                    |
|                           | Tolerance category | 2                                |                                    |
| Bending strength          |                    | 3.5Mpa                           |                                    |
| Slip/skid resistance      |                    | Satisfactory                     |                                    |
| Reaction to fire          |                    | A1                               |                                    |
| External fire performance |                    | Satisfactory                     |                                    |
| Thermal conductivity      |                    | 1.52 ( $\lambda_{10, dry}$ )W/mK |                                    |
| Durability                |                    | Pass                             |                                    |
| Emission of Asbestos      |                    | No content                       |                                    |

This declaration of performance is issued under the sole responsibility of the manufacturer above

Signed on behalf of Stowell Concrete Ltd:



Vincent Stowell

Managing Director 18<sup>th</sup> August 2021