

Maschiatori pneumatici con inversione a trazione Pneumatic and reversible tapping attachments


Mod. Series	Capacità (acciaio) Capacity (steel)	Attacco Mandrino Chuck connection	Giri Min Rpm	Coppia a 6 Bar Torque at 6 bar	Raccordo Aria Air connection	Consumo Aria Air Consumption Lt/min	Diam Tubo Pipe dia. mm	Diam Corpo Body dia. mm	L	Peso Weight (Kg)	Db
 DIRITTO POTENZA 150 WATT STRAIGHT											
REVM080150	3 - 8	B10	370	14	1/4" GAS	260	6	38	340	1,30	75
 DIRITTO POTENZA 300 WATT STRAIGHT											
REVDR120300	4 - 12	B10	360	28	1/4" GAS	430	8	38	350	1,50	75
 ANGOLO 90° POTENZA 300 WATT 90° DEGREES											
REV9R120300	6 - 12	B10	360	28	1/4" GAS	430	8	38	350	1,50	75

Maschiatori pneumatici con inversione a pulsante Pneumatic and Reversible Tapping attachments with

Mod. Series	Capacità (acciaio) Capacity (steel)	Attacco Mandrino Chuck connection	Giri Rpm Min	Coppia a 6 Bar Torque at 6 bar	Raccordo Aria Air connection	Consumo Aria Air Consumption Lt/min	Diam Tubo Pipe dia. mm	Diam Corpo Body dia. mm	L	Peso Weight (Kg)	Db
 DIRITTO POTENZA 300 WATT STRAIGHT											
RAPDR080300	3 - 8	B12	650	16	1/4" GAS	600	10	43	297	1,50	82
RAPDR140300	6 - 14	B12	350	28	1/4" GAS	600	10	43	297	1,50	82
 DIRITTO CON POTENZA 500 WATT STRAIGHT											
RAPDR160500	4 - 16	B16	270	64	1/2" GAS	1000	13	55	404	3,50	80
RAPDR300500	10 - 30	B16	100	180	1/2" GAS	1000	13	55	440	4,20	82

Altri modelli di maschiatori pneumatici a richiesta – On request other models of pneumatic tapping attachments

Banco di maschiatura Bench for tapping arm



Uso: per braccio articolato 600x900mm.

Use: for tapping arm 600x900mm.