Hex Detex™ Solvent A

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
Issue date: 6/22/2026 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : Hex Detex™ Solvent A
Product code : HD-2001A

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

No additional information available

1.4. Supplier's details

Veteran Equipment Sales, LLC
3773 E. Comstock Ave.
Nampa, Idaho 83687
United States
T 1-877-75-BLAST (25278)
info@vessystems.com - www.vessystems.com

1.5. Emergency phone number

Emergency number : 1-877-75-BLAST (25278)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 2	H225	Highly flammable liquid and vapor.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Carcinogenicity, Category 1A	H350	May cause cancer.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor
H319 - Causes serious eye irritation
H350 - May cause cancer.
Precautionary statements (GHS US) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof equipment.

P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective clothing, eye and face protection, protective gloves.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc.	GHS US classification
phosphoric acid, conc≥25%, aqueous solutions	CAS-No.: 7664-38-2	70 – 80	Not classified
ethanol	CAS-No.: 64-17-5	10 – 20	Flam. Liq. 2, H225 Carc. 1A, H350
acetone	CAS-No.: 67-64-1	5 – 15	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
methanol	CAS-No.: 67-56-1	< 1	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 Acute Tox. 3 (Inhalation:dust,mist), H331 STOT SE 1, H370

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation	:	Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	:	Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact	:	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	:	Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders.	:	First-aiders should consider self-protection and use the recommended personal protective equipment (see section 8).

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	:	None under normal conditions.
Symptoms/effects after skin contact	:	None under normal conditions.
Symptoms/effects after eye contact	:	Eye irritation.
Symptoms/effects after ingestion	:	None under normal conditions.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	:	Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	:	Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	:	Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	:	Highly flammable liquid and vapor.
Explosion hazard	:	No direct explosion hazard.
Hazardous decomposition products in case of fire	:	Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	:	Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	:	Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

For non-emergency personnel

Protective equipment	:	Wear recommended personal protective equipment.
Emergency procedures	:	No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene.

For emergency responders

Protective equipment	:	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	:	Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions	:	Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb spilled material with sand or earth. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Packaging materials : Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

ethanol (64-17-5)	
USA - ACGIH® - Threshold Limit Values	
Local name	Ethanol
ACGIH® TLV® STEL	1000 ppm
Remark (ACGIH®)	TLV® Basis: URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Ethyl alcohol (Ethanol)
OSHA PEL TWA	1900 mg/m³
	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

methanol (67-56-1)	
USA - ACGIH® - Threshold Limit Values	
Local name	Methanol
ACGIH® TLV® TWA	200 ppm
ACGIH® TLV® STEL	250 ppm
Remark (ACGIH®)	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2024
USA - ACGIH® - Biological Exposure Indices	
Local name	Methanol
BEI	15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B, Ns
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Methyl alcohol
OSHA PEL TWA	260 mg/m³
	200 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

acetone (67-64-1)	
USA - ACGIH® - Threshold Limit Values	
ACGIH® TLV® TWA	250 ppm
ACGIH® TLV® STEL	500 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:
Wear recommended personal protective equipment.

Hand protection:
Protective gloves

Eye protection:
Safety glasses

Skin and body protection:
Wear suitable protective clothing

Respiratory protection:
[In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	:	Liquid
Color	:	No data available
Odor	:	No data available
Odor threshold	:	No data available
pH	:	No data available
Melting point	:	Not applicable
Freezing point	:	No data available
Boiling point	:	No data available
Flash point	:	No data available
Flammability (solid, gas)	:	Not applicable.
Vapor pressure	:	No data available
Relative vapor density at 20°C	:	No data available
Relative density	:	No data available
Solubility	:	Water: Solubility in water of component(s) of the mixture : • ethanol: 78.9 g/100ml • methanol: ≥ 100 g/100ml • acetone: • phosphoric acid, conc≥25%, aqueous solutions:
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity, kinematic	:	No data available
Explosion limits	:	No data available
Particle characteristics	:	No data available

ethanol	
Boiling point	78 °C (1013 hPa)
Flash point	13 °C (Closed cup, 1013.25 hPa)
Auto-ignition temperature	363 – 425 °C (1013.25 hPa, T2)
Vapor pressure	57 hPa (20 °C)
Vapor pressure at 50°C	300 hPa

methanol	
Boiling point	65 °C (1013 hPa)
Flash point	10 °C (Closed cup, 1013 hPa, EU Method A.9: Flash-Point)
Auto-ignition temperature	455 °C (1013 hPa, DIN 51794: Self-ignition temperature, T1)
Vapor pressure	128 hPa (20 °C)
Vapor pressure at 50°C	552 hPa

acetone	
Boiling point	56 °C
Flash point	-17 °C (Closed cup)
Auto-ignition temperature	465 °C (T1)
Vapor pressure	240 hPa (20 °C)
Vapor pressure at 50°C	828 hPa

phosphoric acid, conc≥25%, aqueous solutions	
Boiling point	101 – 158 °C
Flash point	Not applicable
Auto-ignition temperature	Not applicable
Vapor pressure	2 – 23 hPa (20 °C)

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 oral	8300 mg/kg body weight Animal: mouse
LD50 dermal rabbit	> 15800 mg/kg body weight (Rabbit, Experimental value, Dermal)
LC50 Inhalation - Rat	124.7 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	8300 mg/kg body weight

methanol (67-56-1)	
LD50 oral rat	1187 – 2769 mg/kg body weight (BASF test, Rat, Male / female, Experimental value, 15-35 % aqueous solution, Oral, 7 day(s))
LD50 dermal rabbit	17100 mg/kg (Rabbit, Inconclusive, insufficient data, Dermal)
LC50 Inhalation - Rat	128.2 mg/l air (BASF test, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
ATE US (oral)	1187 mg/kg body weight
ATE US (dermal)	17100 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 15800 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	132 mg/l (3 h, Rat, Male, Experimental value, Inhalation (vapours))
ATE US (oral)	5800 mg/kg body weight
ATE US (vapors)	132 mg/l/4h
ATE US (dust, mist)	132 mg/l/4h

Skin corrosion/irritation : Not classified

ethanol (64-17-5)	
pH	7 (789 g/l, 20 °C)

methanol (67-56-1)	
pH	No data available in the literature

acetone (67-64-1)	
pH	5 – 6 (20 °C)

phosphoric acid, conc≥25%, aqueous solutions (7664-38-2)	
pH	No data available in the literature

Serious eye damage/irritation : Causes serious eye irritation.

ethanol (64-17-5)	
pH	7 (789 g/l, 20 °C)

methanol (67-56-1)	
pH	No data available in the literature

acetone (67-64-1)	
pH	5 – 6 (20 °C)

phosphoric acid, conc≥25%, aqueous solutions (7664-38-2)	
pH	No data available in the literature

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : May cause cancer.

ethanol (64-17-5)	
IARC group	1 - Carcinogenic to humans

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

methanol (67-56-1)	
STOT-single exposure	Causes damage to organs.

acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

ethanol (64-17-5)	
NOAEL (subchronic,oral,animal/male,90 days)	< 9700 mg/kg body weight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic,oral,animal/female,90 days)	> 9400 mg/kg body weight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

Aspiration hazard : Not classified

ethanol (64-17-5)	
Viscosity, kinematic	1.6 mm²/s (20 °C)
methanol (67-56-1)	
Viscosity, kinematic	0.68 – 0.747 mm²/s
acetone (67-64-1)	
Viscosity, kinematic	No data available in the literature
phosphoric acid, conc≥25%, aqueous solutions (7664-38-2)	
Viscosity, kinematic	No data available in the literature

Symptoms/effects after inhalation : None under normal conditions.

Symptoms/effects after skin contact : None under normal conditions.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

ethanol (64-17-5)	
LC50 - Fish [1]	15300 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 72h - Algae [1]	275 mg/l (Equivalent or similar to OECD 201, Chlorella vulgaris, Static system, Fresh water, Experimental value, Growth rate)
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'

methanol (67-56-1)	
LC50 - Fish [1]	15400 mg/l (EPA 660/3 - 75/009, 96 h, Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	18260 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 96 h, Daphnia magna, Semi-static system, Fresh water, Experimental value, Locomotor effect)
EC50 96h - Algae [1]	22000 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Growth rate)
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	446.7 mg/l Test organisms (species): Pimephales promelas Duration: '28 d'
acetone (67-64-1)	
LC50 - Fish [1]	6210 – 8120 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)

12.2. Persistence and degradability

Hex Detex™ Solvent A	
Persistence and degradability	Not rapidly degradable
ethanol (64-17-5)	
Persistence and degradability	Biodegradable in the soil, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.8 – 0.967 g O_2/g substance
Chemical oxygen demand (COD)	1.7 g O_2/g substance
ThOD	2.1 g O_2/g substance
BOD (% of ThOD)	0.43
methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in the soil, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.6 – 1.12 g O_2/g substance
Chemical oxygen demand (COD)	1.42 g O_2/g substance
ThOD	1.5 g O_2/g substance
acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil, Biodegradable in the soil under anaerobic conditions, Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O_2/g substance
Chemical oxygen demand (COD)	1.92 g O_2/g substance
ThOD	2.2 g O_2/g substance
phosphoric acid, conc≥25%, aqueous solutions (7664-38-2)	
Persistence and degradability	Biodegradability: not applicable.

12.3. Bioaccumulative potential

ethanol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.35 (Experimental value, Equivalent or similar to OECD 107, 24 °C)

ethanol (64-17-5)	
Bioaccumulative potential	Not bioaccumulative.

methanol (67-56-1)	
BCF - Fish [1]	1 – 4.5 (72 h, Cyprinus carpio, Static system, Fresh water, Experimental value)
Partition coefficient n-octanol/water (Log Pow)	-0.77 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

acetone (67-64-1)	
BCF - Fish [1]	0.69 (Pisces, Literature study)
Partition coefficient n-octanol/water (Log Pow)	-0.23 (Test data)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

phosphoric acid, conc≥25%, aqueous solutions (7664-38-2)	
Bioaccumulative potential	Does not contain bioaccumulative component(s).

12.4. Mobility in soil

ethanol (64-17-5)	
Surface tension	22.31 mN/m (20 °C, 100 %)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.2 (log Koc, Experimental value)
Ecology - soil	Highly mobile in soil.

methanol (67-56-1)	
Mobility in soil	2.75 Source: HSDB
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	-0.89 – -0.21 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

acetone (67-64-1)	
Surface tension	23.3 mN/m (20 °C)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.374 – 0.988 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

phosphoric acid, conc≥25%, aqueous solutions (7664-38-2)	
Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the component(s) available.

12.5. Other adverse effects

Ozone : Not classified

Fluorinated greenhouse gases : No

SECTION 13 Disposal considerations

Regional waste regulation	:	Disposal must be done according to official regulations.
Waste treatment methods	:	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	:	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	:	Disposal must be done according to official regulations.
Additional information	:	Flammable vapors may accumulate in the container. Do not re-use empty containers.
Ecological waste information	:	The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

UN-No. (DOT)	:	UN2920
UN-No. (TDG)	:	UN2920
UN-No. (IMDG)	:	2920
UN-No. (IATA)	:	2920

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT)	:	Corrosive liquids, flammable, n.o.s. (phosphoric acid, ethanol, acetone)
Proper Shipping Name (TDG)	:	CORROSIVE LIQUID, FLAMMABLE, N.O.S.
Proper Shipping Name (IMDG)	:	CORROSIVE LIQUID, FLAMMABLE, N.O.S.
Proper Shipping Name (IATA)	:	Corrosive liquid, flammable, n.o.s.

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 8 (3)

Hazard labels (DOT) : 8, 3



TDG

Transport hazard class(es) (TDG) : 8 (3)

Hazard labels (TDG) : 8, 3



IMDG

Transport hazard class(es) (IMDG) : 8 (3)

Hazard labels (IMDG) : 8, 3



IATA

Transport hazard class(es) (IATA) : 8 (3)

Hazard labels (IATA) : 8, 3



14.4. Packing group

Packing group (DOT) : II
Packing group (TDG) : II
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

UN-No. (DOT) : UN2920

DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 243
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L
DOT Vessel Stowage Location : C - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 25 - Shade from radiant heat,40 - Stow "clear of living quarters"

TDG

UN-No. (TDG) : UN2920

TDG Special Provisions	:	16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the danger or dangers posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a) UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S; (b) UN1851, MEDICINE, LIQUID, TOXIC, N.O.S; (c) UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S; (d) UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e) UN3249, MEDICINE, SOLID, TOXIC, N.O.S. (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a) UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b) UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS.
Explosive Limit and Limited Quantity Index	:	1 L
Excepted quantities (TDG)	:	E2
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	:	1 L
Emergency Response Guide (ERG) Number	:	132

IMDG

Special provision (IMDG)	:	274
Limited quantities (IMDG)	:	1 L
Excepted quantities (IMDG)	:	E2
Packing instructions (IMDG)	:	P001
IBC packing instructions (IMDG)	:	IBC02
Tank instructions (IMDG)	:	T11
Tank special provisions (IMDG)	:	TP2, TP27
EmS-No. (Fire)	:	F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	:	S-C - SPILLAGE SCHEDULE Charlie - FLAMMABLE CORROSIVE LIQUIDS
Stowage category (IMDG)	:	C
Stowage and handling (IMDG)	:	SW1, SW2
Properties and observations (IMDG)	:	Causes burns to skin, eyes and mucous membranes.

IATA

PCA Excepted quantities (IATA)	:	E2
PCA Limited quantities (IATA)	:	Y840
PCA limited quantity max net quantity (IATA)	:	0.5L
PCA packing instructions (IATA)	:	851
PCA max net quantity (IATA)	:	1L
CAO packing instructions (IATA)	:	855
CAO max net quantity (IATA)	:	30L
ERG code (IATA)	:	8F

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.		
methanol	CAS-No. 67-56-1	< 1%

methanol (67-56-1)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	5000 lb

acetone (67-64-1)	
CERCLA RQ	5000 lb

phosphoric acid, conc≥25%, aqueous solutions (7664-38-2)	
CERCLA RQ	5000 lb

15.2. International regulations

CANADA

ethanol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

phosphoric acid, conc≥25%, aqueous solutions (7664-38-2)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

methanol (67-56-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

acetone (67-64-1)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

phosphoric acid, conc≥25%, aqueous solutions (7664-38-2)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. State regulations

WARNING: This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
ethanol(64-17-5)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
methanol(67-56-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List
acetone(67-64-1)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
phosphoric acid, conc≥25%, aqueous solutions(7664-38-2)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)

Issue date : 6/22/2026

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H350	May cause cancer.
H370	Causes damage to organs.

Safety Data Sheet (SDS), USA

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness

Hex Detex™ Powder B

Safety Data Sheet

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
Issue date: 7/20/2026 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form	:	Substance
Substance name	:	Hex Detex™ Powder B
CAS-No.	:	140-22-7
Product code	:	HD-2001B
Formula	:	C13H14N4O

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

No additional information available

1.4. Supplier's details

Veteran Equipment Sales, LLC
3773 E. Comstock Ave.
Nampa, Idaho 83687
United States
T 1-877-75-BLAST (25278)
info@vessystems.com - www.vessystems.com

1.5. Emergency phone number

Emergency number : 1-877-75-BLAST (25278)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

Precautionary statements (GHS US) : P261 - Avoid breathing dust, fume, gas, mist, vapors, spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective clothing, eye and face protection, protective gloves.

P302+P352 - If on skin: Wash with plenty of water.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a poison center or doctor if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P332+P313 - If skin irritation occurs: Get medical advice or attention.
P337+P313 - If eye irritation persists: Get medical advice or attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Name : Hex Detex™ Powder B
CAS-No. : 140-22-7

Name	Product identifier	Conc.	GHS US classification
1,5-diphenylcarbazide	CAS-No.: 140-22-7	100	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general : Call a poison center/doctor/physician if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.
Personal protection for first-aid responders. : First-aiders should consider self-protection and use the recommended personal protective equipment (see section 8).

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation.
Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : None under normal conditions.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : No fire hazard.
Explosion hazard : No direct explosion hazard.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Evacuate unnecessary personnel.
Environmental precautions : Avoid release to the environment.

6.2. Methods and materials for containment and cleaning up

For containment : Using a clean shovel, put the material in a dry container and cover without compressing it.
Methods for cleaning up : Mechanically recover the product.
Other information : Dispose of materials or solid residues at an authorized site.
For further information refer to section 13.

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	:	Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	:	Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
Additional hazards when processed	:	Not expected to present a significant hazard under anticipated conditions of normal use.

7.2. Conditions for safe storage, including incompatibilities

Technical measures	:	Keep in a cool, well-ventilated place away from heat.
Storage conditions	:	Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Packaging materials	:	Always store product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	:	Ensure good ventilation of the work station.
Environmental exposure controls	:	Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Hand protection:
Protective gloves
Eye protection:
Safety glasses
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	:	Solid
Color	:	No data available
Odor	:	No data available

Odor threshold	:	No data available
pH	:	No data available
Melting point	:	No data available
Freezing point	:	Not applicable
Boiling point	:	No data available
Flash point	:	Not applicable
Flammability (solid, gas)	:	Non flammable.
Vapor pressure	:	No data available
Relative vapor density at 20°C	:	No data available
Relative density	:	No data available
Solubility	:	Water: Solubility in water of component(s) of the mixture : • 1,5-diphenylcarbazide:
Partition coefficient n-octanol/water (Log Pow)	:	No data available
Auto-ignition temperature	:	Not applicable
Decomposition temperature	:	No data available
Viscosity, kinematic	:	Not applicable
Explosion limits	:	Not applicable
Particle characteristics	:	No data available

1,5-diphenylcarbazide	
Auto-ignition temperature	No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified
Skin corrosion/irritation	:	Causes skin irritation.

Serious eye damage/irritation	:	Causes serious eye irritation.
Respiratory or skin sensitization	:	Not classified
Germ cell mutagenicity	:	Not classified
Carcinogenicity	:	Not classified
Reproductive toxicity	:	Not classified
STOT-single exposure	:	May cause respiratory irritation.

1,5-diphenylcarbazide (140-22-7)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure	:	Not classified
Aspiration hazard	:	Not classified

Hex Detex™ Powder B (140-22-7)	
Viscosity, kinematic	Not applicable

Symptoms/effects after inhalation	:	May cause respiratory irritation.
Symptoms/effects after skin contact	:	Irritation.
Symptoms/effects after eye contact	:	Eye irritation.
Symptoms/effects after ingestion	:	None under normal conditions.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	:	The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short–term (acute)	:	Not classified
Hazardous to the aquatic environment, long–term (chronic)	:	Not classified

12.2. Persistence and degradability

Hex Detex™ Powder B (140-22-7)	
Persistence and degradability	Not rapidly degradable

1,5-diphenylcarbazide (140-22-7)	
Persistence and degradability	Biodegradability in water: no data available.

12.3. Bioaccumulative potential

1,5-diphenylcarbazide (140-22-7)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	:	Not classified
Fluorinated greenhouse gases	:	No

SECTION 13 Disposal considerations

Regional waste regulation	:	Disposal must be done according to official regulations.

Waste treatment methods	:	Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	:	Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	:	Comply with applicable regulations for solid waste disposal. Disposal must be done according to official regulations.
Additional information	:	Do not re-use empty containers.
Ecological waste information	:	The waste of the product should be considered as hazardous as the product itself, with the likelihood of impacting the environment in the same way. Consider the handling and disposal of the waste as defined by the product itself.

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN number

Not regulated for transport

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT)	:	Not regulated
Proper Shipping Name (TDG)	:	Not regulated
Proper Shipping Name (IMDG)	:	Not regulated
Proper Shipping Name (IATA)	:	Not regulated

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : Not regulated

TDG

Transport hazard class(es) (TDG) : Not regulated

IMDG

Transport hazard class(es) (IMDG) : Not regulated

IATA

Transport hazard class(es) (IATA) : Not regulated

14.4. Packing group

Packing group (DOT)	:	Not regulated
Packing group (TDG)	:	Not regulated
Packing group (IMDG)	:	Not regulated
Packing group (IATA)	:	Not regulated

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT

Not regulated

TDG

Not regulated

IMDG

Not regulated

IATA

Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:		
1,5-diphenylcarbazide	CAS-No. 140-22-7	100%

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other information

according to 29 CFR § 1910.1200, Hazard Communication Standard (HCS 2024)
Issue date : 7/20/2026

Full text of hazard classes and H-statements	
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation

Safety Data Sheet (SDS), USA

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness