

### SAFETY DATA SHEET

Product Name      ULTRA FLEX

#### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier name      AUSTRALIAN MEMBRANE INDUSTRIES PTY LTD  
Address      PO Box 242, Glenorie, NSW, 2157, AUSTRALIA  
Telephone      1800 099 990  
Fax      (02) 9652 0411  
Emergency      1800 099 990  
Email      [info@membraneindustries.com.au](mailto:info@membraneindustries.com.au)  
Web site      [www.membraneindustries.com.au](http://www.membraneindustries.com.au)  
Synonym(s)      ULTRAFLEX  
Use(s)      COATING • MEMBRANE COATING • WATER PROOFING  
SDS date      16 NOVEMBER 2024

#### 2. HAZARDS IDENTIFICATION

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Risk Phrases  
None allocated

Safety Phrases  
None allocated

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN Number	None Allocated	Transport Hazard Class	None Allocated
Packing Group	None Allocated	Hazchem Code	None Allocated

#### 3. COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredient	Identification	Classification	Content
STYRENE - ACRYLIC COPOLYMER	Not Available	Not Available	60 to 70%
NONIONIC POLYURETHANE DISPERSION	Not Available	Not Available	15 to 25%
FILLER(S)	Not Available	Not Available	10 to 15%
BACTERICIDE	Not Available	Not Available	Not Available
COALESCING AGENT	Not Available	Not Available	Not Available
COLOURING AGENT(S)	Not Available	Not Available	Not Available
DEFOAMER(S)	Not Available	Not Available	Not Available
THICKENER(S)	Not Available	Not Available	Not Available
WATER	CAS: 7732-18-5 EC: 231-791-2	Not Available	Not Available

#### 4. FIRST AID MEASURES

Eye      If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

**Product Name** ULTRA FLEX

**Inhalation** If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.

**Skin** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

**Ingestion** For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

**Advice to doctor** Treat symptomatically.

### 5. FIRE FIGHTING MEASURES

**Flammability** Non flammable. May evolve carbon oxides and hydrocarbons when heated to decomposition.

**Fire and explosion** Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

**Extinguishing** Use an extinguishing agent suitable for the surrounding fire.

**Hazchem code** None Allocated

### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions** Wear Personal Protective Equipment (PPE) as detailed in Section 8.

**Environmental precautions** Prevent product from entering drains and waterways.

**Methods of cleaning up** Contain spillage, then cover/absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

**References** See Sections 8 and 13 for exposure controls and disposal.

### 7. STORAGE AND HANDLING

**Storage** Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should have appropriate ventilation systems.

**Handling** Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure standards** No exposure standard(s) allocated.

**Biological limits** No biological limit allocated.

**Engineering controls** Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.

**PPE**

**Eye / Face** Wear splash-proof goggles.

**Hands** Wear PVC or rubber gloves.

**Body** When using large quantities or where heavy contamination is likely, wear coveralls.

**Respiratory** Where an inhalation risk exists, wear a Type A (Organic vapour) respirator.



Product Name      ULTRA FLEX

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	VISCOUS LIGHT GREY, BROWN OR SANDSTONE COLOURED LIQUID
Odour	ODOURLESS
Flammability	NON FLAMMABLE
Flash point	NOT RELEVANT
Boiling point	100°C
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	9.0
Vapour density	NOT AVAILABLE
Specific gravity	1.04 (Approximately)
Solubility (water)	NOT AVAILABLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT RELEVANT
Lower explosion limit	NOT RELEVANT
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE
Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE
% Volatiles	20 % to 30 % (Water)

### 10. STABILITY AND REACTIVITY

Chemical stability	Stable under recommended conditions of storage.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources.
Material to avoid	Incompatible with oxidising agents (eg. hypochlorites) and acids (eg. nitric acid).
Hazardous Decomposition Products	May evolve carbon oxides and hydrocarbons when heated to decomposition.
Hazardous Reactions	Hazardous polymerization is not expected to occur.

### 11. TOXICOLOGICAL INFORMATION

Health Hazard Summary	Low toxicity - low irritant. Use safe work practices to avoid eye or skin contact and inhalation. This product may contain trace amounts of residual acrylic and styrene monomers, however due to the very low levels present, adverse health effects are not anticipated with normal use.
Eye	Low to moderate irritant. Contact may result in irritation, lacrimation, pain and redness.
Inhalation	Low to moderate irritant. Over exposure to vapours may result in irritation of the nose and throat, with coughing. High level exposure may result in dizziness, nausea and headache. Due to the low vapour pressure, an inhalation hazard is not anticipated with normal use.
Skin	Low irritant. Prolonged or repeated contact may result in mild irritation, rash and dermatitis.
Ingestion	Low toxicity. Ingestion may result in gastrointestinal irritation, nausea, vomiting, headache and diarrhoea.
Toxicity data	No LD50 data available for this product.

### 12. ECOLOGICAL INFORMATION

Toxicity	No information provided.
Persistence and degradability	No information provided.
Bioaccumulative potential	No information provided.
Mobility in soil	No information provided.
Other adverse effects	No information provided.

Product Name      ULTRA FLEX

### 13. DISPOSAL CONSIDERATIONS

**Waste disposal**      For small amounts absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer for additional information if larger amounts are involved. Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.

**Legislation**      Dispose of in accordance with relevant local legislation.

### 14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
UN Number	None Allocated	None Allocated	None Allocated
Proper Shipping Name	None Allocated	None Allocated	None Allocated
Transport Hazard Class	None Allocated	None Allocated	None Allocated
Packing Group	None Allocated	None Allocated	None Allocated

**Environmental hazards**      No information provided

**Special precautions for user**

**Hazchem code**      None Allocated

### 15. REGULATORY INFORMATION

**Poison schedule**      A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Inventory Listing(s)**      **AUSTRALIA: AICS (Australian Inventory of Chemical Substances)**  
All components are listed on AICS, or are exempt.

### 16. OTHER INFORMATION

**Additional information**      **ACRYLIC - WATER BASED COMPOUNDS:** It should be noted that most water based paints and acrylic or thermoplastic resins may contain small percentage of solvents, usually less than 5%. The solvent is used as a dispersion agent for the resin of choice. This solvent component may present potential respiratory hazards only in poorly ventilated areas or when sprayed. Those individuals with existing skin disorders should avoid direct contact.

**WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT:** If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (eg. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.

**STYRENE-ACRYLIC RESINS:** These polymeric materials may contain traces of styrene monomer. Over exposure to styrene monomer may result in styrene sickness. Chronic exposure is reported to cause nerve damage-peripheral neuropathy. Styrene is reported to cause reproductive abnormalities and teratogenicity in experimental animals. Styrene is classified as possibly carcinogenic to humans (IARC Group 2B), however due to the very low concentrations present, adverse health effects are not anticipated.

**RESPIRATORS:** In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.



**Product Name** ULTRA FLEX

### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

### Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
GHS	Globally Harmonized System
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
REACH	Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

### Revision history

Revision	Description
1.0	Initial SDS Creation
0.1	Standard SDS Review

### Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ("SDS").

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

### Prepared by

AMI wp Pty, Ltd/

Revision: 1

SDS Date: 16 November 2024

**End of SDS**