





GAS DRIVEN, OIL FIRED SELF CONTAINED PRESSURE WASHER | Specifications:

GENERAL					ENGINE/BURNER SYSTEM						DIMENSIONS/WEIGHT			
Model	GPM	PSI	НР	Drive	Volt	Engine	Engine Start	Fuel Engine/ Burner	вти	Stack Size	L	w	н	Lb
42-430H / 42-430GH	4	3000	13	Belt	12/110	Honda	Electric	Gas/Oil	384,000	8"	43"	34"	43"	725/850
42-430H-C / 42430GH-C	4	3000	13	Clutch	12/110	Honda	Electric	Gas/Oil	384,000	8"	43"	34"	43"	740/865
42-440V / 42-440GV	4	4000	16	Belt	12/110	Vanguard	Electric	Gas/Oil	384,000	8"	43"	34"	43"	750/850
42-440H / 42-440GH	4	4000	20	Belt	12/110	Honda	Electric	Gas/Oil	384,000	8"	43"	34"	43"	750/850
42-530V / 42-530GV	5	3000	16	Belt	12/110	Vanguard	Electric	Gas/Oil	465,000	8"	43"	34"	43"	750/820
42-530V-C / 42-530GV-C	5	3000	16	Clutch	12/110	Vanguard	Electric	Gas/Oil	465,000	8"	43"	34"	43"	765/835
42-535H / 42-535GH	5	3500	20	Belt	12/110	Honda	Electric	Gas/Oil	465,000	8"	43"	34"	43"	800/865
42-530H-C / 42-530GH-C	5	3000	20	Clutch	12/110	Honda	Electric	Gas/Oil	465,000	8"	43"	34"	43"	815/880
42-830V / 42-830GV	8	3000	23	Belt	12/110	Vanguard	Electric	Gas/Oil	547,000	8"	43"	34"	43"	1015/1080
42-830V-C / 42-830GV-C	8	3000	23	Clutch	12/110	Vanguard	Electric	Gas/Oil	547,000	8"	43"	34"	43"	1015/1080

Features (not shown on breakout):

- · Quick Couple Stainless Steel Nozzles
- ASTM A53 Schedule 80 Steel Heating Coil
- Trigger Gun Control
- Variable Pressure Wand (42-430/42-530)
- · Wire Braid Discharge Hose
- · Low Oil Engine Protection
- · Water Separating Fuel Filter
- · Low Water Shutoff Protection
- Automatic Electric Burner Ignition

- Extended Engine Oil Drain (Vanguard)
- Auxiliary Gasoline Tank (42-440/42-530/42-830)
- · Shock Mount Plastic Battery Box
- · Stainless Steel Control Panel

12V H Models

- · High Amp Charging System
- 12V Ignition System
- · Downstream Chemical Injection

110V GH Models

- Calibrated Detergent Mixing Valve
- · High Pressure Soap
- · Circuit Breaker Protected
- · Stainless Steel Float Tank



A Closer Look at the Features:



Hour Meter Allows you to keep track for periodic maintenance.



Adjustable Temp. Control For your precise temp. control.



Electric Start Allows for quick & easy operation without pull cord strain



Vanguard/ Honda Engines
Time proven
dependability.



Shock Absorbing Engine Base Dampens vibrations reducing engine & frame fatigue, prolonging life.







Industrial Strength Triplex Built strong to handle the toughest demands.



Optional Clutch Drive Save money by lengthening the life of your





High Efficiency Burner Conserve fuel & your dollars.

durable protection.

Durable Powder Coated
Heavy Duty Roll Cage
Frame
For years of great looking

service & protecting the unit's internal parts.

Exclusive

Coil Design Heats water quicker & more

Combustion Chamber & Side Panels Maintenance free,

efficiently Stainless Steel





Notes:

Configured for you by:



2928 Washington Ave • Clearfield, PA 16830 1-800-664-5697 • info@hsws.net www.hydro-spray.net