

## Clear FLO Reverse Osmosis Systems



WALL MOUNT



FREE STANDING

### Clear FLO Reverse Osmosis Systems

In today's economy the consumer expectation is at an all-time high. As a car wash operator, you know the importance of good water quality. So, no matter how good your city water is it still contains TDS (total dissolved solids) which creates spots on glass and painted surfaces of the vehicle resulting in a poor wash quality. Clear FLO RO Systems are designed to efficiently remove the TDS from the softened city water resulting in a spot free wash and happy customers who will return.

## Clear FLO Reverse Osmosis Systems Wall Mount



Model	Production (gpd)	Recovery	Supply Flow (Feed Water) (gpm/lpm)	Permeate Flow (Product) (gpm/lpm)	Concentrate Flow (Reject) (gpm/lpm)	Pump HP	Membrane Qty	Inlet (FPT)	Permeate Outlet (MPT)	Concentrate Outlet MPT	Width	Depth	Height	Shipping Weight (lbs)
DWM-1800	1800	60%	2.1 / 7.9	1.3 / 4.7	0.9 / 3.2	1/2	1	3/4	1/2	1/2	21.5"	13.5"	48"	150
DWM-2400	2400	60%	2.8 / 10.7	1.7 / 6.4	1.1 / 4.2	3/4	1	3/4	1/2	1/2	21.5"	13.5"	48"	150
DWM-4800	4800	70%	4.9 / 18.4	3.4 / 12.9	1.5 / 5.7	3/4	2	3/4	1/2	1/2	21.5"	13.5"	48"	160
DWM-7200	7200	75%	6.8 / 25.7	5.1 / 19.3	1.7 / 6.4	1 1/2	3	3/4	1	1/2	21.5"	13.5"	48"	161

## Free Standing



Model	Production (gpd)	Recovery	Supply Flow (Feed Water) (gpm/lpm)	Permeate Flow (Product) (gpm/lpm)	Concentrate Flow (Reject) (gpm/lpm)	Pump HP	Membrane Qty	Inlet (FPT)	Permeate Outlet (MPT)	Concentrate Outlet MPT	Width	Depth	Height	Shipping Weight (lbs)
DFS-1800	1800	60%	2.1 / 7.9	1.3 / 4.7	0.9 / 3.2	1/2	1	3/4	1/2	1/2	25"	26"	68"	160
DFS-2400	2400	60%	2.8 / 10.7	1.7 / 6.4	1.1 / 4.2	3/4	1	3/4	1/2	1/2	25"	26"	68"	160
DFS-4800	4800	70%	4.9 / 18.4	3.4 / 12.9	1.5 / 5.7	3/4	2	3/4	1/2	1/2	25"	26"	68"	180
DFS-7200	7200	75%	6.8 / 25.7	5.1 / 19.3	1.7 / 6.4	1 1/2	3	3/4	1	1/2	25"	26"	68"	210
DFS-9600	9600	75%	9.0 / 34.1	6.8 / 25.7	2.2 / 8.3	1 1/2	4	1	1	1/2	25"	32"	72"	230
DFS-12000	12000	75%	11.1 / 42.1	8.3 / 31.4	2.8 / 10.6	2	5	1	1	1	25"	32"	72"	255
DFS-14400	14400	75%	13.3 / 50.3	10 / 37.8	3.3 / 12.5	2	6	1	1	1	25"	32"	72"	275
DFS-18000	18000	75%	16.7 / 63.2	12.5 / 47.3	4.2 / 15.9	3	8	1	1	1	36"	32"	75"	375

### Features

- Powder Coated Frame
- Pre-Wired for Single Phase & Three Phase Applications
- Hinge Design on Wall Mount Units
- Self-Diagnostic Controller w/Reset
- Panel Mount Gauges
- Panel Mount Flow Meters
- Automatic Membrane Flush
- High Level Cut Off Switch
- Auto Restart
- Carbon Membrane Housing(s)
- Sediment Pre-Filter
- Back Washing Carbon Filter
- Fresh Water By-Pass and High-Level Float Switch

### Options

- Capacities from 1,800-18,000 GPD
- Clear FLO Digital Controller
- Re-Pressurization Pump(s)
- Multi-Bay Flow Control
- Storage Tanks
- Low Water Cut Off Switch
- Stainless Steel Membrane Housing(s) and Casters for Free Standing Models