

PVC SPECIALITY CEMENTS

TECHNICAL SPECIFICATIONS

**POOL
SPA
&
IRRIGATION**

639 Sovereign Road Unit 3, London Ontario, Canada N5V 4K8

P. (519) 268-1190

E. info@plascowelding.com

PVC Speciality Cements
Technical Specifications

PVC-21 BLUE
TECHNICAL SPECIFICATIONS
Low VOC PVC Solvent Cement



PRODUCT:

Spears® PVC-21 Blue is a medium bodied, fast setting, high strength PVC cement. It is suitable for use on rigid PVC with interference fit Schedule 40 thru 6" and Schedule 80 thru 4".

ALTERNATIVE TO IPS 721 & CHRISTY'S RED HOT BLUE GLUE

INTENDED USE:

PVC-21 Can be used without primer on PVC Schedule 40 and SDR pressure water piping systems through 4" if local code permits. Do not use PVC-21 without primer in any other application, schedule, or size such as Schedule 80 industrial applications.

CONFORMANCE STANDARDS AND APPROVALS:

- NSF®/ANSI Standard 14 Listed and Certified for compliance to ASTM D2564
- NSF®/ANSI Standards 14/61 Listed and Certified for Potable Water, Drain Waste and Vent, and Sewer service use (NSF®-PW, DWV, SW) NSF® Listed and Certified to requirements of the Uniform Plumbing Code (NSF® U.P. Code); NSF® Certified Lead-Free.
- Meets SCAQMD Rule 1168/316A for Compliance with LEED® (Leadership in Energy and Environmental Design). Low VOC product credit can be claimed for LEED® Rating System.
- PVC-21 cement has achieved GREENGUARD GOLD Certification to Underwriters Laboratories (UL) 2818. UL GREENGUARD GOLD Certification allows for LEED® (Leadership in Energy and Environmental Design) credit eligibility.

PACKAGING- Sold by CASE QUANTITY only

<u>Can Size</u>	<u>Standard Case Quantity</u>
1/4 Pint	24
1/2 Pint	24
Pint	12
Quart	12
Gallon	6

PVC Speciality
Technical Specifications

PVC-25 AQUA BLUE WET-N-DRY

TECHNICAL SPECIFICATIONS
Low VOC PVC Solvent Cement



PRODUCT:

Spears® PVC-25 AQUA BLUE WET-N-DRY: (will fade to CLEAR in sunlight) is medium bodied, very fast setting PVC cement for all classes and schedules with interference fit through 6" diameter and Schedule 80 through 4" diameter.

INTENDED USE:

PVC-25 AQUA BLUE WET-N-DRY is formulated for wet conditions and quick pressurization. Designed for irrigation, plumbing, and pool & spa applications. Can be used without primer on non-pressure systems if local code permits.

ALTERNATIVE TO IPS 725 & CHRISTY'S RED HOT BLUE GLUE

CONFORMANCE STANDARDS AND APPROVALS:

- NSF®/ANSI Standard 14 Listed and Certified for compliance to ASTM D2564.
- NSF®/ANSI Standards 14/61 Listed and Certified for Potable Water, Drain Waste and Vent, and Sewer service use (NSF®-PW, DWV, SW) NSF® Listed and Certified to requirements of the Uniform Plumbing Code (NSF® U.P. Code); NSF® Certified Lead-Free.
- Meets SCAQMD Rule 1168/316A for Compliance with LEED® (Leadership in Energy and Environmental Design). Low VOC product credit can be claimed for LEED® Rating System.
- PVC-25 cement has achieved GREENGUARD GOLD Certification to Underwriters Laboratories (UL) 2818. UL GREENGUARD GOLD Certification allows for LEED® (Leadership in Energy and Environmental Design) credit eligibility.

PACKAGING- Sold by CASE QUANTITY only

<u>Can Size</u>	<u>Standard Case Quantity</u>
1/4 Pint	24
1/2 Pint	24
Pint	12
Quart	12
Gallon	6

PVC Speciality
Technical Specifications

PVC-26 Pool-Pro™ BLUE
TECHNICAL SPECIFICATIONS
Low VOC PVC Solvent Cement



PRODUCT:

Spears® PVC-26 Pool-Pro™ Blue (will fade to CLEAR in sunlight) is medium bodied, very fast setting PVC cement for all classes and schedules with interference fit through 6" diameter and Schedule 80 through 4" diameter.

ALTERNATIVE TO IPS 726

INTENDED USE:

PVC-26 Pool-Pro™ is specially formulated for pool maintenance and repair - wet or quick pressurization conditions. Can be used without primer on non-pressure systems if local code permits.

CONFORMANCE STANDARDS AND APPROVALS:

- NSF®/ANSI Standard 14 Listed and Certified for compliance to ASTM D2564
- NSF®/ANSI Standards 14/61 Listed and Certified for Potable Water, Drain Waste and Vent, and Sewer service use (NSF®-PW, DWV, SW) NSF® Listed and Certified to requirements of the Uniform Plumbing Code (NSF® U.P. Code); NSF® Certified Lead-Free.
- Meets SCAQMD Rule 1168/316A for Compliance with LEED® (Leadership in Energy and Environmental Design). Low VOC product credit can be claimed for LEED® Rating System.
- PVC-26 cement has achieved GREENGUARD GOLD Certification to Underwriters Laboratories (UL) 2818. UL GREENGUARD GOLD Certification allows for LEED® (Leadership in Energy and Environmental Design) credit eligibility.

PACKAGING- Sold by CASE QUANTITY only

<u>Can Size</u>	<u>Standard Case Quantity</u>
1/4 Pint	24
1/2 Pint	24
Pint	12
Quart	12
Gallon	6

PVC Speciality
Technical Specifications

PVC-95 Flexible CLEAR/BLUE

TECHNICAL SPECIFICATIONS Low VOC PVC Solvent Cement



PRODUCT:

Spears® PVC-95 Flexible CLEAR/BLUE is: Medium bodied, fast setting PVC cement specially formulated for use on flex-to-flex and flex-to-rigid PVC connections with interference fit through 6" and Schedule 80 through 3".

ALTERNATIVE TO IPS 795

INTENDED USE:

PVC-95 Flexible is specially formulated for use on flex-to-flex and flex-to-rigid PVC connections to maintain high-strength, flexible joints.

CONFORMANCE STANDARDS AND APPROVALS:

- NSF®/ANSI Standard 14 Listed and Certified for compliance to ASTM D2564
- NSF®/ANSI Standards 14/61 Listed and Certified for Potable Water, Drain Waste and Vent, and Sewer service use (NSF®-PW, DWV, SW) NSF® Listed and Certified to requirements of the Uniform Plumbing Code (NSF® U.P. Code); NSF® Certified Lead-Free.
- Meets SCAQMD Rule 1168/316A for Compliance with LEED® (Leadership in Energy and Environmental Design). Low VOC product credit can be claimed for LEED® Rating System.
- PVC-95 cement has achieved GREENGUARD GOLD Certification to Underwriters Laboratories (UL) 2818. UL GREENGUARD GOLD Certification allows for LEED® (Leadership in Energy and Environmental Design) credit eligibility.

PACKAGING- Sold by CASE QUANTITY only

<u>Can Size</u>	<u>Standard Case Quantity</u>
1/4 Pint	24
1/2 Pint	24
Pint	12
Quart	12
Gallon	6