



SPEARS

Hard to Find Pool & Spa Fittings

Plasco Welding & Fabrication Inc. | 639 Sovereign Road, Unit 3, London, ON

Phone: 519 - 268 -1190 | Email: info@plascowelding.com



All Pool & Spa Specialty Fittings have a maximum use service pressure of 150 psi @ 73° F (22° C). Standard pressure de-ratings must be applied for use at elevated temperatures with a maximum service temperature of 140°F (60° C).

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Short Socket Tees

Socket Style Sch 40

Special short-socket end allows close connection at pumps, filters and other areas with minimum available space.

S401-249	2X2X1	25	0	015	17.34
S401-251	2x2x1-1/2	25	0	015	17.34



Male Thread Tee (Branch)

Socket x Socket x Mipt

402B-010	1	50	0	040	7.58
----------	---	----	---	-----	------



Spigot Tee, 2"

Spigot x Spigot x Spigot Sch 40

404A-020	2	30	0	040	18.08
----------	---	----	---	-----	-------



90° Ell, 2"x1-1/2" Reducing, Socket/Spigot

2"x2" 90° Street Ell, Socket x Spigot Sch 40

Handy dual-purpose configuration is 2"x1-1/2" Socket Reducing 90° Ell and also a 2" Socket x 2" Spigot 90° Street Ell.

406-251N	2X1-1/2	10	0	015	21.77
----------	---------	----	---	-----	-------



90° Ell 2-1/2"x2" Reducing Socket/Spigot

2-1/2"x2-1/2" 90° Street Ell, Socket x Spigot Sch 40

Handy dual-purpose configuration is 2-1/2" x 2" Socket Reducing 90° Ell and also a 2-1/2" Socket x 2-1/2" Spigot 90° Street Ell.

406-292N	2-1/2X2 (2-1/2 Spigot)	10	0	040	25.49
----------	------------------------	----	---	-----	-------



90° Spigot Ell, 1-1/2"

Spigot x Spigot Sch 40

422-015	1-1/2	25	0	015	17.46
---------	-------	----	---	-----	-------



45° Street Ell -Short Spigot

Spigot x Socket Sch 40

Special short-spigot end allows close connection in extra-tight spaces.

S427-020	2	10	0	015	15.43
----------	---	----	---	-----	-------



45° Street Ell

Spigot x Socket

427-005	1/2	50	400	040	2.34
427-007	3/4	50	0	040	3.64
427-010	1	50	0	040	4.34
427-012	1-1/4	25	0	040	6.07
427-015	1-1/2	25	0	040	7.58
427-020	2	25	0	040	9.93
427-025	2-1/2	10	0	040	32.31
427-030	3	10	0	040	40.11
427-040	4	5	0	040	71.89
427-050	5	4	0	040	216.14
427-060	6	4	0	040	222.03
427-080	8	2	0	040	534.03
427-100	10	1	0	041	1405.18
427-120	12	1	0	041	2060.12
427-140F	14	1	0	047	1535.36
427-160F	16	1	0	047	2086.87
427-180F	18	1	0	047	2278.02
427-200F	20	1	0	047	2891.48
427-240F	24	1	0	047	4554.66



22-1/2° Street Ell

Spigot x Socket

442-005	1/2	50	400	040	3.31
442-007	3/4	50	0	040	5.15
442-010	1	50	0	040	6.18
442-012	1-1/4	20	0	040	8.64
442-015	1-1/2	25	0	040	10.86
442-020	2	20	0	040	14.22
442-025F	2-1/2	1	18	047	80.33
442-030	3	5	0	040	82.86
442-040	4	4	0	040	127.92
442-060	6	4	0	040	315.78
442-060F	6	1	5	047	186.34
442-080	8	1	4	040	759.55
442-080F	8	1	4	047	280.69





Schedule 40 Fittings Product

Pool & Spa Fittings

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

22-1/2° Street Ell (continued)

Spigot x Socket

442-100F	10	1	0	047	434.35
442-120F	12	1	0	047	652.00

Grated Coupling, 2" Sch 40

Socket Style Sch 40

Specially designed internal grate at pipe stop gives extra protection to pumps, filters and equipment from damaging gravel and debris.

429GR-020	2	25	0	015	9.52
-----------	---	----	---	-----	------

Smooth Barb Adapter

Spigot x Smooth Barb

Special adapter for making connections to Flexible Vinyl Hose

432-007525	3/4X1/2	100	600	015	4.08
432-007775	3/4	50	600	015	6.52
432-010775N	1(3/4)X3/4	50	400	015	6.82

"N" suffix indicates Nesting - Spigot also serves as size smaller socket

Venturied Tee, Multi Configuration - Socket Style Sch 40

1-1/2" Socket (2" Spigot) x 1-1/2" Socket x 3/4" Socket (1" Spigot)

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-210	with 7/16" Nozzle	25	0	015	17.19
473-210-1/4	with 1/4" Nozzle	25	0	015	17.19
473-210-3/8	with 3/8" Nozzle	25	0	015	17.19

Venturied Tee, Multi Configuration - Socket Style Sch 40

1" Socket x 3/4" Socket (1" Spigot) x 3/4" Socket (1" Spigot)

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-825	with 7/16" Nozzle	50	0	015	14.02
473-825-3/8	with 3/8" Nozzle	50	0	015	14.02
473-825-1/4	with 1/4" Nozzle	50	0	015	14.02

Venturied Tee, Multi Configuration - Socket Style Sch 40

Individual Nozzles Only

Special spa jet fitting with standard 7/16" nozzle plus optional 3/8" or 1/4".

473-1	7/16" Nozzle	100	600	015	4.53
473-2	1/4" Nozzle	100	600	015	4.53

Part Number	Size	Std Pk	Mstr Ctn	Prod Code	MSRP
-------------	------	--------	----------	-----------	------

Venturied Tee, Multi Configuration - Socket Style Sch 40

(continued)

Individual Nozzles Only

473-3	3/8" Nozzle	100	600	015	4.53
-------	-------------	-----	-----	-----	------

120° Wye, 1-1/2"x1"x1"

Spigot x Socket x Socket Sch 40

Unique spigot end take off with 120° branched wye pattern for special distribution connections.

475-21131T	1-1/2X1X1	25	0	015	24.48
------------	-----------	----	---	-----	-------

120° Wye, 2"

Socket

475-020120	2	10	0	015	28.71
------------	---	----	---	-----	-------

Nesting Union

2" Socket x 1-1/2" Socket (2" Spigot) Buna-N O-ring

235 psi @ 73°F (23°C)

8057-251W	2X1-1/2 (2)	5	0	080	136.33
-----------	-------------	---	---	-----	--------

Nesting Union

2" Socket x 1-1/2" Socket (2" Spigot) EPDM O-ring

235 psi @ 73°F (23°C)

8097-251W	2X1-1/2 (2)	5	0	080	160.45
-----------	-------------	---	---	-----	--------