

Auto Backup Kit

BUK1-RJ/M12/USB

Auto Backup Kit for CTC Managed Switch with RJ45/M12/USB Connector

- ◆ RS232 RJ45 Type Console Connection (BUK1-RJ)
- ◆ RS232 M12 Type Console Connection (BUK1-M12)
- ◆ USB Type C Console Connection (BUK1-USB)
- ◆ Powered by USB
- ◆ Plug & Play Operation
- ◆ Supports CTC Managed Switch for Auto Backup and Restore Configuration



The automatic backup configuration kit - BUK1 series is designed to save, download and upload the setup configurations of CTC managed Ethernet switches series through the RS-232 or USB console port. Easily back up or restore the Ethernet switch's system parameters and configuration by simply pressing a button on the BUK1. it is a greatly simplified design that enhances network deployment and maintenance processes, thereby reducing system downtime and costs.

Features

- Push button for start to upload/download configuration
- DIP SW for upload/download configuration selection


Specifications

DIP SW	DIP 1	OFF: Upload Configuration ON : Download Configuration
	DIP 2	OFF: USB-A ON : USB-C
Push Button	Start to process	Press the button to start the configuration upload/download process
Connector	1x RJ45 RS232	With RJ45-to-RJ45 (Pin to Pin) cable for RJ45 console managed switch (BUK1-RJ) With RJ45-to-M12 cable for M12 console managed switch (BUK1-M12)
	1x USB	With USB Type A to USB Type C cable for USB console managed switch (BUK1-USB)
LED	Power	ON: Power On (Green) Blinking: Process (Green)
	Status	ON: Process Success (Green) Blinking: Device Not Match (Red) ON: Fail (Red)
Power Supply	Powered by USB Type C	
Operating Temperature	-10 ~ 60°C	
Operating Humidity	5% to 95% (Non-condensing)	
Storage Temperature	-40 ~ 85°C	
Housing	Rugged Metal, IP30 Protection and Fanless	
Dimensions	30 x 72 x 26mm (D x W x H)	
Weight	TBD	

MTBF TBD (MIL-HDBK-217)

Certification

EMC/EMS	CE (EN55032, EN55035)
EMI (Electromagnetic Interference)	FCC Part 15 Subpart B Class A, CE
EMS (Electromagnetic Susceptibility) Protection Level	EN61000-4-2 (ESD) Level 3, Criteria B EN61000-4-3 (RS) Level 3, Criteria A EN61000-4-4 (Burst) Level 3, Criteria A EN61000-4-5 (Surge) Level 3, Criteria B EN61000-4-6 (CS) Level 3, Criteria A EN61000-4-8 (PFMF, Magnetic Field) Field Strength: 300A/m, Criteria A

Dimensions**Ordering Information**

Model Name	Connector for Switch Console	Push Button	DIP SW	Power	Certification	Operating Temperature
	Port	Cable	Power / Start	Upload/ Download	Powered by USB	
BUK1-RJ	RJ45	RJ45 to RJ45	1	1	Type C	V -10 ~ 60°C
BUK1-M12	RJ45	RJ45 to M12	1	1	Type C	V -10 ~ 60°C
BUK1-USB	USB Type A	USB Type A to USB Type C	1	1	Type C	V -10 ~ 60°C

Package List**BUK1-RJ**

- 1x BUK1 device
- 1x RJ45-to-RJ45 pin-to-pin Cable 30cm

BUK1-M12

- 1x BUK1 device
- 1x RJ45-to-M12 Cable 30cm

BUK1-USB

- 1x BUK1 device
- USB Type A to USB Type C Cable 30cm