



IGR-2408SM-24PH

Industrial Layer 3 GbE PoE Switch

L3 24x GbE RJ45 + 8x 100/1000Base-X SFP with 24x PoE 400W 48VDC

- » VRRP v2/v3, L3 IPV4/IPV6 Static Routing, RIP v1/v2 Dynamic Routing, OSPF v2/v3 Dynamic Routing
- » Supports IEEE 1588 PTP V2
- » Supports u-Ring, ERPS, EPS, MSTP, RSTP, STP for Redundant Cabling
- » EN62368-1, EN50121-4, EN61000-6-2/4, CE and FCC Certified
- » 4KV Surge Protection for PoE, RJ45 and SFP Ports



As an Industrial grade Layer 3 Ethernet switch, the IGR-2408SM-24PH provides full Gigabit capability with high performance and the ability to quickly transfer large amounts of video, voice, and data across a network. IGR series has 8x Gigabit SFP slots and 24x Gigabit RJ45 Ethernet ports with PoE. They support Layer 3 routing function, ERPS ring, RSTP/STP and u-Ring redundancy technologies, support wide operating temperature, fanless design, to increase system reliability and the availability of your network.

Features

- Maximum up to 24x IEEE 802.3af / 802.3at PoE+ output, 30W per port, 400W PoE power budget in total
- Redundant dual input power 48VDC (44~57VDC)
- STP, RSTP, MSTP, ITU-T G.8032 Ethernet Ring Protection Switching (ERPS) for network redundancy
- Provides 14 instances each can support u-Ring, u-Chain or Sub-Ring for flexible networking applications
- u-Ring redundancy, recovery time <20ms in 250 devices
- Supports IEEE 1588 PTP V2 for precise time synchronization to operate in Ordinary-Boundary, Peer to Peer Transparent Clock, End to End Transparent Clock, Master, Slave mode by each port
- Supported EMS Management

Specifications

Standard		
IEEE 802.3	10Base-T 10Mbit/s Ethernet	
IEEE 802.3u	100Base-TX, 100Base-FX, Fast Ethernet	
IEEE 802.3ab	1000Base-T Gbit/s Ethernet over twisted pair	
IEEE 802.3z	1000Base-X Gbit/s Ethernet over Fiber-Optic	
IEEE 802.1d	STP (Spanning Tree Protocol)	
IEEE 802.1w	RSTP (Rapid Spanning Tree Protocol)	
IEEE 802.1s	MSTP (Multiple Spanning Tree Protocol)	
ITU-T G.8032 / Y.1344	ERPS (Ethernet Ring Protection Switching)	
ITU-T G.8031 / Y.1342	EPS (Ethernet Protection Switching)	
IEEE 802.1Q	Virtual LANs (VLAN)	
IEEE 802.1X	Port based and MAC based Network Access Control, Authentication	
IEEE 802.3ac	Max frame size extended to 1522Bytes	
IEEE 802.3ad	Link aggregation for parallel links with LACP (Link Aggregation Control Protocol)	
IEEE 802.3af	PoE (Power over Ethernet)	
IEEE 802.3at	PoE+ (Power over Ethernet enhancement)	
IEEE 802.3X	Flow control for full duplex	
IEEE 802.1ad	Stacked VLANs, Q-in-Q	
IEEE 802.1p	LAN Layer 2 QoS/CoS Protocol for Traffic Prioritization	
IEEE 802.1ab	Link Layer Discovery Protocol (LLDP)	
IEEE 802.3az	EEE (Energy Efficient Ethernet)	



VLAN ID	4094 IEEE802.1Q VLAN ID
Switch Architecture	Back-plane (Switching Fabric): 64Gbps (Full wire-speed)
Data Processing	Store and Forward
Network Connector	SFP: 8x 100/1000Base-X SFP socket, Support DDMI RJ45: 24x 10/100/1000Base-T RJ-45, Support Auto negotiation speed, Auto MDI/MDI-X function PoE: 24x IEEE 802.3af /IEEE 802.3at PoE+, End-Span, Alternative A mode. Maximum 30W per port, 400W PoE power budget in total RJ45 Pin Assignment: PoE Positive (V+) : RJ-45 pin 1, 2. PoE Negative (V-) : RJ-45 pin 3, 6. Data (1, 2, 3, 6, 4, 5, 7, 8)
Console	RS-232 (RJ-45)
Network Cable	UTP/STP Cat.5e cable or above EIA/TIA-568 100-ohm (100meter)
Protocols	CSMA/CD
Reverse Polarity Protection	For input power
Overload Current Protection	Supported
Power Supply	Redundant dual input power 48VDC (44~57VDC) (Removable terminal block) (50~57VDC input is recommended for IEEE802.3at PoE+ in 30W applications)
Power Consumption	< 30W @50VDC without PoE load <445W @50VDC with 400W PoE load
LED	System: Power 1 (Green), Power 2 (Green), Act /Alarm (Green/Amber), Ring Master (Green) P1~P24 UTP: 10/100 Link/Active (Green), 1000 Link/Active (Amber) P25~P32 SFP Slot: Link/Active (Amber) PoE (P1~P24): PoE ON (Green)
Jumbo Frame	10K Byte
MAC Address Table	32K
Memory Buffer	4M Bytes for packet buffer
Device Memory	16M Bytes Flash ROM, 1G Bytes RAM
Warning Message	System Syslog, SMTP/ e-mail event message, alarm relay
Alarm Relay Contact	Relay outputs with current carrying capacity of 1A @24VDC, 2-Pin removable terminal block
Operating Temperature	-40 ~ 75°C (IGR-2408SM-24PHE) -10 ~ 60°C (IGR-2408SM-24PH)
Operating Humidity	5% to 95% (Non-condensing)
Storage Temperature	-40 ~ 85°C
Housing	Rugged Metal, IP30 Protection and Fanless
Dimensions	280 x 440 x 44mm (D x W x H)
Weight	4.26kg
Installation Mounting	19" rack mount
MTBF	97,078 Hours (MIL-HDBK-217)

Certification

EMC	CE (EN55032, EN55035)
EMI (Electromagnetic Interference)	FCC Part 15 Subpart B Class A, CE
Railway Traffic	EN50121-4
Immunity for Heavy Industrial Environment	EN61000-6-2
Emission for Heavy Industrial Environment	EN61000-6-4
EMS (Electromagnetic Susceptibility) Protection Level	EN61000-4-2 (ESD) Level 3, Criteria B EN61000-4-3 (RS) Level 3, Criteria A EN61000-4-4 (Burst) Level 3, Criteria A EN61000-4-5 (Surge) Level 3, Criteria B EN61000-4-6 (CS) Level 3, Criteria A EN61000-4-8 (PFMF, Magnetic Field) Field Strength: 300A/m, Criteria A



Safety	EN62368-1
Surge Protection	4KV for PoE, RJ45 and SFP ports
Shock	IEC 60068-2-27
Freefall	IEC 60068-2-32
Vibration	IEC 60068-2-6

Software Specifications

L3 Routing

IPv4/v6 Static Routing	Supported
RIP v1/v2 Dynamic Routing	Supported
OSPF v2/v3 Dynamic Routing	Supported
Layer 3 Redundancy	VRRP v2, v3

Topology

VLAN	IEEE 802.1q VLAN, up to 4094 802.1Q VLAN ID IEEE 802.1q VLAN, up to 4094 Groups IEEE 802.1ad Q-in-Q MAC-based VLAN, up to 256 entries IP Subnet-based VLAN, up to 128 entries Protocol-based VLAN (Ethernet, SNAP, LLC), up to 128 entries VLAN Translation, up to 256 entries Private VLAN for port isolation GVRP (GARP VLAN Registration Protocol) MVR (Multicast VLAN Registration) Voice VLAN
Link Aggregation (Port Trunk)	Static (Hash with SA, DA, IP, TCP/UDP port), up to 16 trunk group Dynamic (IEEE 802.3ad LACP), up to 16 trunk group Per group up-to 8 port
Spanning Tree	IEEE 802.1d STP, IEEE 802.1w RSTP, IEEE 802.1s MSTP
Multiple μ-Ring	Up to 14 instances each support μ -Ring, μ -Chain or Sub-Ring for flexible networking applications Recovery time <20ms The maximum number of device is allowed 250 nodes in a Ring.
Loop Protection	Supported
ITU-T G.8032 / Y.1344 ERPS (Ethernet Ring Protection)	Recovery time <50ms Single Ring, Sub-Ring, Multiple ring topology
ITU-T G.8031 / Y.1342 EPS (Ethernet Protection Switching)	Supported

QoS Features

Class of Service	IEEE 802.1p 8 active priorities queues per port
Traffic Classification QoS	IEEE 802.1p based CoS IP Precedence based CoS IP DSCP based CoS QCL (QoS Control List): Frame Type, Source/Destination MAC, VLAN ID, PCP, DEI, Protocol, Source IP, IP Fragment, DSCP, TCP/UDP port number
Bandwidth Control for Ingress	Per port based
Bandwidth Control for Egress	Per port based Per queue / Per port shaper
DiffServ (RF 2474) Remarking	
Storm Control	For Unicast, Broadcast and Multicast

IP Multicasting Features

IGMP / MLD Snooping	IGMP Snooping v1, v2, v3 / MLD Snooping v1, v2 Port Filtering Profile Throttling, Fast Leave Maximum Multicast Group : up to 1022 entries Query / Static Router Port
----------------------------	--



Security Features

IEEE 802.1X	Port-Based
	MAC-Based
ACL	Number of rules : up to 256 entries for L2 / L3 / L4 L2 : Mac address SA/DA/VLAN L3 : IP address SA/DA, Subnet L4 : TCP/UDP
RADIUS	Authentication & Accounting
TACACS+	Authentication, Authorization and Accounting
HTTPS, HTTP	Supported
SSL / SSH v2	Supported
sFlow	Supported
User Name Password Authentication	Local Authentication
	Remote Authentication (via RADIUS / TACACS+)
Management Interface Access Filtering	Web, Telnet / SSH, CLI RS-232 console

Management Features

CLI	Cisco® like CLI
Web UI	Supported
Telnet	Server
SNMP	V1, V2c, V3
sFlow	Supported
Modbus/TCP	Supports management and monitoring
SW & Configuration Upgrade	SFTP, TFTP, HTTP
	Redundant firmware in case of upgrade failure
RMON	RMON I (1, 2, 3, 9 group), RMON II
MIB	RFC1213 MIB II, Private MIB
UPnP	Supported
DHCP	Server, Client, Relay, Relay option 82, Snooping
IP Source Guard	Supported
Mirroring	Local and Remote
Event Syslog	Syslog server (RFC3164)
Warning Message	System syslog, e-mail, alarm relay
DNS	Client, Proxy
IEEE1588 PTP V2	Supports 5 operating mode in each port : Ordinary-Boundary, Peer to Peer Transparent Clock, End to End Transparent Clock, Master and Slave
NTP V4.0, SNTP	Client
LLDP (IEEE 802.1ab)	Link Layer Discovery Protocol
	LLDP-MED

IPv6 Features

IPv6 Management	Telnet Server/ICMP v6
SNMP over IPv6	Supported
HTTP over IPv6	Supported
SSH over IPv6	Supported
IPv6 Telnet	Supported
IPv6 NTP, SNTP	Client
IPv6 TFTP	Supported
IPv6 QoS	Supported
IPv6 ACL	Number of rules: up to 256 entries
	for L2 / L3 / L4
	L2 : Mac address SA/DA/VLAN
	L3 : IP address SIP, Subnet (32bit)
	L4 : TCP/UDP

Advanced PoE Management	PoE PD failure auto checking, and auto reset when PD fail PoE port on/off weekly scheduling PoE Configuration PoE Enable/Disable Power limit by classification Power limit by management Total PoE Power budget limitation management: Maximum 400W power budget Power feeding priority
Other Features	Green Ethernet Supports IEEE 802.3az EEE (Energy Efficient Ethernet) Management to optimize the power consumption Determine the cable length and lowering the power for ports with short cables Lower the power for a port when there is no link LED Power Management : Adjustment LEDs intensity Cable Diagnostic Measuring UTP cable normal or broken point distance

Dimensions

Front View



Rear View



Top View



Side View



Ordering Information

Model Name	Managed	Total Port	RJ45	SFP	PoE		Input Power	Certification				Operating Temperature
			10/100/1000 Base-T(X)	100/1000 Base-X	IEEE 802.3af/at	Power Budget	48VDC	Safety EN62368-1	EN50121-4	EN61000-6-2 EN61000-6-4	CE FCC	
IGR-2408SM-24PHE	V	32	24	8	24	400W	2	V	V	V	V	-40~75℃
IGR-2408SM-24PH	V	32	24	8	24	400W	2	V	V	V	V	-10~60℃

Optional Accessories

■ Industrial SFP Transceiver

The ISFP series of industrial grade SFP modules have been fully tested with all CTC Union industrial grade Ethernet switches for guaranteed compatibility and performance. Best performance can be guaranteed, even in mission-critical applications. (Please see CTC Union's Industrial SFP datasheets for more items and detailed information.)

ISFP-M7000-85-D(E)	Industrial SFP GbE 1000Base-SX, M/M, 500 meter, wave length 850nm, 7.5dB, LC, DDML, -10~70°C (-40~85°C)
ISFP-S7020-31-D(E)	Industrial SFP 1000Base-LX, S/M, 20km, wave length 1310nm, 15dB, LC, DDML, -10~70°C (-40~85°C)
ISFP-T7T00-00-(E)	Industrial SFP 10/100/1000Base-T UTP 100meter, -10~70°C (-40~85°C)
ISFP-M5002-31-D(E)	Industrial SFP 155M 100Base-FX, MM, 2km, wave length 1310nm, 12dB, LC, DDML, -10~70°C (-40~85°C)
ISFP-S5030-31-D(E)	Industrial SFP 155M 100Base-FX, SM, 30km, 1310nm, 19dB, LC, DDML, -10~70°C (-40~85°C)

■ Industrial Power Supply

NDR-480-48	Industrial Power, Input 90 ~ 264VAC/127 ~ 370VDC, Output 48VDC, 480W, -20 ~ 70°C
------------	--