

40G Transponder

FRM220-40G-1Q4S
40G QSFP+ to 4 × 10G SFP+ Transponder

The FRM220-40G-1Q4S is a 40G QSFP+ to 4 × 10G SFP+ transponder that provides media conversion and distance extension for 40G over 10G links. The FRM220-40G-1Q4S meets the growing need for more bandwidth for data centers and enterprises. The emergence of high-end servers and Ethernet switches with 40G Ethernet interfaces increases the need for media conversion (multi-mode to single-mode) and link range extension. The FRM220-40G-1Q4S is a two slot wide hot-swappable card with one QSFP+ slot for QSFP+ 40G transceiver and four SFP+ slots for SFP+ 10G transceivers. The installation and setup is simple plug and play. The FRM220-40G-1Q4S can be inserted into any powered FRM220-CH20 chassis with QSFP+ and SFP+ transceivers required for the application.

Features

- Device Management via FRM220 Chassis with NMC
- Multiple functions in one module: 40G converter/repeater and Quad 10G optical multiplexer
- 40G link interface -- Ethernet/IEEE: 802.3ba 40GE-LR4
- 40G multi-link (fiber) interfaces -- Ethernet/IEEE: 802.3ba XLAUI and OIF: CEI-11G
- QSFP+ ports for flexibility and scalability
- Hot-swap support (module and interfaces)
- Supports 1 × 40G QSFP+ and 4 × 10G SFP+
- Supports DMI function for QSFP+ & SFP+ module
- Supports Loopback test function
- 3R function
- Supports LFPT function

Specifications

Equipment function	3R Transponder, Regenerator, Reshaper, Retimer	
Data Rate	Aggregate Data Rate	32 - 56.8 Gbps
	Data Rate per Lane	8 - 14.2 Gbps
Protocol	CPRI × 16	
	STM - 64	
	OC - 192	
	FC8, FC10	
	10G Ethernet	
Interface Type	40Gbps : QSFP+ (1 port), 10Gbps : SFP+ (4 ports)	
Transmission Distance	depends on QSFP+ & SFP+ module	
Power requirement	Power input 12VDC	
	Power consumption: ≤12W	
Work Environment	Operating Temperature	0 ~ 50°C
	Storage Temperature	-10 ~ 70°C
	Humidity	10 ~ 90% (non-condensing)
Weight	170g	
Dimension	159.5 × 42.1 × 88mm (D×W×H)	
Certification	CE, FCC	

