

# ITP-802GT-8PH24

## EN50155 PoE Switch

**2x Gigabit M12 + 8x 10/100Base-TX M12 with 8x PoE 120W, 24/48VDC**

- » 24/48VDC Power Input
- » Regulated PoE Output Voltage
- » M12 Connector for UTP and Power
- » EN50155, EN50121-4, EN61000-6-2, EN61000-6-4, EN45545-2, CE and FCC Certified



As an EN50155 certified M12 PoE switch, ITP-802GT-8PH24 has 8x 10/100Base-TX M12 D-code Ethernet ports and 2x Gigabit M12 X-code ports. Designed for heavy industrial, vehicle and rolling stock applications, utilizing M12 connectors to ensure secure connections and reliable operation, and withstand environmental disturbances such as vibration and shock. 24VDC power input design, compatible with vehicle battery power supply, realizes PoE function through voltage boosting. EN50155 certification covers operating temperature, mains input voltage, surge, ESD, vibration and shock, making the switch suitable for vehicle, rolling stock applications.

### Features


- Use M12 connector anti vibration and shock for vehicle, rolling stock, and railway applications
- Regulated PoE output voltage (53VDC) to stabilize PoE device, and guarantee delivery PoE power distance to 100 meters
- Wide operating temperature -40~75°C
- CE, FCC, EN51055, EN50121-4 and EN45545-2 for railway certified
- Industrial Grade EMS, EMI, EN61000-6-2, EN61000-6-4 certified

### Specifications

<b>Standard</b>	IEEE 802.3	10Base-T Ethernet
	IEEE 802.3u	100Base-TX Fast Ethernet
	IEEE 802.3ab	1000Base-T Gbit/s Ethernet over twisted pair
	IEEE 802.3x	Flow Control and Back Pressure
	IEEE 802.3af	PoE (Power over Ethernet)
	IEEE 802.3at	PoE+ (Power over Ethernet enhancements)
<b>Switch Architecture</b>	Back-plane (Switching Fabric): 5.6Gbps (Full wire-speed)	
<b>Data Processing</b>	Store and Forward	
<b>Flow Control</b>	IEEE 802.3x flow control, back pressure flow control	
<b>MAC Address Table</b>	4 K	
<b>Packet Buffer Size</b>	448Kbits	
<b>Network Connector</b>	8x M12 D-code Female	
	10/100Base-TX Auto negotiation speed	
	2x M12 X-code Female	
	10/100/1000Base-TX Auto negotiation speed	
	Auto MDI/MDI-X function	
<b>Network Cable</b>	Full/Half duplex	
	UTP/STP Cat. 5e cable above	
	EIA/TIA-568 100-ohm (100meter)	

<b>Protocols</b>	CSMA/CD				
<b>LED</b>	System: Power 1 (Green)				
	Per: Link/Active (Green)				
	PoE: ON (Green)				
<b>Reverse Polarity Protection</b>	Present for power input				
<b>Overload Current Protection</b>	Supported				
<b>PoE Standard</b>	IEEE 802.3af, IEEE 802.3at				
<b>PoE Power Budget</b>	Maximum PoE output power budget 120W (30W/port)				
<b>Power Supply</b>	Provides 1x M12 (5-Pin) for DC 24/48V (20~57VDC) input power				
	Built-in very high efficiency (97~98%) to boost PoE output voltage to 53VDC				
	Regulate PoE output voltage (53VDC) to stabilize PoE device, and guarantee delivery PoE power distance to 100 meters				
<b>Power Consumption</b>	<b>Input Voltage</b>	<b>Total Power Consumption</b>	<b>Device Power Consumption</b>	<b>PoE Budget</b>	<b>Boost Efficiency</b>
	24 VDC	125W	3.6W	120W	98%
	48 VDC	127W	4.3W	120W	97%
<b>Operating Temperature</b>	-10 ~ 60°C (ITP-802GT-8PH24) -40 ~ 75°C (ITP-802GT-8PHE24)				
<b>Operating Humidity</b>	5% to 95% (Non-condensing)				
<b>Storage Temperature</b>	-40 ~ 85°C				
<b>Housing</b>	Rugged metal, IP40 protection housing and fanless				
<b>Dimensions</b>	63.3 x 71.5 x 219mm (D x W x H)				
<b>Weight</b>	0.8kg				
<b>Installation Mounting</b>	Wall mounting				
<b>MTBF</b>	531,231 Hours (MIL-HDBK-217)				
<b>Certification</b>					
<b>EMC</b>	CE (EN55035, EN55032)				
<b>EMI</b>	FCC, FCC Part 15 Subpart B Class A				
	CE				
<b>Railway Traffic</b>	EN50155, EN50121-4				
<b>Fire Protection of Railway Vehicles</b>	EN45545-2				
<b>Immunity for Heavy Industrial Environment</b>	EN61000-6-2				
<b>Emission for Heavy Industrial Environment</b>	EN61000-6-4				
<b>EMS (Electromagnetic Susceptibility) Protection Level</b>	EN61000-4-2 (ESD) Level 3, Criteria B				
	EN61000-4-3 (RS) Level 3, Criteria A				
	EN61000-4-4 (Burst) Level 3, Criteria A				
	EN61000-4-5 (Surge) Level 3, Criteria B				
	EN61000-4-6 (CS) Level 3, Criteria A				
	EN61000-4-8 (PFMF, Magnetic Field) Field Strength: 300A/m, Criteria A				
	EN61000-4-11 Voltage Dips				
<b>Shock</b>	IEC 61373				
<b>Freefall</b>	IEC 60068-2-32				
<b>Vibration</b>	IEC 61373				

## Dimensions



## Ordering Information

Model Name	Total Port	UTP M12		PoE	PoE Total Power Budget	Power Input	Certification				Shock Vibration	Operating Temperature
		10/100 Base-TX	10/100/1000 Base-T(X)	IEEE 802.3at		Redundant	EN45545-2	EN50155 EN50121-4	EN61000-6-2 EN61000-6-4	CE, FCC	IEC61373	
ITP-802GT-8PH24	8	8	2	8	120W	24/48VDC	V	V	V	V	V	-10~60℃
ITP-802GT-8PHE24	8	8	2	8	120W	24/48VDC	V	V	V	V	V	-40~75℃

## Optional Accessories

### ■ Optional Cable/Connector

#### P/N: CAB-M12DM4-RJ45

M12 D-code Male (4-Pin) to RJ-45, AWG 24, IP67, 1 meter



For FE UTP

#### P/N: CAB-M12AF5-OPEN

M12 A-code Female (5-Pin) to open wire, AWG 22, IP67, 1 meter



For Power

#### P/N: CAB-M12XM8-RJ45

M12 X-code Male (8-Pin) to RJ-45, AWG 24, IP67, 1 meter



For Alarm

#### P/N: M12D-M4

M12 D-code Male (4-Pin) connector, IP67



For FE UTP