

# RocketLinx® ES8510-XT

Part Number: 32061-6



## KEY FEATURES AND BENEFITS

- Multiple redundant ring (recovery time <5ms)
- Supports TACACS+
- Seven 10/100BASE-TX ports and three Gigabit RJ45/SFP combo ports (10/100/1000BASE-TX, 100BASE-FX, 1000BASE-X)
- 32Gbps non-blocking, 8K MAC address table
- VLAN, GVRP, QoS, IGMP snooping V1/V2/V3, rate control, port trunking, LACP, online multi-port mirroring
- Management via console CLI, Web, SNMP V1/V2c/V3, RMON, HTTPS, SSH and NetVision
- Advanced security feature supports IP security, port security, DHCP server, IP and MAC binding, 802.1x network access control
- Event notification by email, SNMP trap, syslog, digital input and relay output
- -40° to +74°C operating temperature for extreme environments
- Rigid aluminum IP31 housing, excellent heat dispersion, redundant power, DIN rail/wall mount installation
- NEMA TS2 Compliant
- RoHS2 compliant under CE
- IPv6 support

## PRODUCT DESCRIPTION

The RocketLinx ES8510-XT is a managed industrial Ethernet switch, equipped with seven 10/100TX ports and three 10/100/1000 RJ45/100-FX/Gigabit SX/LX/LHX/ZX/SFP combo ports. Two Gigabit ports may be used to form a non-stop Redundant Ring while the third Gigabit port enables connection to an upper switch, couple ring or public server. The Gigabit combo port design provides flexibility to choose copper or fiber media supporting 100BASE-FX or 1000BASE-X, Multi-Mode or Single-Mode for a wide variety of distance and installation requirements.

The RocketLinx ES8510-XT is housed in a rugged aluminum enclosure that features an excellent heat dispersing mechanical design and extended operating temperature support. The embedded software supports full Layer 2 management features, multi-form ring redundancy, network control, monitoring, security and notification. The RocketLinx ES8510-XT also provides a built-in watchdog timer and digital input and relay output to avoid undetected problems. The RocketLinx ES8510-XT provides the perfect foundation for building your industrial Ethernet infrastructure.

### Three Gigabit Ports for Flexible Network Planning

A unique feature to the RocketLinx ES8510-XT is the three Gigabit RJ45/SFP combo ports, which can improve performance dramatically compared to products with only two Gigabit RJ45/SFP combos. Each combo comes with a flexible connection - 100Mbps or 1000Mbps, as well as fiber or copper connection options. All together, as many as ten different combinations of port connections are possible. By selecting the appropriate fiber transceivers, the RocketLinx ES8510-XT can meet your industrial application requirements with virtually any transmission distance.

### 100/1000Mbps SFP

The RocketLinx ES8510-XT SFP socket supports 100BASE-FX Single/Multi-Mode and 1000BASE-SX/LX/LHX/XD Multi/Single-Mode transceivers. The available distance of the 100BASE-FX is up to 30KM. 1000BASE-SX Multi-Mode supports 550M, 1000BASE-LX Single-Mode supports 10KM, 1000BASE-LHX Single-Mode supports 30KM, 1000BASE-XD Single-Mode supports up to 50KM. 1000BASE-ZX Single-Mode supports up to 70KM.

## ROCKETLINX SPECIFICATIONS

### HARDWARE

<b>Network Interfaces</b>	
10/100BASE-TX, 10/100/1000BASE-TX or 100BASE-FX and 1000BASE-SX/LX/LHX/XD/ZX Gigabit Fiber	
<b>Connector Types</b>	RJ45, SFP
<b>Enclosure</b>	
IP31 grade aluminum metal case	
<b>Installation Method</b>	DIN rail, wall mount
<b>LED Indicators</b>	
Power 1, Power 2, Ring Master (R.M.), 10/100BASE-TX link/activity, 10/100BASE-TX Full-Duplex/collision, Gigabit copper/SFP combo link activity, Digital Input 1&2, Digital Output 1&2	
<b>Digital Input (DI)</b>	
Two Digital Inputs, 4-Pin screw terminal block	
<b>Digital Output</b>	
Two Digital Outputs (Dry Relay Output), 4-Pin screw terminal block	
<b>Serial Console Port</b>	
One RJ45 RS232 (TXD, RXD, Signal GND), Baud Rate: 9600bps	
Data Bits	8
Parity	None
Stop Bits	1
Flow Control	None
<b>Dimensions</b>	5.0" x 6.3" x 3.7" 12.7 x 16 x 9.4 cm
<b>Product Weight</b>	2.63 lb 1.19 kg

### ETHERNET SPECIFICATIONS

<b>Number of Ports</b>	10
7 standard fast Ethernet and 3 combo RJ45/SFP Gigabit Ethernet	
<b>RJ45</b>	10/100BASE-TX, auto MDI/MDIX, auto negotiation (speed/duplex mode) 10/100/1000BASE-TX, auto MDI/MDIX, auto negotiation (speed/duplex mode)
<b>SFP (Optional)</b>	100BASE-FX Fiber, 1000BASE-SX/LX, auto MDI/MDIX, auto negotiation (speed/duplex mode)
<b>Cable Types</b>	Cat 3, Cat 4, Cat 5, Cat 5e (UTP or STP)
<b>Link Distances</b>	RJ45: 100 meters SFP: depends on model: Single-Mode: 30KM, Multi-Mode: 2KM
<b>Port Alarm Relay</b>	Yes
<b>Standards</b>	
IEEE 802.1AB: Link Layer Discovery Protocol (LLDP)	
IEEE 802.1D-2004: Rapid Spanning Tree Protocol (RSTP)	
IEEE802.1p: Class of Service	
IEEE 802.1Q: VLAN Tagging and GVRP	
IEEE 802.1s: Multiple Spanning Tree Protocol (MSTP)	
IEEE 802.1X: Port Based Network Access Control	
IEEE 802.3: 10BASE-T	
IEEE 802.3ad: Link Aggregation Control Protocol (LACP)	
IEEE 802.3u: 100BASE-TX, 100BASE-FX	
IEEE 802.3x: Flow Control and Back-Pressure	
<b>Internet Protocol</b>	
IPv4 and IPv6	

### MANAGEMENT FEATURES

<b>Configuration Management</b>	
Out-band management: Console port with Command Line Interface (CLI) - similar to Cisco CLI, In-band management: NetVision (Windows application), web interface (HTTP/HTTPS) or a Telnet/SSH console with CLI	
<b>Embedded Watchdog</b>	
Embedded hardware watchdog timer automatically resets system if switch system failure occurs	
<b>System Upgrade/Backup</b>	
TFTP/web interface for firmware upgrade and configuration backup/restore	
<b>SNMP</b>	V1, V2c, V3 with SNMP trap function, up to four trap stations
<b>SNMP MIB</b>	MIB-II, bridge MIB, VLAN MIB, IGMP MIB, Ethernet-like MIB, Control private MIB, and RMON
<b>Email Warning</b>	
Automatic warning, up to four accounts by pre-defined events	
<b>System Log</b>	
Supports both local mode and server mode	
<b>DHCP</b>	
DHCP client, DHCP server with IP and MAC address binding and DHCP	

### NETWORK PERFORMANCE

<b>Back Pressure</b>	
IEEE 802.3x: 10/100Mbps Half-Duplex Only	
<b>Class of Service (CoS)</b>	
IEEE 802.1p: 4 priority level (0-7), queue ID (0-3)	
<b>Flow Control Pause Frame</b>	
IEEE 802.3x: 10/100Mbps Full-Duplex	
<b>IGMP Snooping</b>	
V1/V2 /V3 for multicast filtering and IGMP query V1/V2; supports unknown multicasting, processes forwarding policies: drop, flooding and forward to router port, 256 IGMP multicast groups	
<b>IP Security</b>	
Assign authorized IP addresses to specific port, 10 max/port	
<b>Time Synchronization</b>	
Supports NTP protocol with daylight saving function, and localized time sync function	
<b>Port-Based Network Access Control</b>	
IEEE 802.1X: Supports user authentication by the RADIUS account, password and key for the RADIUS servers (primary and secondary), Supports TACACS+	
<b>Port Configuration</b>	
Port link speed, link mode, port status, enable/disable	
<b>Port Mirroring</b>	
Online traffic monitoring on multiple selected ports	
<b>Port Security</b>	
Assign authorized MAC addresses to specific port, 10 max/port	
<b>Port Trunk</b>	
IEEE 802.3ad LACP with timer and static port trunk; trunk member up to 8 ports and maximum 5 trunk groups	
<b>Private VLAN</b>	
Direct client ports in isolated/community VLAN to promiscuous port in primary VLAN	
<b>Rate Control</b>	
Ingress filtering for broadcast, multicast, unknown DA or all packets. Egress filtering for all packet types	
<b>Switch Technology</b>	
32Gbps switch fabric store and forward switch technology, 8K MAC address	
<b>System Throughput</b>	
10Mbps	14,880pps
100Mbps	148,880pps
Gigabit Ethernet	1,488,100pps
64 byte packet size	
<b>Transfer Packet Size</b>	
64 bytes to 1522 bytes (includes VLAN tag)	
<b>Packet Buffer</b>	
1Mbits shared memory	
<b>Traffic Prioritization (QoS)</b>	
Supports 4 physical queues, weighted Round Robin queuing (WRR 8:4:2:1) and strict priority scheme (IEEE 802.1p COS tag and IPv4 ToS/ diffserv information) to prioritize industrial network traffic	
<b>VLAN</b>	
IEEE 802.1Q: Tag VLAN with 256 (Max) VLAN entries, 2K GVRP entries; 3 VLAN link modes (trunk, hybrid, and link access)	
<b>Modbus TCP/IP</b>	
CLI support for Modbus TCP/IP communications with Function Code 4 (factory automation). Operates as slave/ server device, while a typical master/client device is a host computer running appropriate through Ethernet. The Modbus TCP/IP master can read or write to the Modbus registers provided by the Modbus TCP/IP application software (SCADA / HMI System)	

### NETWORK REDUNDANCY

<b>Rapid Spanning Tree Protocol</b>	
IEEE 802.1D-2004 Rapid Spanning Tree Protocol (RSTP): Compatible with Legacy STP and IEEE 802.1w	
<b>Multiple Spanning Tree Protocol</b>	
IEEE 802.1s MSTP: each MSTP instance can include one or more VLANs and supports multiple RSTPs deployed in a VLAN or multiple VLANs	
<b>Redundant Ring Technology</b>	
Failure Recovery within 5ms	
<b>Rapid Dual Homing</b>	
Multiple uplink paths to upper switches	
<b>Ring Trunking</b>	
Integrates port aggregate function in ring path to get higher throughput ring architecture	
<b>Multiple Ring</b>	
Couple or multiples of up to 16 rings, supports up to 5 Fast Ethernet rings/switch	

### ELECTRICAL SPECIFICATIONS

<b>Device</b>	
DC Input Voltage (positive or negative)	12-48 VDC
Current Consumption (24VDC)	0.8A
Power Consumption (Max)	20W
<b>Number of Power Connectors</b>	1
<b>Power Connector Type</b>	
4-Pin screw terminal block	
<b>Power Input Redundancy</b>	
Dual Redundant Inputs	
<b>Reverse Polarity Protection</b>	Yes
<b>Digital Input</b>	
2 with photo optical isolation	
Logic Low (0)	0 to 10VDC
Logic High (1)	11 to 30VDC
<b>Digital Output (Relay Output)</b>	
2	
DC Input Voltage	24VDC
Current Consumption (24VDC)	1A Maximum

### ENVIRONMENTAL SPECIFICATIONS

<b>Air Temperature</b>	
System On	-40° to 74° C
System Off	-40° to 85° C
<b>Operating Humidity</b>	
Non-condensing	5% to 95%
<b>MTBF (Mean Time Between Failures)</b>	28.53 years

### EXPORT INFORMATION

<b>Package Shipping Weight</b>	3.9 lbs 1.77 kg
<b>Package Dimensions</b>	11.3" x 5.5" x 9.1" 28.7 x 13.97 x 23.11 cm
<b>UPC Code</b>	7-56727-32061-6
<b>ECCN</b>	5A992
<b>Schedule B Number</b>	8517.62.0050

### REGULATORY APPROVALS

<b>Emissions</b>	
Canadian EMC Requirements	
ICES-003	
European Standard EN55022	
EN61000-6-4	
CISPR 22	
FCC Part 15 Subpart B	
Class A limit	
<b>Immunity</b>	
European Standard EN55024	
IEC 61000-6-2:	
IEC 1000-4-2/EN61000-4-2: ESD	
IEC 1000-4-3/EN61000-4-3: RF	
IEC 1000-4-4/EN61000-4-4: Fast Transient	
IEC 1000-4-5/EN61000-4-5: Surge	
IEC 1000-4-6/EN61000-4-6: Conducted Disturbance	
IEC 1000-4-8/EN61000-4-8: Magnetic Field	
IEC 1000-4-11/EN61000-4-11: Dips and Voltage Variations	
<b>Safety</b>	
IEC 60950/EN60950 (LISTED)	
CSA C22.2 No. 60950/UL60950 Third Edition	
<b>Shock</b>	IEC 60068-2-27
<b>Vibration</b>	IEC 60068-2-6
<b>Free Fall</b>	IEC 60068-2-32
<b>Hi-Pot</b>	
AC 1.2KV for all ports and power	
<b>Regulatory Approvals</b>	
European Standard: RoHS2 compliant under CE	
NEMA TS2 Certified	
<b>Other Regulatory Approvals</b>	

