

# SOLAR STORAGE TANKS WITH ELECTRIC ELEMENT **6-Year Tank Warranty 6-Year Parts Warranty**

## 2" Non-CFC Foam Insulation

Foam insulation saves fuel by retarding heat loss.

#### Fused Ceramic Shield

Applied under pressure and fired at 1600°F to completely cover the tank interior. This provides a tough interior surface for storage tanks and maximum protection against the wearing effects of high-volume and high-temperature hot water.

Anode Rod

Promote longer tank life through even distribution, for protection against corrosion of tank interior.

### • Factory-Supplied Top Temperature and Pressure **Relief Valve**

Factory-Installed Dielectric Nipples

#### Pre-Wired Sensor Lead

From storage sensor mounting stud to top of tank. Does not include sensor.

#### Water Connections

Accessible from four factory-installed 3/4" dielectric nipples located on top of tank.

#### • 4500-Watt Heating Element and Automatic Thermostat

Where a back-up system is desired.

## UL Listed

Model # SE62-80H-045S		SE62-119R-045S
Gal Capacity	80	119
Hght Wtr Conn.	60.25	62
Jacket Diameter	24	28
Hght Top of Tank	59.25	61.5
Hght Top T&P	59.25	61.5
Approx. Ship Wght	191	278

Copyright<sup>©</sup> by American Water Heater Company 2005. All rights reserved.



#### **6-Year Limited Tank Warranty**

Heavy gauge steel is automatically formed, rolled and welded to assure continuous seams for Fused Ceramic Shield<sup>™</sup> lining. Each tank is triple tested to ensure qualitv.

#### **6-Year Parts Warranty**

Original factory parts warranted for 6 years.

For complete warranty information consult the written warranty of American Water Heater Company at (800) 999-9515.