



Subject: Restrictor 4.8oz Woven Needlepoint Landscape Fabric

This letter certifies that our Restrictor 4.8oz Woven Needlepoint Landscape Fabric, manufactured by Core & Main, meets the average laboratory test values listed below:

PROPERTY	TEST METHOD	UNIT	ROLL VALUE
Weight	ASTM D 5261	Oz/sq/yd	4.8
Tensile Strength	ASTM D 4632	Lbs	115x65
Elongation	ASTM D 4632	%	10
Trapezoidal Tear	ASTM D 4533	Lbs	30x30
CBR Puncture Strength	ASTM D 6241	Lbs	220
AOS	ASTM D 4751	mm	0.425
Permittivity	ASTM D 4491	Sec ⁻¹	0.1
Water Flow Rate	ASTM D 4491	Gpm/ft ²	10
UV Resistance	ASTM D 4355	%/hours	70/500

Disclaimer: Core & Main LP assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. Core & Main LP disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The end user assumes sole responsibility for the use of this information and product. The property values listed above are subject to change without notice. Unless otherwise noted, this certification is based on testing conducted by our Quality Assurance & Quality Control testing laboratories at the time of manufacturing. Core & Main LP issued this letter of certification to indicate our commitment to providing our customers with a quality product which will meet or exceed the minimum average roll values in accordance with the applicable American Society for Testing and Materials (ASTM) test method.

Respectfully,

Rusty Payne
Business Development / Engineering