



Geotextiles | Erosion Control | Site Solutions

Subject: Sedi-Bag / Dewatering Bag Data Sheet

This letter certifies our Sedi-Bag, also known as Dewatering Bags are produced using ES800N Non Woven Geotextile Fabric. Sedi-Bag are inert to biological degradation and resist naturally encountered chemicals and acids. The stitching is a durable, double thread chain stitch. Standard Sizes: 5' X 6', 10' X 15' and 15' X 15'. Custom Sizes are available. The average laboratory test values are as follows: 5' X 6', 10' X 15' and 15' X 15'. Custom Sizes are available. The average laboratory test values are as follows:

Properties	Test Method	English MARV ²	Metric MARV ²
MECHANICAL PROPERTIES			
Grab Tensile Strength	ASTM D4632	205 lbs	0.912 kN
Grab Elongation	ASTM D4632	50%	
Trapezoidal Tear Strength	ASTM D4533	85 lbs	0.378 kN
CBR Puncture Strength	ASTM D6241	535 lbs	2.37 kN
HYDRAULIC PROPERTIES			
Permittivity ³	ASTM D4491	1.40 sec ⁻¹	
Water Flow ³	ASTM D4491	95 gpm/ft ²	3870 l/min/m ²
Apparent Opening Size (AOS) ^{3,4}	ASTM D4751	80 US Sieve	0.18 mm
ENDURANCE PROPERTY			
UV Stability	ASTM D4355	70% at 500 hours	

Disclaimer: This information describes product properties at the time of manufacture and testing only and does not constitute or confer any warranties. Values stated will be affected over time by handling, storage, shipping, installation, use and other factors. GroGreen Solutions does not provide engineering advice with respect to use of the product herein or otherwise and will not be liable for installation error. GroGreen Solutions DISCLAIMS ALL IMPLIED WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY.

GroGreen Solutions assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. GroGreen Solutions disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The end user assumes sole responsibility for the use of this information and product. The property values listed above are subject to change without notice.

Unless otherwise noted, this certification is based on testing conducted by our Quality Assurance & Quality Control testing laboratories at the time of manufacturing. GroGreen Solutions issued this letter of certification to indicate our commitment to providing our customers with a quality product which will meet or exceed the minimum average roll values in accordance with the applicable American Society for Testing and Materials (ASTM) test method.

GroGreen Solutions

Direct Phone: 912-534-6071 - Toll Free: 800-948-7870