




BrightLync® 300

Connectivity-as-a-Service (CaaS)

BrightLync® 300 expands connectivity to support the industry's most widely deployed EVCs, enabling utilities to bring more endpoints onto the unified BrightLync® platform. Robust cellular connectivity and serial communications seamlessly deliver meter data to existing systems, providing reliable data access and greater visibility across the network.

Features

- IoT advanced communications platform
 - Carrier agnostic cellular infrastructure
 - 100% cloud native
 - Serial communication
 - Over-the-air (OTA) updates
 - Remote monitoring and access to near real-time data
 - Near real-time alarm transmission
 - Automatic daily data transfer to cloud
- Integrated Device Manager and API compatible with various operational systems
 - Automated logs, event histories, audit ready records
- Industry-leading security with end-to-end encrypted hardware, transmission, and storage

Applications

- High value C&I metering endpoints

Secure CaaS with zero infrastructure investment

With BrightLync® there are no infrastructure investments, allowing utilities to expand network connection at the rate of value, not infrastructure absorption. By pairing our purpose-built gateway devices with existing cellular networks, BrightLync® provides a rapidly deployable, scalable CaaS solution.

Reliable network coverage across North America

BrightLync® is carrier agnostic by design, providing flexibility to optimize connectivity at each and every endpoint. By leveraging North America's premier wireless carrier networks, BrightLync® ensures ubiquitous coverage, reliable uptime, and continuous network upgrades

Simplified integration with existing systems

BrightLync® uses a modern web API to exchange data through standard conventions - there is no learning curve and no custom protocol to decode. For teams that want data files delivered, BrightLync® can auto-generate daily flat files to move batch data to existing billing and operation systems. No matter the existing platform, BrightLync® makes integration easy.

Secure by design, today and into the future

BrightLync® features robust cybersecurity protocols to protect against threats of today, while Romet's foundational Security Strategy ensures BrightLync® is proactively engineered for the threats of tomorrow, including the transition to post-quantum cryptography (PQC). Over-the-air (OTA) firmware updates will deliver PQC-enabled security as standards and threats evolve to protect asset investment, and ensure security remains resilient throughout the full product lifecycle.

BrightLync® 300

Specifications

All specifications are dependent on connected EVC capabilities

- Network
 - Tier 1, carrier agnostic LTE-M network infrastructure
- Data transmission
 - High-fidelity serial data from edge device
 - Frequency: Hourly data once per day
 - Automatic data pull at next wake-up
- Data Storage
 - 13 months active. >13 months archived. No minimum storage limit.
- Systems Integration
 - Standard API, autogenerated flat file
- Device Manager User Interface
 - User access and administration management (MFA default, SSO login configurable)
 - Visualization of available data
 - Manual (.csv/.json) file download and automated data transfer (Representational State Transfer (REST) API)
 - Automated notifications
 - Remote threshold management

Gateway Device (BL-300)

- Physical
 - Weather resistant, UV resistant, ESD grade engineered polycarbonate enclosure
 - Direct/bracket mount configurations
 - Dimensions: 5.6" (142mm) x 5.9" (150mm) x 3.9" (98mm)
 - Weight: 1.7 lbs (780 g)
- Battery & Power
 - 20-year nominal battery life
 - End of battery life warning
- User Interface
 - Magnetic wake up
 - BLE connectivity to iOS/Android commissioning app



EVC Integration

All specifications are dependent on connected EVC capabilities

- Available data
 - Corrected and uncorrected volume (daily, total, interval)
 - Daily and interval average temperature and pressure
- Malfunction status notification
- Lost connection alarm
- Available alarm notifications
 - Temperature, pressure and flow limit violations
 - Battery low
- Available configurable threshold notifications
 - High/Low pressure
 - High/Low flow
 - Remaining battery life (voltage)

Approvals / Certifications

- Intrinsically safe: Class I, Zone 0, Class I, Div 1 Group D (cETLus)
- Industry Canada ICES-003 Class B
- FCC Part 15 Class B
- PTCRB

ROMET®

Romet Limited
5030 Timberlea Blvd,
Mississauga, Ontario L4W 2S5
Canada
1-800-387-3201
www.rometlimited.com

USA
8517 West Washington Street, Unit 301
Indianapolis, Indiana 46231
United States

ROMET and ROMET & DESIGN are registered trademarks of Romet Limited. Romet Limited's gas metering technology is protected under U.S. Patent No. 4,910,519 and 6,453,721 and Canadian Patent No. 1,293,568

Disclaimer: The values quoted are typical of normal production. They do not constitute a specification. Romet Limited reserves the right to change any information in this literature without notice. All of the information and data in this literature has been carefully compiled and thoroughly checked; however, Romet Limited will not assume responsibility for any possible omissions or errors.

F-145 Rev 1 | August 2026 | © 2026 Romet Limited