


## Rotary Gas Meters RMT300 - Soft Metric



Note: AMI/AMR adaptors available upon request.

METER SIZE	ANSI 125 FF FLANGE	А	В	С	D1	D2	D3	D4	E1	WEIGHT (lbs)
RMT300	4"	9.5"	8.25"	8.24"	19.96"	21.24"	22.90"	23.10"	4.00"	54-60

Meets or exceeds ANSI B109.3


## SOFT METRIC RMT300 4" FLANGE CONNECTION TECHNICAL SPECIFICATION

Connection (Flange)	ANSI 125 FF	4"	
MAOP	(kPa)	1206	
Flow Capacity	(m³/h)	300	
Rangeability * @ ±2% / ±1% Error		1:200 / 1:140	
Start Rate	(m³/h)	0.039	
Stop Rate	(m³/h)	0.023	
Differential @ 100 % Flow [AIR/N.G.]	(Pa)	436/262	
Instrument Drive Rate	(m³/rev)	0.1	
LF Pulser (Optional)	(m³/pulse)	0.1	

<sup>\*</sup>Note: It should be noted, that moving parts in the meters with a greater rangeability ratio are made to high class accuracy and tight tolerances. Improper installation, stresses on piping system due to temperature changes, settling and gas conditions can create a risk of meter rejection.

## CORRECTED FLOW CAPACITY AND TYPICAL ACCURACY GUIDE

RMT300 METER (Sm³/h)				
Gauge Pressure kPa 1.72	RMT300 Qmax = 300m³/h			
5	313.8			
10	328.6			
50	447.1			
100	595.1			
150	743.1			
200	891.2			
250	1039.2			
300	1187.3			
500	1779.4			
750	2519.6			
1000	3259.8			
1100	3555.9			
1200	3852.0			





The values quoted are typical of normal production. They do not constitute a specification. Romet Limited reserves the right to change any information in this literature without notice. All of the information and data in this literature has been carefully compiled and thoroughly checked. However, Romet Limited will not assume responsibility for any possible omissions or errors.

ROMET and ROMET & DESIGN are registered trademarks of Romet Limited. Romet Limited's gas metering technology is protected under U.S.Patent No.4,910,519 and 6,453,721 and Canadian Patent No.1,293,568.