



RCKT Mobile POS

Advanced, Secure, Convenient Mobile Payments Acceptance

RCKT is the perfect companion device, putting the power of advanced, secure, and convenient EMV mobile payments into the palm of your hand.

EvolvPay Micro Promo No Cost Processing Solution

Features



Backlit LCD
Display



Wireless Bluetooth
Connectivity



Optional 2G/4G
Connectivity



Plug and Play



Long-Lasting
Battery



PCI-PTS
5.0 Certified



Remote Key
Injection



Data Integration to
Evolv Platform for Unified
Omnichannel Commerce



Lightweight,
Easy-to-Hold



Contact/
Contactless
Swipe, Dip, & Tap



Credit, Signature/
PIN Debit, &
EBT Acceptance



Buyers Choice
& Surcharging

BENEFITS

- Offer Consumers Convenience with Swipe, Dip, and Tap Capabilities
- Generate More Sales with Credit, Signature & PIN Debit, plus EBT Mobile Acceptance
- Reduce Payment Processing Costs with Card-Present Transaction Qualification
- Reduce Counterfeit, Lost, and Stolen Card Fraud with EMV Security
- Save Time and Money and Gain Better Insights with Unified Omnichannel Commerce
- Get More Functionality at Comparable Pricing



SPECIFICATIONS

CPU		32-bit high performance secure processor
OS		RTOS (proprietary)
Memory	Optional	512KB SRAM, 512KB+ 4 MB FLASH 512KB SRAM, 512KB+ 8 MB FLASH
Display		1.7-inch monochrome LCD display, resolution of 128 x 64, with backlight
Wireless Communication	Optional	Bluetooth 4.2
	Optional	2G
	Optional	4G (NB-IOT)
Magnetic Card Reader	Optional	Triple track, bi-directional, conforming to ISO 7810/7811/7813
Smart Card Reader		EMV L1/L2, conforming to ISO 7816, 1.8V/3V/ 5V synchronous & Asynchronous, T=0 & T=1
Contactless Card Reader		EMV Contactless L1, conforming to ISO 14443 Type A/B, Mifare , Felica
Audio		Built-in buzzer
Peripheral Ports		1 x TYPE-C for charging and communication
Keypad		10 x alphanumeric keys, 5 x function keys, 1 x Power button
Card Slots	4G/2G Version	2 x SIM
Battery		Li-ion battery, 3.7V/470mAh/1.74Wh
	4G/2G Version	Li-ion battery, 3.7V/1100 mAh/4.07Wh
Power Supply		5V DC, 0.5A
	4G/2G Version	5V DC, 1.0A
Dimensions		102.7mm(L) x 55.8mm(W) x 16.5mm(H)
	4G/2G Version	102.7mm(L) x 55.8mm(W) x 17.9mm(H)
Weight		100g including battery
	4G/2G Version	108g including battery
Environment		Operating temperature: 0°C~40°C (32°F~104°F) Storage temperature: -20°C~70°C (-4°F~158°F) Relative humidity: 10%~90% (Non-condensing)
Certifications		PCI PTS 5.x, EMV L1/L2, EMV Contactless L1, PayPass, payWave American ExpressPay, Discover D-PAS,TQM, CE, RoHS



888.311.7248



info@poweredbyevolv.com



10999 Stahl Road
Newburgh, IN 47630



poweredbyevolv.com