

# CSW200UL

COMMERCIAL SWING GATE OPERATORS

## Specifications


- Power**  
110V Single Phase
- Intelligent Master/Second**  
Precise, synchronized movement and communication between two gate operators.
- Gate Traveling Speed**  
90° opening in 13-15 seconds.
- Temperature Specification**  
-40F (-40C) to 140F (60C)
- Warranty**  
5 years Commercial Application  
7 years Single Home Application

## Construction

- Chassis**  
Constructed with 1/4" sanded, welded and gold zinc-plated sheet metal.
- Finishing**  
All metal parts are gold zinc-plated for rustproof protection.
- Wormgear Reduction**  
2 commercial oil bath gear boxes with 900:1 wormgear reduction.
- Cover**  
High-density UV resistant polyethylene plastic for excellent heat and corrosion resistance.
- Operator Weight**  
CSW200UL - 175lbs  
CSW200ULST - 194lbs  
CSW200ULDLM - 199lbs  
CSW200UL1HP - 199lbs

## Dimensions

- CSW200UL  
15"w x 28"h X 20.5"d
- CSW200ULST  
14"w x 28"h X 19"d
- CSW200ULDLM  
CSW200UL1HP  
15"w x 28"h X 24.5"



# LiftMaster®

The Chamberlain Group, Inc. • 845 Larch Avenue • Elmhurst, IL 60126  
[www.LiftMaster.com](http://www.LiftMaster.com)



©2013 The Chamberlain Group, Inc. LMGTBRC5W2 Printed in U.S.A. 1/13  
ISO 9001 Certified Manufacturer

## Available Options

-  **DC2000 Power Backup** Provides uninterrupted access during a power outage. Meets Fire Marshalls requirements for Emergency Access. Compatible with 1/2HP and Dual Motor models.
-  **EL2000** Multi Tenant Telephone Entry System
-  **EL25 & TAC1** Single/Multi Tenant Telephone Entry System
-  **LiftMaster AELD Plug-in Loop Detector**
-  **CPS UN4/G65 MGR20** Safety reversing photo eye & edge
-  **G6518** Heater Kit
-  **MPEL** Post Mount Plate
-  **Power Hinges**
-  **LiftMaster Security+ 2.0™ Remotes**
-  **Advanced Traffic Management** Quick Close Option

# ELITE SERIES®

# CSW200UL

COMMERCIAL SWING GATE OPERATORS



## The Most Reliable Commercial Swing Gate Operators in the Industry

The Elite Series® CSW200UL models of swing gate operators are the first choice for heavy-traffic applications such as large gated communities, residential developments, commercial complexes and private estates.

The Security+ 2.0™ technology used exclusively in LiftMaster remote controls virtually eliminates interference and provides up to double the range of standard remotes so you don't have to wait at the gate to access your property.

Featuring the highest quality components, the legacy Elite model CSW drive train is backed by years of proven dependability; each unit is carefully inspected and mechanically tested to provide unsurpassed reliability. Unique engineering innovations in each model also ensure that there's a CSW to meet practically every swing gate application.



- **Security+ 2.0™ Technology**  
2x the range of standard remotes
- **Legacy Elite Drive Train**  
Provides unsurpassed reliability



# LiftMaster®

# CSW200UL

COMMERCIAL SWING GATE OPERATORS

## Features/Benefits



### Security+ 2.0™ Receiver

2x range of standard remote controls. Multi frequency radio virtually eliminates interference.



### Advanced Safety and Performance Engineering

OmniControl™ board provides enhanced, reliable performance meeting or exceeding all UL325 and UL991 specifications.



### Surge/Lightning Protection

Protects against lightning strikes at a 50-foot radius.



### Plug-In Loop Detectors

Easy to install, simple to program inputs for shadow, interrupt and exit.




### Alarm Reset Button

Instantly resets the built-in safety alarm siren.



### Complies With UL325 Standards

Secondary entrapment devices must be added to meet UL325 standards. Installer will recommend suitable secondary entrapment devices such as photo eyes or edge sensors.



### Reversing Sensor

Detects obstructions or increased loads. Reverses gate when closing or stops/reverses the gate when opening.



### Emergency Release

Simple to use release handle allows gate to be operated manually and maintain limit position once reengaged.

### Non-Scissor Action Arm

Reduces the risk of injury from the gate operator arm. Operator arms are designed not to cross.



### Limit Switch Design

Precision limit switch system provides limit accuracy and reliability.



### Soft Stop

Soft Stop operation extends operator and hardware life under high-cycle, heavy gate use.

### Wormgear Reducer

Efficient, extremely quiet 900:1 two stage commercial oil-bath reducer.




### CSW200UL and CSW200ULST

#### High-traffic commercial swing gate operators

Ideal for gated communities and commercial applications. Two available models each have identical performance features with a choice of exterior covers. The CSW200UL™ offers a 1/4" thick, unbreakable polyethylene cover for long-lasting protection. The CSW200ULST™ offers a heavy-duty, 16-gauge stainless steel cover finished with an embossed architectural design.

#### Recommended Capacities CSW200UL




### CSW200ULDM

#### High-traffic/high-temperature commercial swing gate operator

Patented dual motor drive system for superior performance in hot weather climates such as desert environments. Engineered to perform without overheating, using one motor to open the gate and the other to close it.

#### Recommended Capacities CSW200ULDM



### CSW200UL1HP

#### Heavy-duty, one-horsepower commercial swing gate operator

Our most powerful swing gate operator. Equipped with two 1/2 HP motors and a heavy-duty, 900:1 double transmission, it is the perfect choice for large, heavy wrought-iron gates. 250 lbs. of pulling torque.

#### Recommended Capacities CSW200UL1HP

