## **HIGH-TRAFFIC COMMERCIAL DC BARRIER GATE OPERATOR**

LiftMaster



## **HIGH-SPEED DC-POWERED BARRIER** GATE OPERATOR WITH BUILT-IN **BATTERY BACKUP**

The Mega Arm Sprint and Mega Arm Sprint Tower are DC-powered, high-speed additions to the LiftMaster® family of gate operators.

Designed with a 24VDC (1/2 HP equivalent) motor, these models provide exceptional speed, making them ideal for parking applications. Constructed with an aluminum alloy chassis, they're corrosion resistant and light enough for one person to carry and install. The heavy-duty motor supports 10,000 cycles per day with an operator speed of 0.9 second to open or close.

Built-in battery backup provides seamless operation of the gate operator and all DC control and sensing devices in the event of a power loss.

#### **Built in Receiver**



Exclusive from LiftMaster," a single remote control solution for gate access and additional access points. Ability to add up to 50 remote controls.

2 2 2



TTTTT

LiftMaste

## MAS/MAST

### **STANDARD FEATURES**

#### Highest grade "Aircraft Quality" **Aluminum Chassis**

High strength rust proof T-6 aluminum alloy chassis for superior strength corrosion resistance. Light enough for a one man installation.

#### **Magnetic Limit Sensors**

Designed for high cycle applications, contain no moving parts to wear out, provide reliable operation.

#### **Break Away Arm**

Available with 12 or 15 ft. break away arm. Arm is held in place with break away retaining nuts. If arm is hit, it will break away and can be re-installed. Universal arm can be set up for right or left hand mount.

#### New & Improved Built-in Surge Protection

Added protection at point of incoming line voltage from power line spikes and surges.

#### 1/2 HPS DC Motor with Soft Start Stop

Heavy duty motor provides strong reliable operation.

#### **Auxiliary Outlet**

Arm One

Simplifies adding / powering up accessories devices. Save the expense of having to add an extra outlet.



**Articulating Arm** 

**Clutch option** 

**OPTIONAL EQUIPMENT** 

For operation in low headroom environments.

Allows arm to be manually pushed open. Arm

automatically resets to normal closed position

upon receiving activation. Ideal for areas that are concerned with vandals damaging arm.



Arm Two



## **ADDITIONAL FEATURES**

**Universal Controller With 8 Inputs Right- Or Left-Handed Operation** Safety-stop Tailgate Feature **Anti-Tailgate Quick-Close Feature** 



15 seconds after power failure of upon battery depletion barrier arm can be set to automatically open. 15 second delay helps reduce nuisance call backs due to short power interruptions or brown outs. Meets fire code for many local Municipalities.

#### **Battery Backup**

Provides operation during power outages to maintain traffic flow. Automatically resets to normal operation when power is restored. (see specific cycle info per model see below)

The built in battery back-up provides up to 900 full cycles (12 ft. arm).

#### **Heavy Duty Drive System**

Extra Large commercial grade #80 gearbox provides strong reliable operation.





©2011 The Chamberlain Group, Inc. Printed in U.S.A. 08/11 LMGTCAOMAS

#### SPECIFICATIONS **Operator Speed**

2.5 seconds to open or close

Power 120V / 220V applications

**Accessory Power** 24VDC 500 MA Battery Backup for Accessory Power

**Operator Weight** (without arm) MA - 89 lbs. MAT - 113 lbs.

#### **UL Listed**

UL325 & UL991 - Class I, II, III, IV


#### Construction

Gear Reduction: 60:1 Reducer in synthetic oil bath Motor: 1/2 HP Equivalent Continuous-Duty 24VDC/ 800 RPM Chassis

Powdercoated 1/4" Aluminum Alloy Cover:

MA - Plastic MAT – Aluminum

#### Dimensions





RECOMMENDED CAPACITIES		
HP*	MAX. GATE LENGTH (ft.)	CYCLES /DAY
1/2	12' & 15' aluminum arm 14' soft-padded arm	6,000

\*equivalent 24VDC

#### 2-YEAR WARRANTY

**10-YEAR WARRANTY Operator Frame** 

I.C./F.C.C.

BOM

# Lift Master

THE CHAMBERLAIN GROUP, INC. 845 Larch Avenue • Elmhurst, IL 60126 www.liftmaster.com





Arm Three