

**CUSTOMER**

# Certificate of Compliance

## Static Conductive Silicone Bellow

DESCRIPTION	YES	NO	NA
ISO 9001:2015 QMS		✓	
FDA 21 CFR 177.2800 (TEXTILES)			✓
FDA 21 CFR 177.2600 (RUBBER ARTICLES)	✓		
FDA 21 CFR 177.1680 (POLYURETHANE)			✓
CALIFORNIA PROPOSITION 65			✓
REACH			✓
RoHS			✓
EC1935/2004	✓		
EC2023/2006	✓		
EC10/2011			✓
EU DIRECTIVE 2014/34 (ATEX)	✓		
PHthalate / BPA FREE	✓		
TSE / BSE / ADI FREE	✓		
LATEX RUBBER FREE		✓	
CONTAINS 3TG MINERALS		✓	

Bellow	479
Abrasion-Resistance	Poor
Temperature Range	-76° - 392°F/ -60° - 200°C
Durometer (Shore A)	60 +/- 5
Static Decay	3x10 <sup>15</sup> ohm/cm <sup>3</sup>
Ultimate Elongation	240%
Mullen Burst	1500 PSI
Permeability	0 CFM @ 0.5"wg
Electrostatic Resistance	<106 Ohm

I do hereby certify that the products and/or services supplied on the above referenced invoice number are of the quality specified and conform to all requirements of the purchase order, including quality control, design and material specifications, drawings, packaging, marking and physical identification requirements as well as regulatory requirements as indicated above.



President