



SENTRICLAD
ARCHITECTURAL METALS



SENTRICLAD ARCHITECTURAL COLOR PALETTE- **FLORIDA ONLY**

COLORS



Cloud Gray #432B161




Stingray #432R792




Liberty Green #435B425



Island Blue #436R2713**



Buckskin #437C2347



Nickel #439RZ11459M ♦***++

□ LEED Compliant for low slope and steep slope

△ LEED Compliant for steep slope only

** Denotes exotic colors and are subject to premium pricing

PVDF- 70% Polyvinylidene fluoride resin paint system

♦ Featuring a pearlescent mica finish; subject to premium pricing. Colors shown are as close to actual colors as allowed by the printing process. Actual metal samples are available. Colors may appear different when viewed at different angles and under different lighting conditions. Due to product improvements, changes and other factors, we reserve the right to change or delete information herein without prior notice.

ARCHITECTURAL PVDF				STEEL				ALUMINUM			
Color	SR	IE	SRI	26GA.¶	24GA.†	22GA.‡®	18GA.‡®	.032"†	.040"†	.050"†®	.063"†®
Cloud Gray	.33	.87	35		■●			■●			
Liberty Green	.44	.84	48		■●			■●			
Buckskin	.21	.87	19		■●						
Stingray	.25	.86	24		■●			■●			
Island Blue**	.38	.86	38		■●			■●			
Nickel**	.37	.82	38		■●						

SR= Solar Reflectivity IE= Initial Emissivity SRI= Solar Reflective Index

PAINT PERFORMANCE PROPERTIES	HOT DIPPED GALVANIZED STEEL OR GALVALUME	ALUMINUM
Accelerated Weathering ASTM D 4587 (Drew Cycle Weatherometer) ASTM G-154 Chalk Rating Per ASTM D 4244, Method A	Hours: 3,000 Total Chalk: Rating 8 Color: 5 E Hunter units max Hours: 5,000 Total Chalk: Rating 8 Color: 5 E Hunter units max	Hours: 3,000 Total Chalk: Rating 8 Color: 5 E Hunter units max Hours: 5,000 Total Chalk: Rating 8 Color: 5 E Hunter units max
Salt Spray ASTM B 117	Hours: 1,000 Total Scribe: Rating 1/16" (2mm) Field: Rating 10, no blisters	Hours: 3,000 Total Scribe: Rating 10, no creepage Field: Rating 10, no blisters
Humidity ASTM D 2247	Hours: 2,000 Total Rating: 10, no blisters per ASTM D 774	Hours: 3,000 Total Rating: 10, no blisters per ASTM D 774
Formability ASTM D 4145	OT- 2T	OT- 2T
ASTM D 522 (Elongation over 1/8" mandrel)	No cracking No loss of adhesion	No cracking No loss of adhesion
Pencil Hardness ASTM D 3363	HB-2H	HB-2H
Abrasion Resistance ASTM D 968	55-75 Liters of falling sand	55-75 Liters of falling sand
Specular Gloss ASTM D 523	30 +/- 5 at 60 55 +/- at 85	30 +/- 5 at 60 55 +/- at 85
Reverse Impact ASTM D 2794	2 x Metal thickness in inch-lbs. No loss of adhesion. No cracking.	1/2 x Metal thickness in inch-lbs. No loss of adhesion. No cracking.
Flame Test ASTM E 84	Class A rated coating	Class A rated coating

SHERWIN-WILLIAMS.

Coil Coatings

Sherwin-Williams® is a trademark of SWIMC LLC.

- † Standard Coil Width is 48.25"
- ‡ Standard Coil Width is 22 GA 48.25" 18 GA 44.375"
- Standard Color Option.
- ▲ 40.5" Coil Option is Available.
- ▲ Additional Lead Times May Apply.
- † Standard Coil Width 40.5"
- ¶ Refers to Reflective Ratings
- △ Offered in 27-1/2" coil width
- ** Denotes Mica Colors
- ** Denotes exotic colors and are subject to premium pricing

NOTES ON AVAILABILITY:

- 24ga, .032, .040, .050, .063 are standard 48.25" in width. 22g 48.25" and 18ga 44.375" in width. 26ga is 40.5" standard width for painted items.
- Protective stippable film is standard on flat sheets.
- Mica+ and exotics+ are subject to premium pricing. Due to the unique effect of the Mica finishes, appearances may vary from batch to batch.
- Standard inventory is non-embossed. Embossed requests are to be quoted.
- Unpainted, acrylic coated, aluminum-zinc alloy steel (A255) is maintained in 26ga 20", 26ga 27-1/2", 26ga 24", 24ga 20", 24ga 27-1/2", 24ga 24" slit coils and 26ga 48"x120", 24ga 48"x120" flat sheets (no stippable film).
- All colors are supplied in Medium Gloss (20-35 at 60 deg). Low gloss on non 26ga available subject to minimum coating run.
- This color chart is subject to change without notice.

SENTRICLAD STANDARD ARCHITECTURAL COLORS AND FINISHES FEATURE 70% POLYVINYLIDENE FLUORIDE (PVDF) RESIN PAINT SYSTEMS TO ENSURE LONG-TERM COLOR RETENTION AND PERFORMANCE. CUSTOM COLORS AND FINISHES ARE ALSO AVAILABLE. MINIMUM QUANTITIES AND SET-UP CHARGES MAY APPLY.

*****PLEASE REFER TO SENTRIGARD.COM FOR MOST UP TO DATE COLOR LISTINGS. SR, IF, SRI CODES AND AVAILABILITY*****

SRI RATINGS ARE FOR GALVALUME ONLY. ALUMINUM RATINGS ARE LISTED ON WWW.SENTRIGARD.COM



SENTRICLAD
ARCHITECTURAL METALS

FLORIDA ONLY

877-495-7663
www.SENTRIGARD.com

© 2024 Sentrigard
98-32-010
3/24 230