

REGIONAL DRIVE

The M920A delivers superb all-weather traction and high mileage for year-round use in regional and urban operations. This unique tire features a Three-Peak Mountain Snowflake plus a wider tread width for even load distribution and improved stability. The deep tread ensures maximum mileage on pickup and delivery vehicles, while the N-speed rating matches OE 19.5 specifications. Computer-optimized design, all-weather traction, and high mileage make the M920A the leading tire for pickup and delivery vehicles.

APPLICATION	RECOMMENDED	SUITABLE
LONG HAUL	DRIVE	-
REGIONAL	DRIVE	-
URBAN	DRIVE	STEER



Three-Peak Mountain Snowflake qualified.

EXCELLENT REMOVAL MILES

- Deep tread depth delivers maximum miles.
- E-balance provides optimum footprint wear to increase mileage performance.
- Wider tread width for even load distribution, improved stability, and excellent profile retention.

SUPERIOR ALL-WEATHER PERFORMANCE

- Cross-sipe arrangement maintains block stiffness to provide traction throughout the life of the tire.

EXCELLENT CASING DURABILITY

- Stone ejectors in all major grooves prevent casing damage.

M920A™
19.5



M920A™
22.5-24.5



TIRE SIZE	PRODUCT CODE	LOAD RANGE & PLY RATING	LI/SS	APPROVED RIM WIDTH RANGE (IN.) (DESIGN RIM)	TIRE WEIGHT (LBS.)	TREAD DEPTH	INFLATED DIMENSIONS*		STATIC LOADED RADIUS (IN.)	MAX LOAD (LBS.)		MAX PRESSURE (LBS.)		REVS PER MILE	MAX SPEED (MPH)
							OVERALL DIAMETER (IN.)	OVERALL WIDTH (IN.)		SINGLE	DUAL	SINGLE	DUAL		
225/70R19.5	540040	G / 14	128/126N	(6.00) -6.75	68	21	32.4	8.3	14.8	3970	3750	110	110	642	87
245/70R19.5	540050	G / 14	133/131N	6.75- (7.50)	79	22	33.6	9.9	15.2	4540	4300	110	110	619	87
22.5-24.5															
11R22.5	540100	G / 14	144/142L	7.50- (8.25)	128	27	41.9	11.1	19.5	6175	5840	105	105	495	75
11R22.5	540090	H / 16	146/143L	7.50- (8.25)	128	27	41.9	11.1	19.5	6610	6005	120	120	495	75
295/75R22.5	540170	G / 14	144/141L	(8.25) -9.00	127	27	40.7	11.1	18.9	6175	5675	110	110	510	75
315/80R22.5	540190	L / 20	157/154L	(9.00) -9.75	174	29	43.1	12.3	20.1	9090	8270	130	130	481	75
11R24.5	540140	H / 16	149/146L	7.50- (8.25)	139	27	43.9	11.1	20.4	7160	6610	120	120	473	75
285/75R24.5	540160	G / 14	144/141L	8.25	132	27	41.9	10.8	19.5	6175	5675	110	110	496	75

Bold designates measuring rim width.

*Inflated dimensions. Never exceed wheel manufacturer's load and inflation limits.