


VR213



Fixed **Recessed Downlight**




VR2138W

CODE	VR2138W
Dimension(mm)	Φ118x48mm
Cutout (mm)	Φ90mm
System power (W)	8W
Input Voltage(V)	220-240VAC 50/60Hz
Light Source	Osram SMD
SDCM	<5
CCT(K)	3000K/4000K standard. Different CCT upon request.
Luminous (lm) ±5%	120 lm/W
CRI	Ra>80
Beam Angle (°)	120°
LED Driver	External LED driver
Dimming Option	On-off / 1-10v / Triac / Dali
UGR	<19
IP Rating	IP20
Product Colour	White
Materials	Aluminum Die-casting
Lifetime (hr)	50,000h
Operating Temp.	-20°~50°

Code	CCT	BEAM
VR2138WC3	3000K	120°
VR2138WC4	4000K	120°






VR21310W

CODE	VR21310W
Dimension(mm)	Φ143X52mm
Cutout (mm)	Φ115mm
System power (W)	10W
Input Voltage(V)	220-240VAC 50/60Hz
Light Source	Osram SMD
SDCM	<5
CCT(K)	3000K/4000K standard. Different CCT upon request.
Luminous (lm) ±5%	120 lm/W
CRI	Ra>80
Beam Angle (°)	120°
LED Driver	External LED driver
Dimming Option	On-off / 1-10v / Triac / Dali
UGR	<19
IP Rating	IP20
Product Colour	White
Materials	Aluminum Die-casting
Lifetime (hr)	50,000h
Operating Temp.	-20°~50°

Code	CCT	BEAM
VR21310WC3	3000K	120°
VR21310WC4	4000K	120°






VR21316W

CODE	VR21316W
Dimension(mm)	Φ178X57mm
Cutout (mm)	Φ145mm
System power (W)	16W
Input Voltage(V)	220-240VAC 50/60Hz
Light Source	Osram SMD
SDCM	<5
CCT(K)	3000K/4000K standard. Different CCT upon request.
Luminous (lm) ±5%	120 lm/W
CRI	Ra>80
Beam Angle (°)	120°
LED Driver	External LED driver
Dimming Option	On-off / 1-10v / Triac / Dali
UGR	<19
IP Rating	IP20
Product Colour	White
Materials	Aluminum Die-casting
Lifetime (hr)	50,000h
Operating Temp.	-20°~50°

Code	CCT	BEAM
VR21316WC3	3000K	120°
VR21316WC4	4000K	120°






VR21324W

CODE	VR21324W
Dimension(mm)	Φ192X58mm
Cutout (mm)	Φ160mm
System power (W)	24W
Input Voltage(V)	220-240VAC 50/60Hz
Light Source	Osram SMD
SDCM	<5
CCT(K)	3000K/4000K standard. Different CCT upon request.
Luminous (lm) ±5%	120 lm/W
CRI	Ra>80
Beam Angle (°)	120°
LED Driver	External LED driver
Dimming Option	On-off / 1-10v / Triac / Dali
UGR	<19
IP Rating	IP20
Product Colour	White
Materials	Aluminum Die-casting
Lifetime (hr)	50,000h
Operating Temp.	-20°~50°

Code	CCT	BEAM
VR21324WC3	3000K	120°
VR21324WC4	4000K	120°





VR21336W

CODE	VR21336W
Dimension(mm)	Φ232X62mm
Cutout (mm)	Φ205mm
System power (W)	36W
Input Voltage(V)	220-240VAC 50/60Hz
Light Source	Osram SMD
SDCM	<5
CCT(K)	3000K/4000K standard. Different CCT upon request.
Luminous (lm) ±5%	120 lm/W
CRI	Ra>80
Beam Angle (°)	120°
LED Driver	External LED driver
Dimming Option	On-off / 1-10v / Triac / Dali
UGR	<19
IP Rating	IP20
Product Colour	White
Materials	Aluminum Die-casting
Lifetime (hr)	50,000h
Operating Temp.	-20°~50°

Code	CCT	BEAM
VR21336WC3	3000K	120°
VR21336WC4	4000K	120°

