



VR312 Tiltable Recessed Downlight



CODE	VR3127W	VR31210W	VR31218W	VR31221W
Dimension(mm)	Φ65x80mm	Φ85x80mm	Φ85x95mm	Φ105x110mm
Cutout (mm)	Φ55mm	Φ75mm	Φ75mm	Φ95mm
System power (W)	7W	9W	18W	21.6W
Input Voltage(V)	220-240VAC 50/60Hz			
Light Source	Osram COB			
SDCM	<5			
CCT(K)	3000K/4000K standard. Different CCT upon request.			
Luminous (lm) ±5%	140 lm/W			
CRI	Ra>80			
Beam Angle (°)	15°/24°/38°/55°			
LED Driver	External LED driver			
Dimming Option	On-off / 1-10v / Triac / Dali			
UGR	<19			
IP Rating	IP20			
Product Colour	Black			
Baffle Colour	Matt Black / Matt White / Silver			
Materials	Aluminum Die-casting			
Lifetime (hr)	50,000h			
Operating Temp.	-20°~50°			



Matt White Baffle

Matt Black Baffle

Sliver Baffle

Code	VR3127W	
	CCT	BEAM
VR3127WC3B15	3000K	15°
VR3127WC4B15	4000K	15°
VR3127WC3B24	3000K	24°
VR3127WC4B24	4000K	24°
VR3127WC3B38	3000K	38°
VR3127WC4B38	4000K	38°
VR3127WC3B55	3000K	55°
VR3127WC4B55	4000K	55°

Code	VR31210W	
	CCT	BEAM
VR31210WC3B15	3000K	15°
VR31210WC4B15	4000K	15°
VR31210WC3B24	3000K	24°
VR31210WC4B24	4000K	24°
VR31210WC3B38	3000K	38°
VR31210WC4B38	4000K	38°
VR31210WC3B55	3000K	55°
VR31210WC4B55	4000K	55°

Code	VR31218W	
	CCT	BEAM
VR31218WC3B15	3000K	15°
VR31218WC4B15	4000K	15°
VR31218WC3B24	3000K	24°
VR31218WC4B24	4000K	24°
VR31218WC3B38	3000K	38°
VR31218WC4B38	4000K	38°
VR31218WC3B55	3000K	55°
VR31218WC4B55	4000K	55°

Code	VR31221W	
	CCT	BEAM
VR31221WC3B15	3000K	15°
VR31221WC4B15	4000K	15°
VR31221WC3B24	3000K	24°
VR31221WC4B24	4000K	24°
VR31221WC3B38	3000K	38°
VR31221WC4B38	4000K	38°
VR31221WC3B55	3000K	55°
VR31221WC4B55	4000K	55°

