



VRL5570



**Linear Profile
DOWNLIGHT**




VRL5570F4

CODE	VRL5570F4
Dimension(mm)	1232x55x70mm
System power (W)	31W
Input Voltage(V)	AC 100-277V 50/60hz
Light Source	SMD2835
SDCM	<5
CCT(K)	3000K/4000K standard. Different CCT upon request.
Luminous (lm) ±5%	2467-3077lm
CRI	Ra>85
Beam Angle (°)	96°
LED Driver	Built-in Power supply
Dimming Option	On-off / 1-10v / DAL / Triac
IP Rating	IP20
Product Colour	White /Black/ Silver
Materials	Aluminum 6063-T5,
Lifetime (hr)	50,000h
Operating Temp.	-20°C~+45°C

4ft Surface Mounted Code	CCT	COLOR
VRL5570F4SC3WH	3000K	White
VRL5570F4SC4WH	4000K	White
VRL5570F4SC3BL	3000K	Black
VRL5570F4SC4BL	4000K	Black
VRL5570F4SC3SI	3000K	Silver
VRL5570F4SC4SI	4000K	Silver

4ft Pendant Code	CCT	COLOR
VRL5570F4PC3WH	3000K	White
VRL5570F4PC4WH	4000K	White
VRL5570F4PC3BL	3000K	Black
VRL5570F4PC4BL	4000K	Black
VRL5570F4PC3SI	3000K	Silver
VRL5570F4PC4SI	4000K	Silver





VRL5570F8

CODE	VRL5570F8
Dimension(mm)	2451x55x70mm
System power (W)	61W
Input Voltage(V)	AC 100-277V 50/60hz
Light Source	SMD2835
SDCM	<5
CCT(K)	3000K/4000K standard. Different CCT upon request.
Luminous (lm) ±5%	5804-6155lm
CRI	Ra>85
Beam Angle (°)	96°
LED Driver	Built-in Power supply
Dimming Option	On-off / 1-10v / DAL / Triac
IP Rating	IP20
Product Colour	White /Black/ Silver
Materials	Aluminum 6063-T5,
Lifetime (hr)	50,000h
Operating Temp.	-20°C~+45°C

8ft Surface Mounted Code	CCT	COLOR
VRL5570F8SC3WH	3000K	White
VRL5570F8SC4WH	4000K	White
VRL5570F8SC3BL	3000K	Black
VRL5570F8SC4BL	4000K	Black
VRL5570F8SC3SI	3000K	Silver
VRL5570F8SC4SI	4000K	Silver

8ft Pendant Code	CCT	COLOR
VRL5570F8PC3WH	3000K	White
VRL5570F8PC4WH	4000K	White
VRL5570F8PC3BL	3000K	Black
VRL5570F8PC4BL	4000K	Black
VRL5570F8PC3SI	3000K	Silver
VRL5570F8PC4SI	4000K	Silver

