


VRM





**Modular
DOWNLIGHT**




VRM6W

CODE	VRM6W
Dimension(mm)	Ø55x49
System power (W)	6W
Input Voltage(V)	220-240VAC 50/60Hz
Light Source	Bridgelux
SDCM	<3
CCT(K)	3000K/4000K standard. Different CCT upon request.
Luminous (lm) ±5%	550lm
CRI	Ra>90
Beam Angle (°)	15° / 24°/38° / 55°
LED Driver	External LED driver
Dimming Option	On-off / 1-10v / Triac / Dali
IP Rating	IP44
Product Colour	Black
Materials	Aluminum Die-casting
Lifetime (hr)	50,000h
Operating Temp.	-20°~50°

Code	CCT	BEAM
VRM6WC3B15	3000K	15°
VRM6WC4B15	4000K	15°
VRM6WC3B24	3000K	24°
VRM6WC4B24	4000K	24°
VRM6WC3B38	3000K	38°
VRM6WC4B38	4000K	38°
VRM6WC3B55	3000K	55°
VRM6WC4B55	4000K	55°









VRM9W

CODE	VRM9W
Dimension(mm)	Ø55x49
System power (W)	9W
Input Voltage(V)	220-240VAC 50/60Hz
Light Source	Bridgelux
SDCM	<3
CCT(K)	3000K/4000K standard. Different CCT upon request.
Luminous (lm) ±5%	900lm
CRI	Ra>90
Beam Angle (°)	15° / 24°/38° / 55°
LED Driver	External LED driver
Dimming Option	On-off / 1-10v / Triac / Dali
IP Rating	IP44
Product Colour	Black
Materials	Aluminum Die-casting
Lifetime (hr)	50,000h
Operating Temp.	-20°~50°

Code	CCT	BEAM
VRM9WC3B15	3000K	15°
VRM9WC4B15	4000K	15°
VRM9WC3B24	3000K	24°
VRM9WC4B24	4000K	24°
VRM9WC3B38	3000K	38°
VRM9WC4B38	4000K	38°
VRM9WC3B55	3000K	55°
VRM9WC4B55	4000K	55°







VRM15W



CODE	VRM15W
Dimension(mm)	Ø55x72
System power (W)	15W
Input Voltage(V)	220-240VAC 50/60Hz
Light Source	Bridgelux
SDCM	<3
CCT(K)	3000K/4000K standard. Different CCT upon request.
Luminous (lm) ±5%	1500lm
CRI	Ra>90
Beam Angle (°)	15° / 24°/38° / 55°
LED Driver	External LED driver
Dimming Option	On-off / 1-10v / Triac / Dali
IP Rating	IP44
Product Colour	Black
Materials	Aluminum Die-casting
Lifetime (hr)	50,000h
Operating Temp.	-20°~50°

Code	CCT	BEAM
VRM15WC3B15	3000K	15°
VRM15WC4B15	4000K	15°
VRM15WC3B24	3000K	24°
VRM15WC4B24	4000K	24°
VRM15WC3B38	3000K	38°
VRM15WC4B38	4000K	38°
VRM15WC3B55	3000K	55°
VRM15WC4B55	4000K	55°





VRM Modular Trim

VRT1SRS Recessed /Adjustable 25°





Dimension(mm)	85x85x52mm
Cutout (mm)	75x75mm
Surface Color:	White / Black

VRT2SRS Recessed /Adjustable 25°





Dimension(mm)	154.5x85x51mm
Cutout (mm)	140x75mm
Surface Color:	White / Black

VRT3SRS Recessed /Adjustable 25°





Dimension(mm)	280x100x67mm
Cutout (mm)	270x90mm
Surface Color:	White / Black

VRT1RRS Recessed /Trimless/Adjustable 25°





Dimension(mm)	120x120x67mm
Cutout (mm)	90x90mm
Surface Color:	White / Black

VRT2RRS Recessed /Trimless/Adjustable 25°




Dimension(mm)	210x120x67mm
Cutout (mm)	180x90mm
Surface Color:	White / Black

VRT3RRS Recessed /Trimless/Adjustable 25°




Dimension(mm)	300x120x67mm
Cutout (mm)	270x90mm
Surface Color:	White / Black

VRT1UG Recessed / Anti Glare



Dimension(mm)	Ø90x37mm
Cutout (mm)	Ø80mm
Surface Color:	White / Black



VRT1UGS Recessed / Anti Glare



Dimension(mm)	90x90x37mm
Cutout (mm)	80x80mm
Surface Color:	White / Black


VRM Modular Trim

VRT2UGS Recessed / Anti Glare




Dimension(mm)	175x90x37mm
Cutout (mm)	165x80mm
Surface Color:	White / Black

VRT1R Recessed / Adjustable 25°




Dimension(mm)	Ø85x52mm
Cutout (mm)	Ø75mm
Surface Color:	White / Black

VRT1F Recessed / Fixed




Dimension(mm)	Ø85x52mm
Cutout (mm)	Ø75mm
Surface Color:	White / Black

VRT1RR Recessed / Trimless/Adjustable 25°




Dimension(mm)	Ø85x52mm
Cutout (mm)	Ø75mm
Surface Color:	White / Black

VRT1RF Recessed / Trimless/Fixed





Dimension(mm)	Ø85x52
Cutout (mm)	Ø75W
Surface Color:	White / Black

VRT71RIP54 Recessed / Shower light IP54




Dimension(mm)	Ø88x48mm
Cutout (mm)	Ø75mm
Surface Color:	White / Black

VRT71SIP54 Recessed / Shower light IP54



Dimension(mm)	88x88x48mm
Cutout (mm)	75x75mm
Surface Color:	White / Black



VRT79RIP54 Recessed / Shower light IP54



Dimension(mm)	Ø105x48mm
Cutout (mm)	Ø90mm
Surface Color:	White / Black


VRM Modular Trim

VRT11R Recessed / Fixed




Dimension(mm)	Ø68x27mm
Cutout (mm)	Ø60mm
Surface Color:	White / Black

VRT12R Recessed / Fixed




Dimension(mm)	Ø85x30mm
Cutout (mm)	Ø75mm
Surface Color:	White / Black

VRT34R Recessed /Deep/Fixed




Dimension(mm)	Ø85x53mm
Cutout (mm)	Ø75mm
Surface Color:	White / Black

VRT1087R Recessed /Deep/Fixed




Dimension(mm)	Ø88x40mm
Cutout (mm)	Ø75W
Surface Color:	White / Black

VRT1088S Recessed /Deep Square/Fixed




Dimension(mm)	88x88x39mm
Cutout (mm)	75x75W
Surface Color:	White / Black

VRT1089R Recessed /Deep/Fixed





Dimension(mm)	Ø88x47mm
Cutout (mm)	Ø75mm
Surface Color:	White / Black

VRT1090R Recessed /Deep Cone/Fixed



Dimension(mm)	Ø88x48
Cutout (mm)	Ø75W
Surface Color:	White / Black

VRT1091S Recessed /Deep Square/Fixed



Dimension(mm)	88x88x47
Cutout (mm)	75x75W
Surface Color:	White / Black