


VRWPE



Waterproof DOWNLIGHT




VRWPE40W

CODE	VRWPE40W
Dimension(mm)	1200x85x75mm
System power (W)	40W
Input Voltage(V)	AC 220-240V 50/60hz
Light Source	LED SMD
SDCM	<3
CCT(K)	3000K/4000K standard. Different CCT upon request.
Luminous (lm) ±5%	120lm/w
CRI	Ra>80
Beam Angle (°)	120°
PF0.	9
LED Driver	PHILIPS
Dimming Option	On-off / 1-10v / Triac / Dali
IP Rating	IP66
Product Colour	Grey base
Materials	Opal PC Cover + PC base + Stainless Steel Clips
Lifetime (hr)	50,000h
Operating Temp.	-20°~40°

Code	CCT	BEAM
VRWPE40WC3	3000K	120°
VRWPE40WC4	4000K	120°
VRWPE40WC6	6000K	120°
VRWPE40WCD	3CCT	120°






VRWPE50W

CODE	VRWPE50W
Dimension(mm)	1500x85x75mm
System power (W)	50W
Input Voltage(V)	AC 220-240V 50/60hz
Light Source	LED SMD
SDCM	<3
CCT(K)	3000K/4000K standard. Different CCT upon request.
Luminous (lm) ±5%	120lm/w
CRI	Ra>80
Beam Angle (°)	120°
PF0.	9
LED Driver	PHILIPS
Dimming Option	On-off / 1-10v / Triac / Dali
IP Rating	IP66
Product Colour	Grey base
Materials	Opal PC Cover + PC base + Stainless Steel Clips
Lifetime (hr)	50,000h
Operating Temp.	-20°~40°

Code	CCT	BEAM
VRWPE50WC3	3000K	120°
VRWPE50WC4	4000K	120°
VRWPE50WC6	6000K	120°
VRWPE50WCD	3CCT	120°





VRWPE60W

CODE	VRWPE60W
Dimension(mm)	1500x85x75mm
System power (W)	60W
Input Voltage(V)	AC 220-240V 50/60hz
Light Source	LED SMD
SDCM	<3
CCT(K)	3000K/4000K standard. Different CCT upon request.
Luminous (lm) ±5%	120lm/w
CRI	Ra>80
Beam Angle (°)	120°
PF0.	9
LED Driver	PHILIPS
Dimming Option	On-off / 1-10v / Triac / Dali
IP Rating	IP66
Product Colour	Grey base
Materials	Opal PC Cover + PC base + Stainless Steel Clips
Lifetime (hr)	50,000h
Operating Temp.	-20°~40°

Code	CCT	BEAM
VRWPE60WC3	3000K	120°
VRWPE60WC4	4000K	120°
VRWPE60WC6	6000K	120°
VRWPE60WCD	3CCT	120°

