

BRITISH PRODUCT OVERVIEW

INDOOR



| | | FireSmoke 44 6 mm MDF face | | FireSmoke 54 6 mm Chipface | | FireSmoke Xtreme 58 3 mm MDF face | | FireSound 44 mm 3 mm MDF face | | FireSound 54 mm 3 mm MDF face | | FireSound 59 mm 3 mm MDF face | | FireSound Xtreme 58 mm 3 mm MDF face | |
|-------------------------|------------|-------------------------------|--------|-------------------------------|-----------|--------------------------------------|------------|----------------------------------|--------|----------------------------------|------------|----------------------------------|------------|---|-----------------|
| Fire rating | | flush | glazed | flush | glazed | flush | glazed | flush | glazed | flush | glazed | flush | glazed | flush | glazed |
| BS 476 Part22 | SD | FD30 | FD30 | FD30/FD60 | FD30/FD60 | FD60/FD90 | FD60/FD90 | FD30 | FD30 | FD30/FD60 | FD30/FD60 | FD30/FD60 | FD30/FD60 | FD60/FD90/FD120 | FD60/FD90/FD120 |
| | DD | FD30 | FD30 | FD30/FD60 | FD30/FD60 | FD60/FD90 | FD60/FD90 | FD30 | FD30 | FD30/FD60 | FD30/FD60 | FD30/FD60 | FD30/FD60 | FD60/FD90 | FD60/FD90 |
| Acoustic value Rw | SD | 32 dB | - | 35 dB | 37 dB | 37 dB | 37 - 38 dB | 40 dB | 39 dB | 40 dB | 39 dB | 43 dB | 40 - 41 dB | 44 dB | 41 dB |
| | DD | - | - | 36 dB | 37 dB | 37 dB | 37 - 38 dB | 39 dB | 38 dB | 40 dB | 39 - 40 dB | 44 dB | 41 - 42 dB | 43 dB | 41 - 42 dB |
| + clad-on panels (25mm) | SD | - | - | 40 - 43 dB | - | 41 - 43 dB | - | - | - | 42 - 46 dB | - | 44 - 46 dB | - | - | - |
| Interconnecting doors | SD | 55 dB* | - | 54 dB* | - | - | - | 57 dB* | - | 56 - 57 dB* | - | 53 - 68 dB** | - | - | - |
| Concealed hardware | | - | - | ✓ | - | - | - | - | - | ✓ | - | ✓ | - | - | - |
| Access systems | | - | - | Electronic locks / RFID | | - | - | - | - | Electronic locks / RFID | | Electronic locks / RFID | | - | - |
| Service life testing | EN1191 | 500.000 cycles | | 500.000 cycles | | - | - | - | - | - | - | 500.000 cycles | | - | - |
| | EN1192 | severe duty | | severe duty | | - | - | - | - | - | - | - | - | - | - |
| | BS EN 6375 | - | - | PAS24 | | - | - | - | - | - | - | - | - | - | - |
| Weight [kg/m²] | | 29 | - | 35 | - | 40 | - | 32 | - | 40 | - | 44 | - | 51 | |
| U-value [W/m²K] | | 1,97 | - | 1,71 | - | 2,2 | - | 1,9 | - | 1,9 | - | 1,51 | - | 2,2 | |
| Climatic perform. | EN1530 | b, c, 3 | | b, c, 4 | | - | - | - | - | b, c, 3 | | b, c, 3 | | - | |
| NAUF | | on request | | on request | | on request | | on request | | on request | | on request | | on request | |
| FSC®/ PEFC | | ✓ | | ✓ | | ✓ | | ✓ | | ✓ | | ✓ | | ✓ | |

* in combination with FireSound 44/54/59 mm

** + clad-on panels (25 mm)

Any Questions?

Moralt AG, Obere Tiefenbachstrasse 1, D-83734 Hausham

Phone: +49 8026 92538-11, E-Mail: info@moralt-ag.de, www.moralt-ag.com



INTERNATIONAL PRODUCT OVERVIEW

INTERNAL DOORBLANKS



| | | FireSmoke 54 mm 6 mm Chipface | | FireSmoke Xtreme 58 mm 3 mm MDF face | | SmartCore 55 mm 22 mm Chipface | | FireSound 44 mm 3 mm MDF face | | FireSound 54 mm 3 mm MDF face | | FireSound 59 mm 3 mm MDF face | | FireSound Xtreme 58 mm 3 mm MDF face | | |
|------------------------------------|--------------|----------------------------------|-----------|---|------------|-----------------------------------|------------|----------------------------------|--------|----------------------------------|------------|----------------------------------|------------|---|-----------------|-----------------|
| Fire rating | | flush | glazed | flush | glazed | flush | glazed | flush | glazed | flush | glazed | flush | glazed | flush | glazed | |
| BS 476 Part22 | timber frame | SD | FD30/FD60 | FD30/FD60 | FD60/FD90 | FD60/FD90 | FD60 | - | FD30 | FD30 | FD30/FD60 | FD30/FD60 | FD30/FD60 | FD30/FD60 | FD60/FD90/FD120 | FD60/FD90/FD120 |
| | DD | FD30/FD60 | FD30/FD60 | FD60/FD90 | FD60/FD90 | - | - | FD30 | FD30 | FD30/FD60 | FD30/FD60 | FD30/FD60 | FD30/FD60 | FD30/FD60 | FD60/FD90 | FD60/FD90 |
| UL10C | timber frame | SD | - | - | 20/45/60 | - | - | - | - | 20/45/60 | - | 20/45/60 | - | 20/45/60 | - | - |
| | DD | - | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Acoustic value STC/Rw _p | SD | 35 dB | 37 dB | 37 dB | 37 - 38 dB | 40 dB | 37 - 38 dB | 40 dB | 39 dB | 40 dB | 39 dB | 43 dB | 40 - 41 dB | 44 dB | 41 dB | |
| | DD | 36 dB | 37 dB | 37 dB | 37 - 38 dB | 39 dB | 37 - 38 dB | 39 dB | 38 dB | 40 dB | 39 - 40 dB | 44 dB | 41 - 42 dB | 43 dB | 41 - 42 dB | |
| + clad-on panels (25mm) | SD | 40 - 43 dB | - | 41 - 43 dB | - | - | - | - | - | 42 - 46 dB | - | 44 - 46 dB | - | - | - | |
| Interconnecting doors | SD | 55 dB* | - | - | - | - | - | 57 dB* | - | 56 - 57 dB* | - | 53 - 68 dB** | - | - | - | |
| Concealed hardware | | ✓ | | - | | ✓ | | - | | ✓ | | ✓ | | - | | |
| Access systems | | Electronic locks / RFID | | | | Electronic locks / RFID | | | | Electronic locks / RFID | | Electronic locks / RFID | | | | |
| Service life testing | EN1191 | 500.000 cycles | | | | | | | | Electronic locks / RFID | | 500.000 cycles | | | | |
| | EN1192 | severe duty | | | | | | | | | | | | | | |
| | BS EN 6375 | PAS24 | | | | | | | | | | | | | | |
| Weight [kg/m ²] | | 35 | | 40 | | 40 | | 32 | | 40 | | 44 | | 51 | | |
| U-value [W/m ² K] | | 1,71 | | 2,2 | | 1,8 | | 1,9 | | 1,9 | | 1,51 | | 2,2 | | |
| Climatic perform. | EN1530 | b, c, 4 | | | | | | | | b, c, 3 | | b, c, 3 | | | | |
| NAUF | | on request | | on request | | on request | | on request | | on request | | on request | | on request | | |
| FSC®/ PEFC | | ✓ | | ✓ | | ✓ | | ✓ | | ✓ | | ✓ | | ✓ | | |

* in combination with FireSound 44/54/59mm

** + clad-on panels (25mm)

Any Questions?

Moralt AG, Obere Tiefenbachstrasse 1, D-83734 Hausham

Phone: +49 8026 92538-11, E-Mail: info@moralt-ag.de, www.moralt-ag.com

warringtonfire



PRODUKTÜBERSICHT EUROPA

ROHLINGE INNENTÜREN



| | | Klassik 38 – 44 mm 3 – 6 mm MDF Deck | | FireSmoke 44 6 mm MDF Deck | | FireSmoke 54 6 mm MDF Deck | | FireSmoke Sandwich 54 mm 6 mm MDF Deck | | FireSound 54 mm 3 mm MDF Deck | | FireSound 59 mm 3 mm MDF Deck | | FireSafe Akustik 68 – 98 mm Furnierdeck /MDF Deck | |
|------------------------------|-------------|---|----------|----------------------------------|----------------------------------|----------------------------------|----------------------------------|---|----------------------------------|----------------------------------|------------|----------------------------------|------------|--|----------------------------------|
| Feuerschutz/Rauchschutz | | ohne LA | verglast | ohne LA | verglast | ohne LA | verglast | ohne LA | verglast | ohne LA | verglast | ohne LA | verglast | ohne LA | verglast |
| EN1634-1 | einflg. | - | - | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 |
| | zweiflg. | - | - | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 |
| EN1634-3 | einflg. | - | - | S _a /S ₂₀₀ | S _a /S ₂₀₀ | - | - | - | - | S _a /S ₂₀₀ | S _a /S ₂₀₀ |
| | zweiflg. | - | - | S _a /S ₂₀₀ | S _a /S ₂₀₀ | - | - | - | - | S _a /S ₂₀₀ | S _a /S ₂₀₀ |
| EN1191 | einflg. | - | - | C - C5 | C - C5 | - | - | - | - | C - C5 | C - C5 |
| | zweiflg. | - | - | C - C5 | C - C5 | - | - | - | - | C - C5 | C - C5 |
| Nation. Zulassung | Deutschland | - | - | T30 (RS) | T30 (RS) | - | - | - | - | - | - |
| | Österreich | - | - | Elz 30 C5 (S200) | Elz 30 C5 (S200) | - | - | - | - | in Bearbeitung | in Bearbeitung |
| | Schweiz | - | - | EI30 | EI30 | EI30 | EI30 | EI30 | EI30 | - | - | - | - | - | - |
| Schallschutz | einflg. | - | - | 32 dB | 37 dB | 35 dB | 37 dB | 37 dB | 37 dB | 43 dB | 42 dB | 43 dB | 42 dB | 44 dB | 44 dB |
| | zweiflg. | - | - | 32 dB | 37 dB | 36 dB | 37 dB | 37 dB | 37 dB | 43 dB | 42 dB | 43 dB | 42 dB | 44 dB | 44 dB |
| + Vorsatzschale | | - | - | 41 - 42 dB | 42 dB | 41 - 44 dB | 42 - 44 dB | 42 - 45 dB | 42 - 45 dB | 44 - 47 dB | 42 - 45 dB | 44 - 47 dB | 42 - 45 dB | - | - |
| Einbruchhemmung | EN1627 | - | - | - | - | RC2/RC3 | RC2/RC3 | RC2/RC3 | RC2/RC3 | - | - | - | - | RC2/RC3 | RC2/RC3 |
| Mech. Festigkeit | EN1192 | Klasse 4 | Klasse 4 | Klasse 4 | Klasse 4 | Klasse 4 | Klasse 4 | Klasse 4 | Klasse 4 | Klasse 4 | Klasse 4 | Klasse 4 | Klasse 4 | Klasse 4 | Klasse 4 |
| Gewicht [kg/m ²] | | 25 | | 29 | | 35 | | 35 | | 40 | | 44 | | 88 - 108 | |
| U-value [W/m ² K] | | 1,97 | | 1,97 | | 1,71 | | 1,71 | | 1,9 | | 1,51 | | 1,2 - 0,78 | |
| Differenzklima | EN1530 | b, c, 3 | | b, c, 3 | | b, c, 4 | | b, c, 4 | | b, c, 3 | | b, c, 3 | | c, d, e, 4 | |
| FSC®/ PEFC | | ✓ | | ✓ | | ✓ | | ✓ | | ✓ | | ✓ | | ✓ | |

Noch Fragen?

Moralt AG, Obere Tiefenbachstraße 1, 83734 Hausham, Deutschland
 Telefon: +49 8026 92538-11, E-Mail: vertrieb@moralt-ag.de, www.moralt-ag.com

