

SCHEMA TECNICA VEICOLO SATELLITE SERIE KVC DUAL "SATELLITE VEHICLE" TECHNICAL INFORMATION - SERIES KVC DUAL



Caratteristiche generali

È il mezzo perfetto nei centri urbani e offre anche la massima adattabilità grazie allo scarico compatibile con compattatori a bocca universale. È il compagno ideale per raccolta differenziata dei rifiuti. La produzione prevede un costipatore da mc 4.5 ribaltabile posteriormente e una vasca da mc 1.6 ribaltabile lateralmente.

L'attrezzatura CM INDUSTRIE SRL, realizzata con adeguate tecniche di costruzione per diminuire i tempi di impiego per la raccolta (sia manuale che con contenitori) è conforme a quanto richiesto dalla UNI EN 1501-1.



General specifications

This is a fundamental "satellite" equipment for the cities, and also offers maximum flexibility through the universal discharge mouth (compatible with larger compactors). It's the perfect team mate for greater compactors, especially in small city environments. The production provides over dumping body with superior compacting shovel and capacity of 4.5 cubic meters of compacted waste refuses, and side dumping body with capacity of 1.6 cubic meters. The CM INDUSTRIES SRL equipment, made with appropriate building techniques to reduce the working hours necessary for (both manual and containers collection). It is built in compliance with the requirements of UNI EN 1501-1.



Dimensioni di ingombro veicolo allestito standard

Modello veicolo <i>Model vehicle</i>		KVC DUAL (COST. MC 4.5 + VASCA MC 1.6)
Volume utile (mc) <i>Body inside volume (c.m.)</i>	m ³	4.5 + 1.6
Rapporto di compattazione <i>Compaction ratio</i>		3:1