

S-Series

S10C

New standard for "all-in-one" Compact Passive Cardioid Subwoofer.

S10C is a combination of horn-loaded 10" driver and second reflex-loaded 10" driver working together as a passive cardioid subwoofer featuring Passive End Fire Technology. This hybrid enclosure design is the most compact passive cardioid sub in S-Series.

Low frequency directivity control with **ONLY ONE** amplifier channel required - no bi-amp presets, multiple subwoofers or complex wiring to achieve directional bass reproduction!

Horn-loading for fast punch and reflex for those lower bass notes: "Best from both worlds" Extremely accurate and dynamic low frequency reproduction.



APPLICATIONS

Noise sensitive installations
Small to medium scale touring
High end installations from night clubs to live music venues
Low frequency extension for i-series and S-series tops

SPECIFICATIONS

Frequency Response (-6 dB): 38 Hz – 120 Hz
Horizontal Coverage (-6 dB): 160 degrees
Vertical Coverage (-6 dB): 160 degrees
Max SPL : 126/132 dB (free space)
Sensitivity, 1w/1m: 101 dB (free space)
Impedance: 4 ohms (nominal)
Power handling: 300 W(rms) 1200W(peak)

DRIVERS

LF: (front) x 10" cone driver, 65mm voice coil
LF: (rear) x 10" cone driver, 52mm voice coil

ENCLOSURE

Enclosure material: Birch plywood, textured black paint finish
Grille: Cold rolled steel grille, textured black paint finish
Connectors: (2) x NL4, +/-1: Input, +/-2: Linked
Dimensions (H/W/D): 310 mm x 560 mm x 830 mm (w/o wheels)
Weight: 38 kg

