


EMERY COUNTY SCHOOL DISTRICT

CLEVELAND ELEMENTARY MECHANICAL UPGRADE


30 SOUTH 100 WEST

CLEVELAND, UTAH




PROJECT CONTACTS

OWNER
EMERY COUNTY SCHOOL DISTRICT
120 NORTH MAIN STREET
HUNTINGTON, UTAH 84528
(435) 687-9846




ARCHITECTURAL
KMA ARCHITECTS, INC.
170 NORTH MAIN STREET
SPANISH FORK, UTAH 84660
(801) 377-5062



STRUCTURAL
DYNAMIC STRUCTURES
744 SOUTH 400 EAST,
OREM, UTAH 84097
(801) 356-1140


MECHANICAL
OLSEN & PETERSON ENGINEERING
14 EAST 2700 SOUTH
SALT LAKE CITY, UTAH 84115
(801) 486-4646



ELECTRICAL
RESOLUT
181 EAST 5600 SOUTH, SUITE 200
MURRAY, UT 84107
(801) 530-3148



GRAPHIC SYMBOLS



PROJECT DATA

MAIN FLOOR AREA 35,411 SQ. FT.
MEZZANINE FLOOR AREA 1,472 SQ. FT.

TOTAL FLOOR AREA 36,883 SQ. FT.

PROJECT SCOPE

CLEVELAND ELEMENTARY SCHOOL MECHANICAL UPGRADE WILL CONSIST OF INSTALLING A NEW NOMINAL TON PACKAGED AIR COOLED CHILLER, REPLACING THE EXISTING FAN COIL UNITS, NEW PUMPS, HOT WATER UNIT HEATERS AND CABINET UNIT HEATER. THE ANTICIPATION FOR THIS PROJECT IS MINIMUM RE-DUCTING AND TYING THE REPLACED UNITS INTO EXISTING DUCT WORK. ELECTRICAL SYSTEMS WILL BE MODIFIED ACCORDINGLY TO MEET THE NEW BUILDINGS NEED AND ARCHITECTURAL REPLACEMENT OF AFFECTED AREAS DUE TO CONSTRUCTION.

INDEX OF DRAWINGS

ARCHITECTURAL

A1.1 - OVERALL MAIN FLOOR PLAN
A1.2 - MEZZANINE FLOOR PLAN

STRUCTURAL

P1.1A - PLUMBING PLAN AREA 'A'
P1.1B - PLUMBING PLAN AREA 'B'
P4.1 - ENLARGED MEZZANINE PLUMBING PLAN
P5.1 - PLUMBING SCHEDULES AND DETAILS

PLUMBING


MECHANICAL

M0.1A - MECHANICAL DEMOLITION PLAN AREA 'A'
M0.1B - MECHANICAL DEMOLITION PLAN AREA 'B'
M0.2 - ENLARGED MEZZANINE MECHANICAL DEMOLITION PLAN
M0.3 - ENLARGED MEZZANINE MECHANICAL DEMOLITION PLAN
M0.4 - ENLARGED MEZZANINE MECHANICAL DEMOLITION PLAN
M1.1A - MECHANICAL PLAN AREA 'A'
M1.1B - MECHANICAL PLAN AREA 'B'
M4.1 - ENLARGED MEZZANINE MECHANICAL PLAN
M4.2 - ENLARGED MEZZANINE MECHANICAL PLAN
M4.3 - ENLARGED MEZZANINE MECHANICAL PLAN
M5.1 - MECHANICAL SCHEDULES

ELECTRICAL

EG001 - ELECTRICAL TITLE SHEET
EG002 - ELECTRICAL SCHEDULES
EG003 - ELECTRICAL ONE-LINE DIAGRAM
EG004 - ELECTRICAL DIAGRAMS
EG005 - ELECTRICAL DIAGRAMS
EP112 - MAIN FLOOR POWER PLAN AREA 'A'
EP113 - MAIN FLOOR POWER PLAN AREA 'B'
EP114 - MEZZANINE POWER PLAN

RENDERING




VICINITY MAP



170 NORTH MAIN STREET
SPANISH FORK, UTAH 84660
www.KMAArchitects.com

KMA
ARCHITECTS



EMERY SCHOOL DISTRICT
CLEVELAND ELEMENTARY SCHOOL
MECHANICAL UPGRADE
CLEVELAND, UTAH

PROJECT TITLE


CLEVELAND ELEMENTARY SCHOOL
MECHANICAL UPGRADE
30 S 100 W

DRAWN BY: STAFF
CHECKED BY: WC
DATE: JAN 2026
PROJECT #: 176525

TITLE

SHEET NOTES

- EXISTING FLOOR TO BE SAW CUT AT HATCHED LOCATIONS.
- EXISTING CONSTRUCTION TO REMAIN. CONTRACTOR TO PATCH, REPAIR, AND CLEAN AS REQUIRED DUE TO DEMOLITION AND NEW CONSTRUCTION.
- NEW 4" THICK CONCRETE EQUIPMENT PAD - COORDINATE WITH MECHANICAL SHEETS ON SIZE AND LOCATION.




GENERAL NOTES

A - COORDINATE WITH MECHANICAL PLANS FOR ADDITIONAL DEMOTION OF MECHANICAL SYSTEMS

B - ADDITIONAL CEILINGS MAY NEED TO BE DEMOLISHED THAT MAY NOT BE NOTED. TO PROVIDE ADDITIONAL ACCESS FOR THE MECHANICAL SYSTEM AND CONTROLS. CONTRACTOR IS TO PLAN ON WORKING ABOVE AND AROUND THE CEILINGS AND NOT TO DAMAGE THE CEILINGS, CEILING GRID, THE GRIDS, EXISTING LIGHTING, FIRE ALARM, AND ANY GYPSUM BOARD MATERIAL FROM ANY DAMAGE. THE CONTRACTOR SHALL REPLACE ANY DAMAGED MATERIALS.

KEY PLAN



PROJECT TITLE: CLEVELAND ELEMENTARY SCHOOL
MECHANICAL UPGRADE
CLEVELAND, UTAH

170 NORTH MAIN STREET
SPANISH FORK, UTAH 84660
www.kmaarchitects.com



REVISIONS:

PROJECT TITLE

DRAWN BY: KMA
CHECKED BY: WC
DATE: JAN 2026
PROJECT #: 176525

A1.1


SHEET NOTES

- 1 - EXISTING CONSTRUCTION TO REMAIN. CONTRACTOR TO PATCH, REPAIR, AND CLEAN AS REQUIRED DUE TO DEMOLITION AND NEW CONSTRUCTION.
- 2 - EXISTING PLYWOOD MEZZANINE FLOOR SHEATHING TO REMAIN. CONTRACTOR TO FILL IN GAPS AND HOLES AS REQUIRED. EXISTING DAMAGED SHEATHING TO BE REPLACED WITH NEW SHEATHING (MATCH EXISTING).
- 3 - NEW MECHANICAL UNITS - SEE MECHANICAL SHEETS.
- 4 - CONTRACTOR IS TO REMOVE EXISTING EXTERIOR AIR DUCT AND INCREASE OPENING REQUIRED FOR ACCESS INTO MEZZANINE. PATCH AND REPAIR OPENING ONCE UNITS HAVE BEEN INSTALLED - COORDINATE DEMOLITION WITH MECHANICAL PLANS
- 5 - CONTRACTOR IS TO REMOVE THE HATCHED CEILING TO ALLOW ACCESS FOR EXISTING EQUIPMENT TO BE REMOVED AND NEW EQUIPMENT TO BE INSTALLED. CONTRACTOR IS TO REPLACE THE CEILING DUE TO CONSTRUCTION.
- 6 - EXISTING ROOF AREA - PATCH AND REPAIR AS NEEDED DUE TO CONSTRUCTION


GENERAL NOTES

A - COORDINATE WITH MECHANICAL PLANS FOR ADDITIONAL DEMOTION OF MECHANICAL SYSTEMS

B - ADDITIONAL CEILINGS MAY NEED TO BE DEMOLISHED THAT WILL BE NEEDED TO PROVIDE ACCESS FOR THE MECHANICAL SYSTEM AND CONTROLS. CONTRACTOR IS TO PLAN ON WORKING ABOVE AND AROUND THE CEILINGS AND TO BE CAREFUL TO PROTECT THE CEILING TILES, THE GRIDS, EXISTING LIGHTS, FIRE ALARM, AND ANY GYPSUM BOARD. EXISTING ROOF AND DRAIN CONTRACTOR SHALL REPLACE ANY DAMAGED MATERIALS.




MEZZANINE FLOOR PLAN - AREA 'A'
1/4" = 1'-0"



MEZZANINE FLOOR PLAN - AREA 'B'
1/4" = 1'-0"

MEZZANINE KEY PLAN



PROJECT TITLE: CLEVELAND ELEMENTARY SCHOOL
DRAWN BY: KMA
CHECKED BY: W.C.
DATE: JAN. 2026
PROJECT #: 176525

A1.2

REFERENCE NOTES

WASTE PIPING TO DROP IN WALL FROM MEZZANINE
ABOVE TO BELOW EXSITING FLOOR.

CONNECT TO EXISTING AT APPROXIMATELY THIS
LOCATION. SAWCUT AS NEEDED, COORDIANTE WITH
ARCHITECT.

consulting engineers, inc.

170 NORTH MAIN STREET
SPANISH FORK, UTAH 84660
WWW.KMAARCHITECTS.COM

KIVIA ARCHITECTS

A circular stamp with a decorative border. The text 'MISSION BAPTIST' is curved along the top inner edge, and 'ENGINEER' is curved along the right inner edge. In the center, the text '4-2202' is printed above 'BAPTIST' and '2026' is printed below 'MISSION'.

6.

CLEVELAND, UTAH MECHANICAL UPGRADE

100 W

30 S
BY: STAFF
BY: M.T.
JAN. 2026
#: 176525

1A

This architectural floor plan illustrates the layout of a school building across four floors (1, 2, 3, 4) and two sections (A, B, C, D, E, F, G, H). The plan includes a detailed piping system with various pipe sizes and fittings, particularly in the central corridor area (Section D).

Rooms and Areas:

- Section A:** Includes a CAFETERIA (44), EXT. STORAGE (38), and COATS (37).
- Section B:** Includes a RESTROOM (41), STORAGE (43), JAN. (40), and RESTROOM (39).
- Section C:** Includes a CLASSROOM (46), SPECIAL ED. (47), SPECIAL ED. (48), CORR. (42), and CORR. (28).
- Section D:** Includes a CLASSROOM (50), CLASSROOM (51), CIRC. (56), A.V. STOR. (57), HALL (53), STORAGE (75), and CORRIDOR (49).
- Section E:** Includes a MEDIA (58), WORKROOM (59), and CORRIDOR (49).
- Section F:** Includes a STAFF (60), WORKROOM (54), CORR. (63), T. (62), T. (64), and RESOURCE (61).
- Section G:** Includes a CORRIDOR (67), RESTROOM (68), DN, CLASSROOM (52), TOILET (69), STORAGE (7), NURSE (5), TOILET (4), ADMIN. (6), PRINCIPAL (8), CONF. (3), and UP.
- Section H:** Includes a KINDERGARTEN (36), CORR. & RAMP (28), TOILET (35), STORAGE (33), and CORR. (28).

Piping and Fittings:


The piping system is detailed with various fittings and pipe sizes:

- Horizontal piping is shown with arrows indicating flow direction.
- Key pipe sizes and fittings include:
 - 4" (E) pipes are shown in several locations, including a main horizontal run and a vertical section.
 - 2" (E) pipes are also present in various sections.
 - Valves and fittings are indicated by symbols, such as a valve labeled '1' and a fitting labeled 'L-2".'
 - A circulator pump is located in the CIRC. (56) area.
 - A check valve is located in the A.V. STOR. (57) area.
 - A vertical pipe section is labeled 'UP' at the bottom.

PLUMBING PLAN AREA A

A scale bar and a north arrow are positioned at the bottom of the drawing. The scale bar is a horizontal line with tick marks and labels: '0', '4' - 0"', '8' - 0"', and '16' - 0"'. Below the scale bar is the text 'SCALE: 1/8" = 1'-0''. To the right of the scale bar is a north arrow consisting of a circle with a diagonal line, labeled 'NORTH'.

The diagram, titled "KEY PLAN" in large, bold, black capital letters at the top, illustrates a layout with two distinct areas.
Area "A" is represented by a gray shaded region with a jagged, stepped boundary. The text "AREA 'A'" is centered within this region in large, bold, black capital letters.
Area "B" is represented by a white region with a black-outlined jagged, stepped boundary. The text "AREA 'B'" is centered within this region in large, bold, black capital letters.
The two areas are separated by a thin black line representing a boundary or path.



REFERENCE NOTES

1 DROP CONDENSATE DRAIN LINE TIGHT TO WALL FROM ABOVE CEILING TO SERVICE SINK.

PROJECT TITLE
CLEVELAND ELEMENTARY SCHOOL
EMERY SCHOOL DISTRICT
MECHANICAL UPGRADE
CLEVELAND, UTAH


REVISIONS:

170 NORTH MAIN STREET
SPANISH FORK, UTAH 84660
www.kmaarchitects.com


KMA
ARCHITECTS

OLSEN & PETERSON
consulting engineers, inc.
14 East 270 South Salt Lake City, UT 84115
Phone: (801) 488-6464 Fax: (801) 487-2351

P1.1B




DRAWN BY: STAFF
CHECKED BY: M.T.
DATE: JAN 2006
PROJECT #: 176525



REFERENCE NOTES

- 1 NEW WASTE PIPING TO RUN BELOW MEZZANINE FLOOR, ABOVE 1ST FLOOR CEILING.
- 2 WASTE PIPING TO DROP IN WALL TO FLOOR BELOW.
- 3 VENT PIPING TO RUN BELOW MEZZANINE FLOOR, ABOVE 1ST FLOOR CEILING.
- 4 RISE TIGHT AT WALL & RUN HIGH IN STRUCTURE.
- 5 VENT THROUGH ROOF (VTR) SEE DETAIL 3/P5.1.
- 6 CONDENSATE PIPE TO RUN LOW, SLOPING TOWARDS FLOOR DRAINS AS SHOWN (TYPICAL).
- 7 CONDENSATE DRAINS TO RACK AGAINST DUCTWORK AND WALLS TO STAY OUT OF WALK WAY (TYP).




REVISIONS:

PROJECT TITLE: EMERY SCHOOL DISTRICT CLEVELAND ELEMENTARY SCHOOL
CLEVELAND, UTAH
MECHANICAL UPGRADE

PROJECT TITLE: KEY PLAN
DRAWN BY: STAFF
CHECKED BY: M.T.
DATE: JAN 2006
PROJECT #: 176525

P4.1

OLSEN & PETERSON
CONSULTING ENGINEERS, INC.
14 East 270 South, Salt Lake City, UT 84115
Phone: (801) 488-6466 Fax: (801) 487-2351



TYPICAL GAS CONNECTION TO EQUIPMENT

SCALE: NTS

7
P5.1



FLOOR DRAIN FOR CONDENSATE

SCALE: NTS

1
P5.1




PIPE SUPPORT DETAIL

SCALE: NTS


PLUMBING FIXTURE SCHEDULE					
SYMBOL	Fixture	Waste	Vent	C.W.	H.W.
FD	FLOOR DRAIN	2"	2"	--	--

NOTES:
(1) CONTRACTOR SHALL VERIFY EXACT LOCATION OF ALL PLUMBING FIXTURES WITH ARCHITECTURAL DRAWINGS PRIOR TO ROUGH-IN OR INSTALLATION.
(2) CONTRACTOR TO ATTACHED FACTORY FURNISHED CONDENSATE FUNNEL TO FLOOR DRAIN. MOUNT FLOOR DRAIN TO EXISTING WOOD FLOOR.





COOLING COIL CONDENSATE DRAIN DETAIL

SCALE: NTS




FLOOR CLEANOUT DETAIL

SCALE: NTS



AIR SEPARATOR DETAIL


SCALE: NTS



VENT THRU ROOF DETAIL



SCALE: NTS

3
P5.1



MECHANICAL DEMOLITION PLAN AREA A

0 4'-0" 8'-0" 16'-0"
SCALE: 1/8" = 1'-0"



AREA "A"

AREA "B"

PROJECT TITLE
CLEVELAND ELEMENTARY SCHOOL
MECHANICAL UPGRADE

EMERY SCHOOL DISTRICT
CLEVELAND, UTAH
CLEVELAND, UTAH

MECHANICAL UPGRADE

DRAWN BY: STAFF
CHECKED BY: M.T.
DATE: JAN 2026
PROJECT #: 176525

REFERENCE NOTES

- 1 REMOVE EXISTING THERMOSTAT IN PREPARATION TO REPLACE WITH NEW HEATING/COOLING TEMPERATURE SENSOR.
- 2 REMOVE EXISTING CUH. DEMO PIPING BACK FAR ENOUGH TO MAKE NEW CONNECTION TO NEW CUH.
- 3 EXISTING DUCTWORK TO REMAIN (TYP).
- 4 EXISTING PIPING TO REMAIN (TYP).
- 5 REMOVE EXISTING THERMOSTAT IN PREPARATION FOR INSTALMENT OF NEW HEATING ONLY THERMOSTAT.
- 6 EXISTING DUCTWORK CONTINUES TO MEZZANINE ABOVE (TYP).
- 7 EXISTING FIRE DAMPER TO REMAIN (TYP).
- 8 EXISTING MANUAL DAMPER TO REMAIN (TYP).
- 9 EXISTING WALL MOUNTED CONVECTORS TO REMAIN (TYP).
- 10 EXISTING RELIEF AIR HOOD TO REMAIN (TYP).
- 11 EXISTING ROOF MOUNTED EXHAUST FAN TO REMAIN (TYP).

14 East 2700 South, Salt Lake City, UT 84115
Phone: (801) 488-6464 Fax: (801) 487-2351

Olsen & Peterson Consulting Engineers, Inc.


170 NORTH MAIN STREET
SPANISH FORK, UTAH 84660
WWW.KMAARCHITECTS.COMKMA
ARCHITECTS

REVISIONS:





BERRETT

UTAH




0 4' - 0" 8' - 0" 16' - 0"
SCALE: 1/8" = 1'-0"



PROJECT TITLE: CLEVELAND ELEMENTARY SCHOOL
CITY: CLEVELAND, UTAH
MECHANICAL UPGRADE
SCALE: 1/8" = 1'-0"

KMA
ARCHITECTS



REVISIONS:

170 NORTH MAIN STREET
SPANISH FORK, UTAH 84660
www.kmaarchitects.com

OLSEN & PETERSON
consulting engineers, inc.







14 East 270 South Salt Lake City, UT 84111
Phone: (801) 488-6464 Fax: (801) 487-2351


REFERENCE NOTES



- 1 REMOVE EXISTING THERMOSTAT IN PREPARATION TO REPLACE WITH NEW HEATING/COOLING TEMPERATURE SENSOR.
- 2 REMOVE EXISTING CABINET UNIT HEATER (CUH). DEMO PIPING BACK FAR ENOUGH TO MAKE NEW CONNECTION TO NEW CUH.
- 3 EXISTING DUCTWORK TO REMAIN (TYP).
- 4 EXISTING PIPING TO REMAIN (TYP).
- 5 REMOVE EXISTING THERMOSTAT IN PREPARATION FOR NEW HEATING ONLY THERMOSTAT.
- 6 NO WORK IN THIS AREA.
- 7 EXISTING FIRE DAMPER TO REMAIN (TYP).
- 8 EXISTING WALL MOUNTED CONVECTOR TO REMAIN (TYP).
- 9 EXISTING RELIEF AIR HOOD TO REMAIN (TYP).
- 10 EXISTING DUCTWORK CONTINUES TO MEZZANINE ABOVE (TYP).
- 11 REMOVE EXISTING DUCTWORK TO APPROXIMATELY THIS LOCATION.
- 12 EXISTING THERMOSTAT TO REMAIN.
- 13 EXISTING MOTORIZED DAMPER TO REMAIN (TYP).
- 14 CEILING MOUNTED EXHAUST FAN TO REMAIN (TYP).
- 15 EXISTING 12" EXHAUST DUCT UP THRU ROOF TO REMAIN.
- 16 EXISTING PIPING CONTINUES TO MEZZANINE ABOVE (TYP).
- 17 EXISTING MANUAL BALANCING DAMPER TO REMAIN (TYP).

REFERENCE NOTES

- 1 REMOVE EXISTING DUCTWORK AND SUPPORTS COMPLETE (TYP).
- 2 EXISTING DUCTWORK TO REMAIN (TYP).
- 3 REMOVE EXISTING DUCTWORK TO APPROXIMATE THIS LOCATION.
- 4 REMOVE EXISTING FAN COIL UNIT COMPLETE.
- 5 TEMPORARILY REMOVE EXISTING LOUVER, STORE IN A DRY LOCATION ON SITE UNTIL END OF PROJECT. USE THIS OPENING FOR REMOVAL OF EXISTING FAN COIL UNITS.
- 6 REMOVE EXISTING DUCT DROP TO FLOOR AT A MINIMUM. REMOVE DUCTWORK AS NEEDED FOR NEW FANCOIL INSTALLATION AND FITTINGS.
- 7 REMOVE EXISTING MECHANICAL PIPING, HANGERS, AND INSULATION TO APPROXIMATE THIS LOCATION.
- 8 REMOVE EXISTING CIRCULATION PUMP AND ACCESSORIES COMPLETE.
- 9 EXISTING LOUVER TO REMAIN (TYP).
- 10 EXISTING RELIEF AIR DUCTS DROPS TO RETURN DUCT. SEE 3.M0.2 FOR CONTINUATION (TYP).
- 11 EXISTING OUTSIDE AIR DUCT DROPS TO RETURN DUCT. SEE 3.M0.2 FOR CONTINUATION (TYP).
- 12 APPROXIMATE LOCATION OF EXISTING MOTORIZED DAMPER. REMOVE DAMPER AND ACTUATOR. RETURN SALVAGED DAMPER AND ACTUATOR TO BUILDING OWNER (TYP).
- 13 EXISTING MOTORIZED DAMPER TO REMAIN.








REFERENCE NOTES

- 1 NEW WALL MOUNTED HEATING/COOLING TEMPERATURE SENSOR TO BE MOUNTED 4'-0" AFF (TYP).
- 2 CONNECT TO EXISTING PIPING AT THIS LOCATION.
- 3 REBALANCE ALL EXISTING DIFFUSERS TO CFM SHOWN (TYP).
- 4 CONNECT EXISTING MOTORIZED RELIEF AIR DAMPER TO NEW ATC CONTROLS SYSTEM (TYP).
- 5 EXISTING ATC SHUT OFF VALVE TO EXISTING CONVECTORS TO TURN OFF DURING COOLING MODE (TYP).
- 6 DUCTWORK IN THIS AREA IS ABANDONED. EXISTING MINI SPLIT AND THERMOSTATS TO REMAIN. PROVIDE A CONTROL POINT FOR REPORTING SPACE TEMPERATURE.
- 7 EXISTING CEILING EXHAUST FAN TO TURN ON WITH LIGHT (TYP).
- 8 TIE EXISTING ROOF MOUNTED EXHAUST FAN TO NEW ATC CONTROLS (TYP).
- 9 EXISTING ROOF MOUNTED EXHAUST FANS SERVING THE KITCHEN HOOD TO BE INTERLOCKED WITH NEW FAN COIL FC-18.
- 10 REBALANCE EXISTING RETURN GRILLE TO CFM SHOWN (TYP).
- 11 TIE EXISTING 3-WAY VALVE TO NEW ATC CONTROLS (TYP).
- 12 NEW WALL MOUNTED HEATING ONLY TEMPERATURE SENSOR TO BE MOUNTED 4'-0"
- 13 NEW PIPING TO RUN ABOVE CEILING. COORDINATE WITH EXISTING CONDITIONS AND ALL TRADES.
- 14 NEW ATC VALVES INTEGRAL WITH CABINET UNIT HEATERS TO CLOSE DURING COOLING MODE (TYP).
- 15 ENSURE EXISTING FIRE DAMPERS ARE OPEN. COORDINATE WITH SCHOOL DISTRICT IF ANY ARE CLOSED PRIOR TO BALANCING (TYP).
- 16 SEE M1.1B FOR CONTINUATION.
- 17 DUCTWORK CONTINUES TO MEZZANINE ABOVE. SEE M4.1 FOR CONTINUATION (TYP).
- 18 MECHANICAL PIPING CONTINUES TO MEZZANINE ABOVE. SEE M4.1 FOR CONTINUATION.

KMA
ARCHITECTS



REVISIONS:



PROJECT TITLE: CLEVELAND ELEMENTARY SCHOOL
EMERY SCHOOL DISTRICT
MECHANICAL UPGRADE
CLEVELAND, UTAH

DRAWN BY: STAFF
CHECKED BY: M.T.
DATE: JAN. 2026
PROJECT #: 176525

M1.1A

MECHANICAL PLAN AREA B

0 4'-0" 8'-0" 16'-0"
SCALE: 1/8" = 1'-0"




REFERENCE NOTES

- 1 NEW WALL MOUNTED HEATING/COOLING TEMPERATURE SENSOR TO BE MOUNTED 4'-0".
- 2 NEW WALL MOUNTED HEATING ONLY TEMPERATURE SENSOR WITH INSULATED BASE TO BE MOUNTED 4'-0".
- 3 NEW WALL MOUNTED HEATING ONLY TEMPERATURE SENSOR TO BE MOUNTED 4'-0".
- 4 CONNECT TO EXISTING PIPING AT THIS LOCATION. REPAIR PIPE INSULATION AT TIE IN.
- 5 REBALANCE ALL DIFFUSERS TO CFM SHOWN (TYP).
- 6 ENSURE EXISTING FIRE DAMPERS ARE OPEN. COORDINATE WITH SCHOOL DISTRICT IF ANY ARE CLOSED PRIOR TO BALANCING (TYP).
- 7 CONNECT EXISTING MOTORIZED RELIEF AIR DAMPER TO NEW ATC CONTROLS SYSTEM (TYP).
- 8 EXISTING CEILING EXHAUST FAN TO TURN ON WITH LIGHT (TYP).
- 9 EXISTING MOTORIZED SHUT OFF VALVE TO EXISTING CONVECTORS TO CLOSE DURING COOLING MODE (TYP).
- 10 CHILLED WATER PIPING TO RUN LOW TO THE GROUND WITH SUPPORTS AT REGULAR INTERVALS. EXTERIOR INSULATION W/ALUMINUM JACKET REQUIRED.
- 11 CHILLED WATER PIPING RISES UP THE SIDE OF THE BUILDING BEFORE GOING THRU WALL.
- 12 NEW WALL MOUNTED HEATING ONLY TEMPERATURE SENSOR TO BE MOUNTED 4'-0".
- 13 CONNECT TO EXISTING DUCTWORK AT APPROXIMATELY THIS LOCATION.
- 14 ABANDONED DUCTWORK CONTINUES TO ABANDONED EQUIPMENT IN MEZZANINE ABOVE.
- 15 MECHANICAL PIPING CONTINUES TO ABANDONED EQUIPMENT IN MEZZANINE ABOVE (TYP).
- 16 NEW ATC VALVES INTEGRAL WITH CABINET UNIT HEATERS TO CLOSE DURING COOLING MODE (TYP).
- 17 SEE M1.1A FOR CONTINUATION.
- 18 SEE M4.3 FOR CONTINUATION.

PROJECT TITLE: CLEVELAND ELEMENTARY SCHOOL
EMERY SCHOOL DISTRICT
CLEVELAND, UTAH
MECHANICAL UPGRADE
CLEVELAND, UTAH


PROJECT TITLE: 30 S 100 W
DRAWN BY: STAFF
CHECKED BY: M.T.
DATE: JAN 2026
PROJECT #: 176525

KMA
ARCHITECTS



REVISIONS:

OLSEN & PETERSON
consulting engineers, inc.
14 East 270 South Salt Lake City, UT 84115
Phone: (801) 488-6464 Fax: (801) 487-2351



M1.1B

REFERENCE NOTES

EXISTING DUCTWORK TO REMAIN (TYP).

NEW DUCTWORK, COORDINATE WITH EXISTING CONDITIONS (TYP).

USE EXISTING MOTORIZED DAMPER. MAINTAIN ACCESS TO DAMPER.

NEW MOTORIZED RELIEF AIR DAMPER (TYP).

NEW MOTORIZED RETURN AIR DAMPER (TYP).

NEW MOTORIZED OUTSIDE AIR DAMPER (TYP).

CONNECT TO EXISTING PIPING AT APPROXIMATELY THIS LOCATION. REPAIR PIPE INSULATION AT TIE-IN.

RUN NEW MECHANICAL PIPING AS HIGH AS POSSIBLE. COORDINATE WITH EXISTING CONDITION (TYP).

INSTALL EXISTING LOUVER.

NEW DUCTWORK TO EXISTING LOUVER OPENINGS. PROVIDE SUPPORTS ON THE ROOF. SEE DETAIL 6/M4.1.

OUTSIDE AIR DUCTWORK TO DROP TO RETURN AIR DUCTWORK AT APPROXIMATELY THIS LOCATION SEE M4.1 (TYP).

RELIEF AIR DUCTWORK TO DROP TO RETURN AIR DUCTWORK AT APPROXIMATELY THIS LOCATION SEE M4.1 (TYP).

NEW FAN COIL UNIT TO BE SUPPORTED FROM THE FLOOR WITH A MINIMUM OF 6" OF CLEARANCE (TYP).

NEW WALL MOUNTED HEATING ONLY THERMOSTAT.

EXISTING MECHANICAL PIPING DROPS TO FLOOR BELOW APPROXIMATELY THIS LOCATION.

NEW ATC PANEL. 120/1/60 POWER REQUIRED.


SUPPLY DUCTWORK TO DROP AND RUN BELOW FAN COIL UNIT.

NEW FAN COIL UNIT TO BE AS HIGH AS POSSIBLE TO MAINTAIN ACCESS TO MEZZANINE THRU EXISTING DOOR.


CONNECT NEW DUCT TO EXISTING, REPAIR INSULATION AT CONNECTION (TYP).

TURNING VANES (TYP).


ENLARGED MECHANICAL PLAN NORTH MEZZANINE - MECHANICAL PIPING



ENLARGED MECHANICAL PLAN NORTH MEZZANINE - SUPPLY & RETURN DUCT




ENLARGED MECHANICAL PLAN NORTH MEZZANINE - REFERENCE




EXISTING ROOF


LOUVER ROOF HOOD




ENLARGED MECHANICAL PLAN NORTH MEZZANINE - OUTSIDE AIR DUCT



ENLARGED MECHANICAL PLAN NORTH MEZZANINE - RELIEF AIR DUCT




KEY PLAN




REFERENCE NOTES

- XISTING DUCTWORK TO REMAIN.
- EW DUCTWORK, COORDINATE WITH EXISTING CONDITIONS (TYP).
- EW MOTORIZED DAMPER (TYP).
- XISTING MOTORIZED DAMPER, CONNECT TO NEW FAN COIL UNIT AND MAINTAIN ACCESS (TYP).
- EW FAN COIL UNIT TO BE SUPPORTED FROM THE FLOOR WITH A MINIMUM OF 6" OF CLEARANCE (TYP).
- EW FAN COIL UNIT TO BE AS HIGH AS POSSIBLE TO MAINTAIN ACCESS TO MEZZANINE THRU EXISTING DOOR.




MECHANICAL SECTION VIEW - NORTH MEZZANINE NORTH WALL

SCALE: 1/4" =




MECHANICAL SECTION VIEW - NORTH MEZZANINE SOUTH WALL

SCALE: 1/4" =



MECHANICAL SECTION VIEW - NORTH MEZZANINE EAST WALL


SCALE: 1/4" =




MECHANICAL SECTION VIEW - NORTH MEZZANINE WEST WALL

SCALE: 1/4" =

KEY PLAN







ENLARGED BOILER ROOM

SCALE: NTS



1 M4.3



ENLARGED SOUTH MEZZANINE

SCALE: NTS



2 M4.3



ENLARGED SOUTH MEZZANINE MECHANICAL PIPING PLAN

SCALE: NTS

3 M4.3



KEY PLAN

M4.3

REFERENCE NOTES

- FACTORY CONDENSATE DRAIN TRAP.
- CONNECT NEW SUPPLY DUCT, RETURN DUCT, AND O/A DUCT TO EXISTING. CONNECT HYDRONIC PIPING TO EXISTING.
- CONNECT TO EXISTING AT THIS POINT.
- EMERGENCY SHUT OFF SWITCH TO SHUT-OFF FUEL SUPPLY TO EXISTING BOILER. SEE DETAIL 7M62.
- PIPING TO RUN AS HIGH AS POSSIBLE. COORDINATE WITH EXISTING CONDITIONS.
- PROVIDE GAS SHUT-OFF TO BE CONTROLLED BY EMERGENCY SWITCH.
- CONNECT TO EXISTING PIPING AT APPROXIMATELY THIS LOCATION. REPAIR PIPE INSULATION AT TIE-IN.
- CONNECT TO EXISTING AT APPROXIMATELY THIS LOCATION. REPAIR INSULATION AT TIE-IN.
- PIPING TO SERVE NEW UNIT (TYPICAL).
- COORDINATE PIPING RUNS WITH EXISTING CONDITIONS AND ALL TRADES (TYPICAL).
- NEW RELEIF AIR MOTORIZED DAMPER.
- RE-USE EXISTING MOTORIZED DAMPER.
- NEW O/A MOTORIZED DAMPER.
- 3-WAY ATC VALVE TO SWITCH FROM HEATING TO COOLING.
- EXISTING CONDENSING BOILER AND NEUTRALIZATION TANK.
- FAN COIL UNIT A MINIMUM OF 24" ABOVE FLOOR.
- FAN COIL UNIT A MINIMUM OF 16" ABOVE FLOOR.

FAN COIL UNIT SCHEDULE														
SYMBOL	ARRANG.	HTG. CAP. BTUH			CFM	EXT. S.P.	CLG. CAP.			MOTOR			MAKE & MODEL	(1)(2)(3)(4)
		MBH	GPM	Δ P (FT)			BTUH	GPM	Δ P (FT)	FLA	ELECT.	UNIT MCA		
[FC-1]	HORIZONTAL	69	7.2	4.70	1280	0.5	25	5.3	2.70	8.6	120/160	9.68	CARRIER 42DEA14ARNY6AYAR	
[FC-2]	HORIZONTAL	69	7.2	4.70	1280	0.5	25	5.3	2.70	8.6	120/160	9.68	CARRIER 42DEA14ARNY6AYAR	
[FC-3]	HORIZONTAL	69	7.2	4.70	1280	0.5	25	5.3	2.70	8.6	120/160	9.68	CARRIER 42DEA14ARNY6AYAR	
[FC-4]	HORIZONTAL	69	7.2	4.70	1200	0.5	25	5.3	2.70	8.6	120/160	9.68	CARRIER 42DEA14ARNY6AYAR	
[FC-5]	HORIZONTAL	69	7.2	4.70	1200	0.5	25	5.3	2.70	8.6	120/160	9.68	CARRIER 42DEA14ARNY6AYAR	
[FC-6]	HORIZONTAL	69	7.2	4.70	1200	0.5	25	5.3	2.70	8.6	120/160	9.68	CARRIER 42DEA14ARNY6AYAR	
[FC-7]	HORIZONTAL	87	9.0	9.20	1975	0.75	33	7.0	6.70	11.6	120/160	13.05	CARRIER 42DEA20ARNY6AYAR	
[FC-8]	HORIZONTAL	69	7.2	4.70	1290	0.5	25	5.3	2.70	8.6	120/160	9.68	CARRIER 42DEA14ARNY6AYAR	
[FC-10]	HORIZONTAL	69	7.2	4.70	1290	0.5	25	5.3	2.70	8.6	120/160	9.68	CARRIER 42DEA14ARNY6AYAR	
[FC-11]	HORIZONTAL	69	7.2	4.70	1290	0.5	25	5.3	2.70	8.6	120/160	9.68	CARRIER 42DEA14ARNY6AYAR	
[FC-12]	HORIZONTAL	80	8.3	7.30	1640	1.0	30	6.3	4.40	11.4	120/160	12.83	CARRIER 42DEA18ARNY6AYAR	
[FC-13]	HORIZONTAL	65	6.8	4.3	1400	0.7	24	5.1	2.60	8.6	120/160	9.68	CARRIER 42DEA14ARNY6AYAR	
[FC-14]	HORIZONTAL	80	8.3	7.30	1650	0.75	30	6.3	4.40	11.4	120/160	12.83	CARRIER 42DEA18ARNY6AYAR	
[FC-15]	HORIZONTAL	55	5.6	6.20	1120	0.5	20	4.3	3.50	6.8	120/160	7.65	CARRIER 42DEA12ARNY6AYAR	
[FC-16]	HORIZONTAL	25	2.5	3.20	350	0.5	9	1.9	2.30	3.3	120/160	4.13	CARRIER 42DEA06ARNY6AYAR	
[FC-17]	HORIZONTAL	106	11.4	24.00	1050	0.5	32	6.8	12.70	6.8	120/160	7.65	CARRIER 42DEA12ARNY6AYAR	
[FC-18]	HORIZONTAL	343	18.3	6.80	3160	0.75	116	24.5	15.50	8.9	208/360	11.13	CARRIER 42DHA30LRPNYYYBMYA	
[FC-19]	HORIZONTAL	184	19.7	7.50	3015	0.75	87	18.4	6.80	8.9	208/360	11.13	CARRIER 42DHA30LRPNYYYBMYA	
[FC-20]	HORIZONTAL	38	4.0	2.90	970	0.5	14	3.0	2.10	5.2	120/160	6.50	CARRIER 42DEA10ARNY6AYAR	

NOTES:

(1) COOLING CAPACITIES BASED ON 45°F EWT, 90°F EDB, 62°F WB, 30% PROPYLENE GLYCOL.

(2) HEATING CAPACITIES BASED ON 140°F EWT, 60°F E.A.T., 107°F L.A.T 30% PROPYLENE GLYCOL.

(3) UNITS TO BE COMPLETE WITH FILTER RACK WITH HINGED / LATCHED ACCESS DOOR AND DUCT FLANGES.

(4) CONTRACTOR SHALL COORDINATE COIL PIPING CONFIGURATION WITH EQUIPMENT SUPPLIER PRIOR TO SUBMITTAL.

MECHANICAL EQUIPMENT SCHEDULE

CH-1	CHILLER: PACKAGED AIR COOLED, 60 NOMINAL TONS, 57 TONS ACTUAL CAPACITY. COOLING EFFICIENCY 9.91 EER@ 3 IPLV IP. 0.025 COP. CARRIER PROJECT ELEMENTS (5) 1/2 HP, 30% PROPYLENE GLYCOL SOLUTION, WITH AMBIENT AIR TEMP 91°F TO COOL 147.7 GPM FROM 55°F TO 45°F. PRESSURE DROP NOT TO EXCEED 13.4 FT W.C. SINGLE POINT ELECTRICAL CONNECTION, TWO (2) SCROLL COMPRESSORS, TWO (2) REFRIGERANT CIRCUITS, R-32 REFRIGERANT, 0.0001 HR-SO FT-DEG FT/BTU FLOWRATE FACTOR, FLOW SWITCH, U.L. LISTED, FULL LOUVER PACKAGE WITH END PANELS, SHELL & TUBE OR PLATE PLATE HEAT EXCHANGER WITH INTEGRAL STRAINER, UNIT MOUNTED STARTERS, SINGLE POINT POWER CONNECTION, AND ALL CONTROLS FOR AUTOMATIC OPERATION.
	UNIT IS TO BE GIVEN A COMPLETE FACTORY OPERATING AND CONTROL SEQUENCE TEST UNDER LOAD CONDITIONS, AND IS TO BE SHIPPED WITH FULL OPERATING CHARGE OF REFRIGERANT AND FULL OIL CHARGE. CHARGE TO BE VERIFIED BY SUPPLIER AT TIME OF DELIVERY TO JOB SITE.

AS-1	MANUFACTURER: CARRIER MODEL: 30RC-06056-3-213 ELECTRICAL: 265 MCA @ 208-230/3/60 (MOPC = 300 A) DIMENSIONS: 95" LENGTH, 88" WIDTH, AND 78" HEIGHT. OPERATING WT: 2,663 LBS.
------	---

SUH-1	AS-1	MANUFACTURER: TACO MODEL: ACT03F-125
-------	------	---


PUMP SCHEDULE								
SYMBOL	TYPE	SYSTEM	LOCATION	G.P.M.	FT. OF HEAD	MINIMUM EFFICIENCY	MOTOR	MAKE & MODEL
P-1	FLEX COUPLED BASE MOUNTED	CHILLER WATER SYSTEM	BOILER ROOM	148	100	68.3	7.5 H.P. 208/360	B&G E-1510 (1)(3)(4)
P-2	CLOSE COUPLED IN-LINE	HOT WATER SYSTEM	BOILER ROOM	47	75	49.7	3 H.P. 208/360	B&G E-80 (2)(3)
P-3	CLOSE COUPLE IN-LINE	HOT WATER SYSTEM	BOILER ROOM	47	75	49.7	3 H.P. 208/360	B&G E-80 (2)(3)

NOTES:	(1) PUMP TO BE SIZED FOR 45°F / 30% PROPYLENE GLYCOL SOLUTION. (2) PUMP TO BE SIZED FOR 140°F / 30% PROPYLENE GLYCOL SOLUTION. (3) PUMP MOTOR TO BE PREMIUM EFFICIENCY NON-OVERLOADING TYPE. (4) PUMP SHALL BE COMPLETE WITH MATCHED SUCTION DIFFUSER.
--------	---

HOT WATER UNIT HEATER SCHEDULE								
SYMBOL	TYPE	MOUNTING	CFM	HEATING COIL		MOTOR	(1)(2)	
				MBH	GPM	Δ P.	RPM	
UH-1	HOT WATER HORIZONTAL	CEILING/WALL	245	4.0	0.46	0.26	1550	16 WATT 120/160 VULCAN HV-108A (3)



NOTES:	(1) HEATING CAPACITY BASED ON 140°F E.W.T., 120°F L.W.T., 30% PROPYLENE GLYCOL. (2) PROVIDE WALL MOUNTED THERMOSTAT.
--------	---

CABINET UNIT HEATER SCHEDULE								
SYMBOL	CFM	TYPE	HEATING COIL			MOTOR		MAKE & MODEL
			MBH (1)	GPM	WPD	AMPS	VOLTAGE	
UH-1	230	RECESSED CEILING MOUNTED	16.0	1.5	.15			





CHILLED WATER PIPING SCHEMATIC2.0

SCALE:




BASE MOUNTED PUMP DET

SCALE:



AIR COOLED CHILLER PIPING DETAIL

SCAL



GLYCOL FEED TANK DETAIL








SCALE:



ITLE
EMERY SCHOOL DISTRICT
CLEVELAND ELEMENTARY SCHOOL

MECHANICAL UPGRADE CLEVE

1



SYMBOL LEGEND GENERAL NOTES	
1. REFER TO LUMINAIRE SCHEDULE FOR FIXTURE TYPES, MOUNTING REQUIREMENTS, WATTAGE & DETAILS.	
2. WIRE LIGHT FIXTURE FROM ADJACENT JUNCTION BOX.	
3. CONNECT NEAREST UN-SWITCHED HOT CONDUCTOR TO EMERGENCY BALLAST.	
4. LIGHT FIXTURES ARE SCALED WITHIN THE DRAWINGS BASED ON ACTUAL DIMENSIONS.	
5. REFER TO DRAWINGS FOR DIRECTIONAL ARROWS.	
6. SUBSCRIPT INDICATES FIXTURES TO BE CONTROLLED.	
7. HEIGHT MEASURED TO CENTER LINE OF THE BOX FROM THE FINISHED FLOOR.	
8. NOT USED.	
9. NEMA TYPE "ND" NON-FUSED UNLESS NOTED "F" (FUSED), USE HEAVY DUTY (HD) DEVICE FOR 480 VOLT.	
10. SIZE TO THE EQUIPMENT BEING CONTROLLED.	
11. PROVIDE H.O.A. & S.PUSHBUTTONS AS REQUIRED.	
12. DOUBLE ARROWS INDICATE A DOUBLE FACE UNIT.	
13. FOR WATER COOLER LOCATION, REFER TO DODGSON BROS. FOR ALL OTHER LOCATIONS, MOUNT AT 18" FROM TOP OF BOX FROM FINISHED FLOOR, OR AS NOTED.	
14. ARROW SHOWN ON DEVICE INDICATE AIMING DIRECTION.	
15. COORDINATE WITH DOOR HARDWARE SUPPLIER.	
16. MOUNT ON TRACK OR OVERHEAD DOOR IF FROM TOP OF DOOR, UNLESS OVERHEAD DOOR IS A ROLL UP DOOR, THEN MOUNT PER MANUFACTURER'S INSTRUCTIONS.	
17. INSTALL DEVICES PER MANUFACTURER'S INSTALLATION INSTRUCTIONS.	
18. DASHED LINE INDICATES EQUIPMENT CLEARANCES. ARROW INDICATES FRONT OF RACK.	
19. HEIGHT MEASURED TO BOTTOM OF THE DEVICE FROM FINISHED FLOOR.	
20. PROVIDE MUD RING OR BOX COVER APPROPRIATE FOR DEVICE/FIXTURE SERVED.	
21. REFER TO DIAGRAMS, ELEVATIONS, & SCHEDULES FOR CUSTOM ROUGH-IN REQUIREMENTS.	
22. ROUGH-IN TO BE HORIZONTAL.	
23. REFER TO MANUFACTURER'S RECOMMENDED CABLE REQUIREMENTS FOR EXACT CABLE REQUIRED.	
24. FOLLOW BICSI STANDARDS FOR CABLE ROUTING & DISTANCES.	
25. SUBSCRIPT INDICATES NEMA CONFIGURATION.	
26. USE A 4" X 4" BOX WITH A MUD RING TO MATCH THE DEVICE & INSTALLATION.	
27. USE WITH POWER PACK.	
28. PROVIDE UL LISTED DEVICE COMPATIBLE WITH THE FIRE ALARM PANEL SYSTEM.	
29. CAMERA TYPES ARE INDICATED INSIDE THE CAMERA SYMBOL.	
30. SOLID BOX AROUND DEVICE INDICATES INSTALLED IN FLOOR, DASHED BOX AROUND DEVICE INDICATES INSTALLED IN CEILING.	
31. WALL DEVICES NOTED WITH A CHEVRON INDICATE THE PROPOSED INSTALLATION HEIGHT, COORDINATE WITH MILLWORK SHOP DRAWINGS & ELEVATIONS FOR HEIGHT.	

GENERAL NOTES	
1. CONSULT ARCHITECTURAL REFLECTED CEILING PLANS FOR EXACT LOCATION OF ALL LIGHTING FIXTURES.	
2. VERIFY ALL EQUIPMENT DIMENSIONS AND LOCATIONS BEFORE BEGINNING ROUGH-IN. SEE APPLICABLE CODES AND STANDARDS FOR REQUIREMENTS TO INSURE NEC CODE CLEARANCES REQUIRED AROUND ALL ELECTRICAL EQUIPMENT.	
3. CONTRACTOR SHALL VERIFY ALL ELECTRICAL LOADS (VOLTAGE, PHASE, CONNECTION REQUIREMENTS ETC) OF ALL EQUIPMENT FURNISHED UNDER ALL DIMENSIONS, INCLUDING ALL EXISTING EQUIPMENT TO BE REVIEWED. REVIEW ALL SHOP DRAWINGS AND EXISTING EQUIPMENT BEFORE BEGINNING ROUGH-IN.	
4. SEE SECTION 26 100 OF THE SPECIFICATION FOR REQUIRED COORDINATION MEETINGS WITH MECHANICAL AND CELICO CONTRACTORS.	
5. SEE APPLICABLE SHOP DRAWINGS FOR LOCATION IN THIN OF ALL EQUIPMENT, WIRING DEVICE ETC. WHERE APPLICABLE MOUNT ALL WIRING DEVICES ABOVE BACK SPLASH EXCEPT THOSE SERVING UNDER COUNTERTOP EQUIPMENT.	
6. FINISHES OF ALL LIGHT FIXTURES SHALL BE AS SELECTED BY ARCHITECT.	
7. THE ELECTRICAL CONTRACTOR SHALL NOTIFY AND COOPERATE WITH THE MECHANICAL CONTRACTOR THAT NO PIPES, DUCTS, OR EQUIPMENT FOREIGN TO THE OPERATION OF THE ELECTRICAL EQUIPMENT SHALL BE PLACED IN THE ELEVATOR OR PASS THRU ELECTRICAL ROOMS OR SPACES, OR ABOVE OR BELOW ELECTRICAL EQUIPMENT IN OTHER AREAS.	
8. ELECTRICAL BOXES SHALL NOT BE LOCATED IN MASONRY COLUMNS IN BRICK WALLS OR IN GROUTED CELLOPHANE ADJACENT TO OPENINGS, COORDINATE LOCATIONS OF BOXES WITH MASONRY CONTRACTOR.	
9. ALL PENETRATIONS OF FIRE RATED FLOORS, WALLS, AND CEILINGS SHALL BE SEALED WITH APPROVED MATERIAL TO MANIFOLD FIRE RATING OF SURFACE PENETRATION.	
10. CONTRACTOR SHALL VERIFY FURNITURE LAYOUT PRIOR TO ANY FLOORBOX OR POKE-THRU INSTALLATION. COORDINATE EXACT LOCATION OF FLOOR BOX OR POKE-THRU WITH OWNER AND FURNITURE PROVIDER PRIOR TO ROUGH-IN.	
11. CIRCUITS EXTENDING OVER 70' FOR 120 VOLTS AND 115 FOR 277 VOLTS 20 AMP CIRCUITS SHALL BE RUN WITH CONDUCTORS TO THE SIZE BELOW.	
A. THESE ARE BASED ON MAXIMUM LENGTH OF CIRCUIT.	
B. PERFORM VOLTAGE DROP CALCULATIONS AND PROVIDE CONDUCTOR SIZE TO KEEP BRANCH CIRCUIT VOLTAGE DROP LESS THAN 3% WITH 15 AMP LOAD.	
C. CONTRACTOR SHALL ENSURE THAT THE INSTALLATION OF EACH BRANCH CIRCUIT STAYS WITHIN 3% VOLTAGE DROP FOR 15 AMP LOAD. IF NECESSARY, CONTRACTOR SHALL INCREASE WIRE AND CONDUIT SIZE TO MEET THE STANDARD AT NO ADDITIONAL COST TO OWNER.	
12. ALL CONDUITS SHALL BE INSTALLED IN STRAIGHT LINES PLEASING TO 45° AT RIGHT ANGLES TO THE STRUCTURE. PLACEMENT OF ELECTRICAL SEPARATION FROM CONDUITS AND FASTENINGS OF CONDUITS SHALL BE NEAT AND CONSISTENT. CONDUIT SHALL BE INSTALLED AS TIGHT TO THE BOTTOM OF STRUCTURAL ELEMENTS WHEN PARALLEL TO JOISTS AS CODE WILL ALLOW. OVERHEAD INSTALLATION SHALL BE ACCOMPLISHED IN AN EASY FASHION. CONTRACTOR NOTIFICATION SHALL BE ALLOWED TO RUN PERPENDICULAR TO THE BOTTOM CHORD OF THE JOISTS.	
13. DIVISION 20 SHALL VISIT SITE PRIOR TO BIDDING. BIDS SHALL SERVE AS EVIDENCE OF KNOWLEDGE OF EXISTING CONDITIONS. FIELD VERIFY ALL ELECTRICAL EQUIPMENT.	
14. BIDDERS SHALL EXAMINE THE SITE AND THE COMPLETE SET OF PLANS AND SPECIFICATIONS COVERING THE ENTIRE PROJECT. THEY SHALL BECOME FULLY FAMILIAR WITH THE TYPE OF GENERAL CONSTRUCTION AS WELL AS ALL PERTINENT FACTS AFFECTING THE COST OF THE PROJECT. CONTRACTOR SHALL NOT CONTRACT WITH A SUBCONTRACTOR.	
15. ELECTRICAL CONTRACTOR SHALL COORDINATE PROJECT PHASING WITH GENERAL CONTRACTOR AND BID AND PERFORM RESPONSIBILITIES FOR THIS PROJECT TO GENERAL CONTRACTOR EXPECTATIONS.	
16. COORDINATE ELECTRICAL DEMOLITION WITH ARCHITECTURAL DRAWINGS AND GENERAL CONTRACTOR.	
17. CLOSELY COORDINATE ANY REQUIRED POWER SHUTDOWNS WITH HEAD CUSTODIAN AND OWNER.	
18. WHERE JOB CONDITIONS REQUIRE CHANGES FROM THE CONTRACT DOCUMENTS THAT DO NOT CHANGE THE SCOPE OF INSTALLATION OR NATURE OF WORK REQUIRED, THE CONTRACTOR WILL MAKE SUCH CHANGES WITHOUT ADDITIONAL COST TO THE OWNER. NO OWNER CHANGES MAY BE MADE WITHOUT WRITTEN PERMISSION FROM THE OWNER.	
19. SEQUENCE, COORDINATE, AND INTEGRATE INSTALLATIONS OF ELECTRICAL MATERIALS AND EQUIPMENT WITH OTHER TRADES. THIS INCLUDES COORDINATE WITH OTHER TRADES TO ENSURE EQUIPMENT RELOCATING PRIOR TO CLOSING IN THE BUILDING. COORDINATE THE CUTTING AND PATCHING OF BUILDING COMPONENTS TO ACCOMMODATE INSTALLATION OF ELECTRICAL EQUIPMENT AND MATERIALS.	
20. DO NOT PENETRATE STRUCTURAL ELEMENTS OF FLOORS, WALLS, CEILINGS, ROOFS, ETC. DISCONNECT AND RECONNECT ANY FIXTURES, DEVICE, EQUIPMENT, ETC. REQUIRED FOR ROUGH-IN. DO NOT PENETRATE CONCRETE, STAINLESS STEEL, ETC.	
21. CONTRACTOR MUST CONCEAL ALL BOXES THROUGHOUT THE PROJECT. SURFACE MOUNT RACEWAYS (EMT) IS APPROVED SOLELY BY THE ARCHITECT. PART TO MATCH SURROUNDING SURFACE.	
22. ALL CONCRETE CUT AND PATCH WORK REQUIRED FOR FLOOR BOXES INSTALLATION AND/OR RELOCATION OF ELECTRICAL DEVICES AND PANELS THAT REQUIRE WORK WITHIN THE FLOORS SHALL BE DONE BY ELECTRICAL CONTRACTOR. ALL CORE CUTTING FOR NEW SERVICE SHALL ALSO BE COVERED UNDER ELECTRICAL CONTRACTORS REQUIRED WORK.	
23. ALL CONCRETE CUT AND PATCH WORK REQUIRED FOR FLOOR BOXES INSTALLATION AND/OR RELOCATION OF ELECTRICAL DEVICES AND PANELS THAT REQUIRE WORK WITHIN THE FLOORS SHALL BE DONE BY ELECTRICAL CONTRACTOR. ALL CORE CUTTING FOR NEW SERVICE SHALL ALSO BE COVERED UNDER ELECTRICAL CONTRACTORS REQUIRED WORK.	
24. CONTRACTOR SHALL AT ALL TIMES KEEP THE PREMISES FREE OF ALL WASTE, SURPLUS MATERIAL, AND SPILLS. CONTRACTOR SHALL NOT PILE MATERIALS ON THE JOB SITE DURING HIS WORK. AFTER ALL EQUIPMENT AND DEVICES HAVE BEEN INSTALLED; REMOVE ALL LABELS, STICKERS, STAINS, TEMPORARY COVERS, ETC. IDENTIFICATION PLATES ON ALL EQUIPMENT.	
25. IT IS THE INTENT THAT THE FORGEING WORK SHALL BE COMPLETE IN EVERY RESPECT AND THAT THE WORK NOT SPECIFICALLY MENTIONED OR SHOWN ON THE DRAWINGS, BUT NECESSARY TO FULLY COMPLETE THE WORK SHALL BE FURNISHED BY ELECTRICAL CONTRACTOR.	
26. PROVIDE GFCI CIRCUIT BREAKERS SERVING RECEPTACLES PROVIDING POWER TO DRINKING FOUNTAINS, REFRIGERATORS, VENDING MACHINES, DISPOSALS, AND WASHING MACHINES.	
27. CAREFULLY REVIEW THE ENTIRE DRAWING PACKAGE PRIOR TO PROVIDING BID, INCLUDING THE ARCHITECTURAL AND MECHANICAL DRAWINGS. NOT REVIEWING THE ENTIRE SET IS NOT ACCEPTABLE.	
28. PROVIDE GFCI CIRCUIT BREAKERS SERVING RECEPTACLES PROVIDING POWER TO DRINKING FOUNTAINS, REFRIGERATORS, VENDING MACHINES, DISPOSALS, AND WASHING MACHINES.	
29. PROVIDE WEATHERPROOF, NEMA 3R RATED EQUIPMENT FOR ALL EXTERIOR APPLICATIONS.	

GENERAL NOTES	
1. CONSULT ARCHITECTURAL REFLECTED CEILING PLANS FOR EXACT LOCATION OF ALL LIGHTING FIXTURES.	
2. VERIFY ALL EQUIPMENT DIMENSIONS AND LOCATIONS BEFORE BEGINNING ROUGH-IN. SEE APPLICABLE CODES AND STANDARDS FOR REQUIREMENTS TO INSURE NEC CODE CLEARANCES REQUIRED AROUND ALL ELECTRICAL EQUIPMENT.	
3. CONTRACTOR SHALL VERIFY ALL ELECTRICAL LOADS (VOLTAGE, PHASE, CONNECTION REQUIREMENTS ETC) OF ALL EQUIPMENT FURNISHED UNDER ALL DIMENSIONS, INCLUDING ALL EXISTING EQUIPMENT TO BE REVIEWED. REVIEW ALL SHOP DRAWINGS AND EXISTING EQUIPMENT BEFORE BEGINNING ROUGH-IN.	
4. SEE SECTION 26 100 OF THE SPECIFICATION FOR REQUIRED COORDINATION MEETINGS WITH MECHANICAL AND CELICO CONTRACTORS.	
5. SEE APPLICABLE SHOP DRAWINGS FOR LOCATION IN THIN OF ALL EQUIPMENT, WIRING DEVICE ETC. WHERE APPLICABLE MOUNT ALL WIRING DEVICES ABOVE BACK SPLASH EXCEPT THOSE SERVING UNDER COUNTERTOP EQUIPMENT.	
6. FINISHES OF ALL LIGHT FIXTURES SHALL BE AS SELECTED BY ARCHITECT.	
7. THE ELECTRICAL CONTRACTOR SHALL NOTIFY AND COOPERATE WITH THE MECHANICAL CONTRACTOR THAT NO PIPES, DUCTS, OR EQUIPMENT FOREIGN TO THE OPERATION OF THE ELECTRICAL EQUIPMENT SHALL BE PLACED IN THE ELEVATOR OR PASS THRU ELECTRICAL ROOMS OR SPACES, OR ABOVE OR BELOW ELECTRICAL EQUIPMENT IN OTHER AREAS.	
8. ELECTRICAL BOXES SHALL NOT BE LOCATED IN MASONRY COLUMNS IN BRICK WALLS OR IN GROUTED CELLOPHANE ADJACENT TO OPENINGS, COORDINATE LOCATIONS OF BOXES WITH MASONRY CONTRACTOR.	
9. ALL PENETRATIONS OF FIRE RATED FLOORS, WALLS, AND CEILINGS SHALL BE SEALED WITH APPROVED MATERIAL TO MANIFOLD FIRE RATING OF SURFACE PENETRATION.	
10. CONTRACTOR SHALL VERIFY FURNITURE LAYOUT PRIOR TO ANY FLOORBOX OR POKE-THRU INSTALLATION. COORDINATE EXACT LOCATION OF FLOOR BOX OR POKE-THRU WITH OWNER AND FURNITURE PROVIDER PRIOR TO ROUGH-IN.	
11. CIRCUITS EXTENDING OVER 70' FOR 120 VOLTS AND 115 FOR 277 VOLTS 20 AMP CIRCUITS SHALL BE RUN WITH CONDUCTORS TO THE SIZE BELOW.	
A. THESE ARE BASED ON MAXIMUM LENGTH OF CIRCUIT.	
B. PERFORM VOLTAGE DROP CALCULATIONS AND PROVIDE CONDUCTOR SIZE TO KEEP BRANCH CIRCUIT VOLTAGE DROP LESS THAN 3% WITH 15 AMP LOAD.	
C. CONTRACTOR SHALL ENSURE THAT THE INSTALLATION OF EACH BRANCH CIRCUIT STAYS WITHIN 3% VOLTAGE DROP FOR 15 AMP LOAD. IF NECESSARY, CONTRACTOR SHALL INCREASE WIRE AND CONDUIT SIZE TO MEET THE STANDARD AT NO ADDITIONAL COST TO OWNER.	
12. ALL CONDUITS SHALL BE INSTALLED IN STRAIGHT LINES PLEASING TO 45° AT RIGHT ANGLES TO THE STRUCTURE. PLACEMENT OF ELECTRICAL SEPARATION FROM CONDUITS AND FASTENINGS OF CONDUITS SHALL BE NEAT AND CONSISTENT. CONDUIT SHALL BE INSTALLED AS TIGHT TO THE BOTTOM OF STRUCTURAL ELEMENTS WHEN PARALLEL TO JOISTS AS CODE WILL ALLOW. OVERHEAD INSTALLATION SHALL BE ACCOMPLISHED IN AN EASY FASHION. CONTRACTOR NOTIFICATION SHALL BE ALLOWED TO RUN PERPENDICULAR TO THE BOTTOM CHORD OF THE JOISTS.	
13. DIVISION 20 SHALL VISIT SITE PRIOR TO BIDDING. BIDS SHALL SERVE AS EVIDENCE OF KNOWLEDGE OF EXISTING CONDITIONS. FIELD VERIFY ALL ELECTRICAL EQUIPMENT.	
14. BIDDERS SHALL EXAMINE THE SITE AND THE COMPLETE SET OF PLANS AND SPECIFICATIONS COVERING THE ENTIRE PROJECT. THEY SHALL BECOME FULLY FAMILIAR WITH THE TYPE OF GENERAL CONSTRUCTION AS WELL AS ALL PERTINENT FACTS AFFECTING THE COST OF THE PROJECT. CONTRACTOR SHALL NOT CONTRACT WITH A SUBCONTRACTOR.	
15. ELECTRICAL CONTRACTOR SHALL COORDINATE PROJECT PHASING WITH GENERAL CONTRACTOR AND BID AND PERFORM RESPONSIBILITIES FOR THIS PROJECT TO GENERAL CONTRACTOR EXPECTATIONS.	
16. COORDINATE ELECTRICAL DEMOLITION WITH ARCHITECTURAL DRAWINGS AND GENERAL CONTRACTOR.	
17. CLOSELY COORDINATE ANY REQUIRED POWER SHUTDOWNS WITH HEAD CUSTODIAN AND OWNER.	
18. WHERE JOB CONDITIONS REQUIRE CHANGES FROM THE CONTRACT DOCUMENTS THAT DO NOT CHANGE THE SCOPE OF INSTALLATION OR NATURE OF WORK REQUIRED, THE CONTRACTOR WILL MAKE SUCH CHANGES WITHOUT ADDITIONAL COST TO THE OWNER. NO OWNER CHANGES MAY BE MADE WITHOUT WRITTEN PERMISSION FROM THE OWNER.	
19. SEQUENCE, COORDINATE, AND INTEGRATE INSTALLATIONS OF ELECTRICAL MATERIALS AND EQUIPMENT WITH OTHER TRADES. THIS INCLUDES COORDINATE WITH OTHER TRADES TO ENSURE EQUIPMENT RELOCATING PRIOR TO CLOSING IN THE BUILDING. COORDINATE THE CUTTING AND PATCHING OF BUILDING COMPONENTS TO ACCOMMODATE INSTALLATION OF ELECTRICAL EQUIPMENT AND MATERIALS.	
20. DO NOT PENETRATE STRUCTURAL ELEMENTS OF FLOORS, WALLS, CEILINGS, ROOFS, ETC. DISCONNECT AND RECONNECT ANY FIXTURES, DEVICE, EQUIPMENT, ETC. REQUIRED FOR ROUGH-IN. DO NOT PENETRATE CONCRETE, STAINLESS STEEL, ETC.	
21. CONTRACTOR MUST CONCEAL ALL BOXES THROUGHOUT THE PROJECT. SURFACE MOUNT RACEWAYS (EMT) IS APPROVED SOLELY BY THE ARCHITECT. PART TO MATCH SURROUNDING SURFACE.	
22. ALL CONCRETE CUT AND PATCH WORK REQUIRED FOR FLOOR BOXES INSTALLATION AND/OR RELOCATION OF ELECTRICAL DEVICES AND PANELS THAT REQUIRE WORK WITHIN THE FLOORS SHALL BE DONE BY ELECTRICAL CONTRACTOR. ALL CORE CUTTING FOR NEW SERVICE SHALL ALSO BE COVERED UNDER ELECTRICAL CONTRACTORS REQUIRED WORK.	
23. ALL CONCRETE CUT AND PATCH WORK REQUIRED FOR FLOOR BOXES INSTALLATION AND/OR RELOCATION OF ELECTRICAL DEVICES AND PANELS THAT REQUIRE WORK WITHIN THE FLOORS SHALL BE DONE BY ELECTRICAL CONTRACTOR. ALL CORE CUTTING FOR NEW SERVICE SHALL ALSO BE COVERED UNDER ELECTRICAL CONTRACTORS REQUIRED WORK.	
24. CONTRACTOR SHALL AT ALL TIMES KEEP THE PREMISES FREE OF ALL WASTE, SURPLUS MATERIAL, AND SPILLS. CONTRACTOR SHALL NOT PILE MATERIALS ON THE JOB SITE DURING HIS WORK. AFTER ALL EQUIPMENT AND DEVICES HAVE BEEN INSTALLED; REMOVE ALL LABELS, STICKERS, STAINS, TEMPORARY COVERS, ETC. IDENTIFICATION PLATES ON ALL EQUIPMENT.	
25. IT IS THE INTENT THAT THE FORGEING WORK SHALL BE COMPLETE IN EVERY RESPECT AND THAT THE WORK NOT SPECIFICALLY MENTIONED OR SHOWN ON THE DRAWINGS, BUT NECESSARY TO FULLY COMPLETE THE WORK SHALL BE FURNISHED BY ELECTRICAL CONTRACTOR.	
26. PROVIDE GFCI CIRCUIT BREAKERS SERVING RECEPTACLES PROVIDING POWER TO DRINKING FOUNTAINS, REFRIGERATORS, VENDING MACHINES, DISPOSALS, AND WASHING MACHINES.	
27. CAREFULLY REVIEW THE ENTIRE DRAWING PACKAGE PRIOR TO PROVIDING BID, INCLUDING THE ARCHITECTURAL AND MECHANICAL DRAWINGS. NOT REVIEWING THE ENTIRE SET IS NOT ACCEPTABLE.	
28. PROVIDE GFCI CIRCUIT BREAKERS SERVING RECEPTACLES PROVIDING POWER TO DRINKING FOUNTAINS, REFRIGERATORS, VENDING MACHINES, DISPOSALS, AND WASHING MACHINES.	
29. PROVIDE WEATHERPROOF, NEMA 3R RATED EQUIPMENT FOR ALL EXTERIOR APPLICATIONS.	

ELECTRICAL ABBREVIATIONS INDEX	
ABBREV.	DESCRIPTION
ACG	ALTERNATING CURRENT
ACLG	ALTERNATING CURRENT LINE TO GND
ADC	ANALOG TO DIGITAL CONVERTER
AF	AVOIDABLE FAULT CURRENT
AFG	ALARM FAULT GENERATOR
AGF / A.F.	ALARM FAULT GENERATOR
AH	ALARM HANDLING UNIT
AMPS	AMPS INTERRUPTING CAPACITY
ALT	ALTERNATE
AMPS METER	AMPS METER
AMP	AMPERE
AMPL	AMPLIFIER
ANN	ANNUNCIATOR
ANPL	ANALOG TO DIGITAL CONVERTER
APPROXIMATELY	APPROXIMATELY
AS	ASSEMBLY
AS-STAT	ASSEMBLY-TO-STRUCTURE
AS-T	AS-TO
ATM	AMPS TRIP
ATPS	AUTOMATIC TRANSFER SWITCH
ATU	AMPERE
AVG	AMPERE
AWG	AMERICAN WIRE GAUGE
BATT	BATTERY
BATT-C	BATTERY CARRIER
BOARD	BOARD
BPC	BELLOWS
BULG	BELLOWS FINISHED GRADE
BULD	BULDING
BMS	BUILDING MANAGEMENT SYSTEM
BNC	BALUN
BOND	BONDING
BONDING	BONDING
BONDING JACKET	BONDING JACKET
BONDING PLATE	BONDING PLATE
BONDING RIBBON	BONDING RIBBON
BONDING STRIP	BONDING STRIP
BONDING WIRE	BONDING WIRE
BONDED	BONDED
BONDED JACKET	BONDED JACKET
BONDED PLATE	BONDED PLATE
BONDED RIBBON	BONDED RIBBON
BONDED STRIP	BONDED STRIP
BONDED WIRE	BONDED WIRE
BONDED WIRE JACKET	BONDED WIRE JACKET
BONDED WIRE PLATE	BONDED WIRE PLATE
BONDED WIRE RIBBON	BONDED WIRE RIBBON
BONDED WIRE STRIP	BONDED WIRE STRIP
BONDED WIRE WIRE	BONDED WIRE WIRE
BONDED WIRE WIRE JACKET	

MECHANICAL EQUIPMENT SCHEDULE

RESPONSIBILITY LEGEND:
EC - ELECTRICAL CONTRACTOR (DIVISION 28)
MC - MECHANICAL CONTRACTOR (DIVISION 23)
CC - CONTROL CONTRACTOR

NOTES:
1. NON-FUSED DISCONNECT SWITCH
2. FUSED DISCONNECT SWITCH
3. BREAKER IN ENCLOSURE
4. MANUAL STARTER WITH THERMAL OVERLOAD
5. MAGNETIC STARTER
6. MAGNETIC STARTER/NON-FUSE DISCONNECT COMBINATION
7. MAGNETIC STARTER/FUSED DISCONNECT COMBINATION
8. MAGNETIC STARTER/BREAKER COMBINATION
9. VARIABLE FREQUENCY DRIVE
10. REVERSING TWO-SPEED STARTER
11. DIRECT CONNECTION
12. RECEPTACLES/SPECIAL PURPOSE OUTLET/ETC.
13. TWO-SPEED STARTER COORDINATE WITH MOTOR TYPE
14. SOLD STATE SOFT-STARTER


A. FURNISHED, INSTALLED AND CONNECTED UNDER DIVISION 28
B. FURNISHED AND INSTALLED UNDER ANOTHER DIVISION, REQUIRED CONNECTION UNDER DIVISION 28(16)
C. FURNISHED UNDER ANOTHER DIVISION BUT INSTALLED AND CONNECTED UNDER DIVISION 28(16)
D. FURNISHED, INSTALLED AND CONNECTED UNDER ANOTHER DIVISION

CB = CIRCUIT BREAKER
CKW = CHILLER KILOWATTS

NOTE 1: PER NEC 250.122(A), EQUIPMENT GROUND IS NOT REQUIRED TO BE LARGER THAN THE PHASE CONDUCTOR.
NOTE 2: OVERCURRENT PROTECTION DEVICE (OCPD) SHOWN IS LOCATED AT POWER PANEL, ALL FUSING TO BE SIZED IN ACCORDANCE WITH FUSE MFR RECOMMENDATION FOR MOTOR NAMEPLATE RATING.
NOTE 3: ALL EQUIPMENT TO BE RATED FOR THE ENVIRONMENT FOR WHICH IT IS INSTALLED.

4. OVERLOAD PROTECTION SHALL BE PROVIDED FOR ALL MOTOR BRANCH CIRCUITS IN COMPLIANCE WITH NEC SECTION 430. SIZE OVERLOAD UNITS BASED ON ACTUAL RUNNING...

TYPE	INSTANCE ID	DESCRIPTION	ELECTRICAL					LOAD INFORMATION					OCPD					CIRCUIT INFORMATION					STARTER			CONTROL			DISCONNECT		
			VOLTAGE	PHASE	MOTOR POWER	APPARENT POWER	REAL POWER	FLA	MCA	EM POWER	TYPE	OCPD	SETS	NO.	SIZE	TYPE	NEUTRAL CONDUCTOR	GROUND CONDUCTOR	SIZE	TYPE	FURNISH	INSTALL	TYPE	FURNISH	INSTALL	TYPE	FURNISH	INSTALL	INTERLOCK	NOTES	
CUH -	1	CABINET UNIT HEATER	120 V	1	0.00 hp	0.1 kVA	0.1 kW	0.8 A	1 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	Cu	12	4A	EC	EC	MC	MC	MC	4A	EC	EC			
CUH -	1	CABINET UNIT HEATER	120 V	1	0.00 hp	0.1 kVA	0.1 kW	0.8 A	1 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC		
CUH -	1	CABINET UNIT HEATER	120 V	1	0.00 hp	0.1 kVA	0.1 kW	0.8 A	1 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC		
CUH -	1	CABINET UNIT HEATER	120 V	1	0.00 hp	0.1 kVA	0.1 kW	0.8 A	1 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC		
CUH -	1	CABINET UNIT HEATER	120 V	1	0.00 hp	0.1 kVA	0.1 kW	0.8 A	1 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC		
CUH -	1	CABINET UNIT HEATER	120 V	1	0.00 hp	0.1 kVA	0.1 kW	0.8 A	1 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC		
CUH -	1	CABINET UNIT HEATER	120 V	1	0.00 hp	0.1 kVA	0.1 kW	0.8 A	1 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC		
CUH -	1	CABINET UNIT HEATER	120 V	1	0.00 hp	0.1 kVA	0.1 kW	0.8 A	1 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC		
CH -	1	CHILLER	208 V	3	0.00 hp	76.4 kVA	68.7 kW	212 A	265 A	No	(Motor) Inverse Time Breaker	300 A	1	3	400	Cu	Yes	400	Cu	4	3"	11A	EC	EC	MC	MC	MC	11A	EC	EC	
FC -	1	FAN COIL	120 V	1	0.00 hp	1.0 kVA	0.9 kW	8.6 A	10.8 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	2	FAN COIL	120 V	1	0.00 hp	1.0 kVA	0.9 kW	8.6 A	10.8 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	3	FAN COIL	120 V	1	0.00 hp	1.0 kVA	0.9 kW	8.6 A	10.8 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	4	FAN COIL	120 V	1	0.00 hp	1.0 kVA	0.9 kW	8.6 A	10.8 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	5	FAN COIL	208 V	1	0.00 hp	1.8 kVA	1.6 kW	8.6 A	10.8 A	No	(Motor) Inverse Time Breaker	15 A	1	2	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	6	FAN COIL	120 V	1	0.00 hp	1.0 kVA	0.9 kW	8.6 A	10.8 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	7	FAN COIL	120 V	1	0.00 hp	1.0 kVA	0.9 kW	8.6 A	10.8 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	9	FAN COIL	120 V	1	0.00 hp	1.0 kVA	0.9 kW	8.6 A	10.8 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	10	FAN COIL	120 V	1	0.00 hp	1.0 kVA	0.9 kW	8.6 A	10.8 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	11	FAN COIL	120 V	1	0.00 hp	1.0 kVA	0.9 kW	8.6 A	10.8 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	12	FAN COIL	120 V	1	0.00 hp	1.0 kVA	0.9 kW	8.6 A	10.8 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	13	FAN COIL	120 V	1	0.00 hp	1.0 kVA	0.9 kW	8.6 A	10.8 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	14	FAN COIL	120 V	1	0.00 hp	1.4 kVA	1.2 kW	11.4 A	14.3 A	No	(Motor) Inverse Time Breaker	20 A	1	1	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	15	FAN COIL	120 V	1	0.00 hp	0.8 kVA	0.7 kW	6.8 A	8.5 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	16	FAN COIL	120 V	1	0.00 hp	0.8 kVA	0.7 kW	6.8 A	8.5 A	No	(Motor) Inverse Time Breaker	15 A	1	1	12	Cu	Yes	12	Cu	12	3/4"	4A	EC	EC	MC	MC	MC	4A	EC	EC	
FC -	17	FAN CO																													



PANELBOARD SCHEDULE																					
PANEL: 'M'				TYPE: Do Not Use; Use...				VOLTS: 208Y/120, 3Φ, 4W				PHASE: 3				WIRES: 4					
LOCATION: BOILER RM 31				MAINS/BUS AMPS: 400								LUGS: Standard									
FED FROM: 'MDP'				MAIN DISC. TYPE: MLO								DOOR-IN-DOOR									
MOUNTING:				MAIN DISC. TRIP: MLO								200% NEUTRAL									
BUSSING: Do Not Use; Use Current Rating												ISO GROUND									
																SPD					
BRANCH BREAKERS																					
ITEM	AMPS	POLE	WIRE SIZE	CIR. NO.	A	B	C	A	B	C	CIR. NO.	WIRE SIZE	POLE	AMPS	ITEM						
EXISTING	20 A	1	--	1	0 VA			0 VA			2	--	1	20 A	EXISTING						
EXISTING	20 A	1	--	3		0 VA			0 VA		4	--	1	20 A	EXISTING						
ATC	20 A	1	#10	5			500 VA			384 VA	6	#10	1	20 A	CABINET UNIT HEATER, Room 18, 19, 27...						
Receptacle - General, BOILER RM 31	20 A	1	#10	7	180 VA			360 VA			8	#10	1	20 A	Power, Receptacle - General						
ATC	20 A	1	#10	9		500 VA			18 VA		10	#10	1	20 A	HOT WATER UNIT HEATER, BOILER RM...						
EXISTING	20 A	1	--	11			0 VA			0 VA	12	--	1	20 A	EXISTING						
EXISTING	20 A	1	--	13	0 VA			0 VA			14	--	1	20 A	EXISTING						
EXISTING	20 A	1	--	15		0 VA			0 VA		16	--	1	20 A	EXISTING						
EXISTING	20 A	1	--	17			0 VA			0 VA	18	--	1	20 A	EXISTING						
EXISTING	20 A	1	--	19	0 VA			2,906 VA			20										
EXISTING	20 A	1	--	21		0 VA			2,906 VA		22	#6	3	40 A	PUMP, BOILER RM 31						
EXISTING	20 A	1	--	23			0 VA			2,906 VA	24										
				25	1,273 VA			0 VA			26	--	1	20 A	EXISTING						
PUMP	20 A	3	#10	27		1,273 VA			0 VA		28	--	1	20 A	EXISTING						
				29		1,273 VA			0 VA	30	--	1	20 A	EXISTING							
EXISTING	20 A	1	--	31	0 VA			1,273 VA			32										
EXISTING	20 A	1	--	33		0 VA			1,273 VA		34	#12	3	20 A	PUMP						
EXISTING	20 A	1	--	35			0 VA			1,273 VA	36										
EXISTING	20 A	1	--	37	0 VA			0 VA			38	--	1	20 A	EXISTING						
EXISTING	20 A	1	--	39		0 VA			0 VA		40	--	1	20 A	EXISTING						
EXISTING	20 A	1	--	41			0 VA			0 VA	42	--	1	20 A	EXISTING						
					5943	5924	6290	TOTAL (VA)									CONNECTED LOAD TOTAL				
					49.5 A	49.4 A	52.4 A	AMPS/PHASE									17,245 VA				
																AIC RATING: 25,614	AMPS RMS SYSM.				
NOTES:																					

PANELBOARD SCHEDULE

PANEL: 'P'				TYPE: Do Not Use; Use...				VOLTS: 208Y/120, 3Φ, 4W				PHASE: 3				
												WIRES: 4				
LOCATION: Space 71				MAINS/BUS AMPS: 400				LUGS: Standard								
FED FROM: 'MDP'				MAIN DISC. TYPE: MLO				DOOR-IN-DOOR								
MOUNTING:				MAIN DISC. TRIP: MLO				200% NEUTRAL								
BUSSING: Do Not Use; Use Current Rating												ISO GROUND				
												SPD				
BRANCH BREAKERS																
ITEM	AMPS	POLE	WIRE SIZE	CIR. NO.	A	B	C	A	B	C	CIR. NO.	WIRE SIZE	POLE	AMPS	ITEM	
HOT WATER UNIT HEATER	20 A	1	#10	1	18 VA			0 VA			2	--	1	20 A	EXISTING	
FAN COIL	20 A	1	#10	3		1,368 VA			816 VA		4	#10	1	20 A	FAN COIL	
FAN COIL	20 A	1	#10	5			396 VA			816 VA	6	#10	1	20 A	FAN COIL	
FAN COIL	20 A	1	#10	7	1,368 VA			1,032 VA			8	#10	1	20 A	FAN COIL	
FAN COIL	20 A	1	#10	9		1,032 VA			1,032 VA		10	#10	1	20 A	FAN COIL	
FAN COIL	20 A	1	#10	11			624 VA			0 VA	12	--	1	20 A	EXISTING	
FAN COIL	20 A	1	#10	13	1,032 VA			0 VA			14	--	1	20 A	EXISTING	
EXISTING	20 A	1	--	15		0 VA			0 VA		16	--	1	20 A	EXISTING	
FAN COIL	20 A	3	#10	17			1,069 VA			0 VA	18	--	1	20 A	EXISTING	
				19	1,069 VA			0 VA			20	--	1	20 A	EXISTING	
				21		1,069 VA			0 VA		22	--	1	20 A	EXISTING	
FAN COIL	20 A	3	#10	23			1,069 VA			0 VA	24	--	1	20 A	EXISTING	
				25	1,069 VA			0 VA			26	--	1	20 A	EXISTING	
				27		1,069 VA			0 VA		28	--	1	20 A	EXISTING	
EXISTING	20 A	1	--	29			0 VA			0 VA	30	--	1	20 A	EXISTING	
EXISTING	20 A	1	--	31	0 VA			0 VA			32	--	1	20 A	EXISTING	
EXISTING	20 A	1	--	33		0 VA			0 VA		34	--	1	20 A	EXISTING	
EXISTING	20 A	1	--	35			0 VA			0 VA	36	--	1	20 A	EXISTING	
EXISTING	20 A	1	--	37	0 VA			0 VA			38	--	1	20 A	EXISTING	
EXISTING	20 A	1	--	39		0 VA			0 VA		40	--	1	20 A	EXISTING	
EXISTING	20 A	1	--	41			0 VA			500 VA	42	#10	1	20 A	ATC	
											CONNECTED LOAD TOTAL 15,947 VA					
				5587	6386	4429	TOTAL (VA)				48 A	54.7 A	36.9 A	AMPS/PHASE		
AIC RATING: 18,728 AMPS RMS SYSM.																
NOTES:																

K13 RATED COPPER TRANSFORMER SCHEDULE																		
PRIMARY (LINE) SIDE 480D, 3P, 3W									SECONDARY (LOAD) SIDE 208/120Y, 3P, 5W, 200% NEUTRAL									
O.C. PROT.	TYPE COND.*	COND. AMPS	SETS	CONDUCTOR		GROUND COND.	CONDUIT SIZE	GEC ①	MIN. Z%	O.C. PROT.	TYPE COND.*	COND. AMPS	SETS	CONDUCTOR		CONDUIT SIZE	BONDING JUMPER ②	
				QUAN.	SIZE									QUAN.	SIZE			
30	P015	30	1	3	10	10	3/4"	10	3	60	S015-2	68	1	5	3	2"	8	
50	P030	50	1	3	6	8	1"	6	3	100	S030-2	120	1	5	1/0	2"	6	
70	P045	70	1	3	4	8	1-1/4"	2	3	175	S045-2	184	1	5	4/0	3"	2	
125	P075	125	1	3	1/0	6	2"	2	3	225	S075-2	248	1	5	350	3"	2	
175	P112	175	1	3	2/0	6	2"	1/0	4	400	S112-2	408	2	5	250	3"	1/0	
300	P150	310	1	3	350	3	3"	2/0	4	600	S150-2	608	2	5	500	4"	2/0	
400	P225	380	1	3	500	3	4"	3/0	4	800	S225-2	804	3	5	400	4"	3/0	
600	P300	620	2	3	350	1	3"	3/0	5	1200	S300-2	1216	4	5	500	4"	250	
800	P500	760	2	3	500	1/0	4"	3/0	5	1600	S500-2	1608	6	5	400	4"	300	
1200	P750	1260	4	3	350	3/0	3"	3/0	5	3000	S750-2	3040	10	5	500	4"	750	

(2) SUPPLY SIDE BONDING JUMPER. (NEC 250.102 (C)(1))

KEYNOTES	
X1	EXISTING SQUARE D POWER-STYLE 1400A 208V 3P SWITCHBOARD TO REMAIN AND BE PROTECTED IN PLACE. CONTRACTOR SHALL PROVIDE NEW BREAKERS WITHIN SQUARE D POWER-STYLE EQUIPMENT. COORDINATE BREAKER REQUIREMENTS WITH SQUARE D REPRESENTATIVE.
X3	FEEDER UPSIZED FOR VOLTAGE DROP. PROVIDE ALL REQUIRED LUG ADAPTERS, PIN REDUCERS, POLARIS LUG KITS, ETC. AS REQUIRED. PROVIDE NEC SIZED JUNCTION BOX AHEAD OF PANELBOARD/GEAR AS NEEDED TO LOCATED AND TERMINATE CONDUCTORS ON POLARIS LUG ADAPTERS (<10' FROM FINAL TERMINATION AT PANELBOARD). SIZE DOWN TO CONDUCTORS THAT FIT THE AVAILABLE LUGS AND/OR BREAKERS.
X4	PROVIDE NEW 300A 208V 3P BREAKER WITHIN EXISTING SQUARE D POWER-STYLE MDP.

PANELBOARD SCHEDULE

PANEL: 'S'	TYPE: Do Not Use; Use...	VOLTS: 208Y/120, 3Φ, 4W	PHASE: 3	WIRES: 4
LOCATION: STORAGE 7		MAINS/BUS AMPS: 400		LUGS: Standard
FED FROM: 'MDP'		MAIN DISC. TYPE: MLO		DOOR-IN-DOOR
MOUNTING:		MAIN DISC. TRIP: MLO		200% NEUTRAL
BUSING: Do Not Use; Use Current Rating				ISO GROUND
				SPD

BRANCH BREAKERS

ITEM	AMPS	POLE	WIRE SIZE	CIR. NO.	A	B	C	A	B	C	CIR. NO.	WIRE SIZE	POLE	AMPS	ITEM
EXISTING	20 A	1	--	1	0 VA			0 VA			2	--	1	20 A	EXISTING
EXISTING	20 A	1	--	3		0 VA			0 VA		4	--	1	20 A	EXISTING
EXISTING	20 A	1	--	5			0 VA			0 VA	6	--	1	20 A	EXISTING
EXISTING	20 A	1	--	7	0 VA			0 VA			8	--	1	20 A	EXISTING
EXISTING	20 A	1	--	9		0 VA			0 VA		10	--	1	20 A	EXISTING
EXISTING	20 A	1	--	11			0 VA			0 VA	12	--	1	20 A	EXISTING
EXISTING	20 A	1	--	13	0 VA			0 VA			14	--	1	20 A	EXISTING
EXISTING	20 A	1	--	15		0 VA			0 VA		16	--	1	20 A	EXISTING
EXISTING	20 A	1	--	17			0 VA			0 VA	18	--	1	20 A	EXISTING
EXISTING	20 A	1	--	19	0 VA			0 VA			20	--	1	20 A	EXISTING
EXISTING	20 A	1	--	21		0 VA			0 VA		22	--	1	20 A	EXISTING
EXISTING	20 A	1	--	23			0 VA			0 VA	24	--	1	20 A	EXISTING
EXISTING	20 A	1	--	25	0 VA			0 VA			26	--	1	20 A	EXISTING
EXISTING	20 A	1	--	27		0 VA			0 VA		28	--	1	20 A	EXISTING
EXISTING	20 A	1	--	29			0 VA			384 VA	30	#10	1	20 A	CABINET UNIT HEATER, Room 1, 2, 9
EXISTING	20 A	1	--	31	0 VA			0 VA			32	--	1	20 A	EXISTING
EXISTING	20 A	1	--	33		0 VA			0 VA		34	--	1	20 A	EXISTING
EXISTING	20 A	1	--	35			0 VA			0 VA	36	--	1	20 A	EXISTING
EXISTING	20 A	1	--	37	0 VA			0 VA			38	--	1	20 A	EXISTING
EXISTING	20 A	1	--	39		0 VA			0 VA		40	--	1	20 A	EXISTING
EXISTING	20 A	1	--	41			0 VA			0 VA	42	--	1	20 A	SPARE


0	0	384	TOTAL (VA)	CONNECTED LOAD TOTAL
0 A	0 A	3.2 A	AMPS/PHASE	384 VA

AIC RATING: 16,124 AMPS RMS SYSM.

NOTES:

COPPER CONDUCTOR & CONDUIT SCHEDULE							
TYPE	MAX. O.C. PROT.	COND. AMPS	SETS	CONDUCTOR		CONDUIT SIZE	EQ. GND. COND.
				QUAN.	SIZE		
0-2	30	30	1	2	10	3/4"	10
0-3	30	30	1	3	10	3/4"	10
0-4	30	30	1	4	10	3/4"	10
0-2	40	40	1	2	8	1"	10
0-3	40	40	1	3	8	1"	10
0-4	40	40	1	4	8	1"	10
0-2	60	55	1	2	6	1"	8
0-3	60	55	1	3	6	1"	8
0-4	60	55	1	4	6	1"	8
0-2	70	70		2	4	1"	8
0-3	70	70	1	3	4	1-1/4"	8
0-4	70	70	1	4	4	1-1/4"	8
0-2	90	85	1	2	3	1-1/4"	8
0-3	90	85	1	3	3	1-1/4"	8
0-4	90	85	1	4	3	1-1/2"	8
0-5	90	88	1	5*	1	2"	6
0-3	100	95	1	3	2	1-1/2"	6
0-4	100	95	1	4	2	1-1/2"	6
0-3	110	110	1	3	1	1-1/2"	6
0-4	110	110	1	4	1	2"	6
25-5	125	120	1	5*	1/0	2"	6
50-3	150	150	1	3	1/0	2"	6
50-4	150	150	1	4	1/0	2"	6
50-5	150	140	1	5*	2/0	2"	6
75-3	175	175	1	3	2/0	2"	6
75-4	175	175	1	4	2/0	2"	6
75-5	175	160	1	5*	3/0	2-1/2"	6
100-3	200	200	1	3	3/0	2"	6
100-4	200	200	1	4	3/0	2"	6
100-5	200	184	1	5*	4/0	2-1/2"	4
150-3	250	230	1	3	4/0	2-1/2"	4
150-4	250	230	1	4	4/0	2-1/2"	4
150-5	250	248	1	5*	350	3"	3
200-3	300	255	1	3	250	3"	4
200-4	300	255	1	4	250	3"	4
200-5	300	268	1	4	350	3"	3
250-3	350	310	1	3	350	3"	3
250-4	350	310	1	4	350	3"	3
250-5	350	304	1	5*	500	4"	3
300-3	400	380	1	3	500	4"	3
300-4	400	380	1	4	500	4"	3
300-5	400	368	2	5*	4/0	3"	3
400-3	600	620	2	3	350	3"	1
400-4	600	620	2	4	350	3"	1
400-5	600	608	2	5*	500	3"	1
500-3	800	760	2	3	500	4"	1/0
500-4	800	760	2	4	500	4"	1/0
500-5	800	744	3	5*	350	4"	1/0
600-3	1000	1140	3	3	500	4"	2/0
600-4	1000	1140	3	4	500	4"	2/0
600-5	1000	1072	4	5*	400	4"	2/0
700-3	1200	1240	4	3	350	4"	3/0
700-4	1200	1240	4	4	350	4"	3/0
700-5	1200	1216	4	5*	500	4"	3/0
800-3	1600	1675	5	3	400	4"	4/0
800-4	1600	1675	5	4	400	4"	4/0
800-5	1600	1608	6	5*	400	4"	4/0
900-4	2000	2010	6	4	400	4"	250
900-4	2500	2660	7	4	500	4"	350
900-4	3000	3040	8	4	500	4"	400
900-4	4000	4180	11	4	500	4"	500

TES: FOR GROUND CONDUCTOR IN PARALLEL RUNS, SIZE IN ACCORDANCE WITH NEC PARAGRAPH 250-122.	30-2	30	1	2	10	3/4"	10	
GND. CONDUCTOR MAY BE DELETED ON SERVICE ENTRANCE CONDUCTORS	30-3	30	1	3	10	3/4"	10	
ALL COPPER CABLE TO BE THHN/THWN.	30-4	30	1	4	10	3/4"	10	
00% NEUTRAL, DERATED TO 80% BASED ON NEC 310.15.B(5)(C)	40-2	40	1	2	8	1"	10	
	40-3	40	1	3	8	1"	10	
	40-4	40	1	4	8	1"	10	
	60-2	60	55	1	2	6	1"	8
	60-3	60	55	1	3	6	1"	8
	60-4	60	55	1	4	6	1"	8
	70-2	70	70	1	2	4	1"	8
	70-3	70	70	1	3	4	1-1/4"	8
	70-4	70	70	1	4	4	1-1/4"	8
	90-2	90	85	1	2	3	1-1/4"	8



ANELBOARD GENERAL SHEET NOTES




MENT LABELING PER SPECIFICATIONS 26 0553. THE LABEL SHALL IDENTIFY THE
PMENT WHERE THE POWER SUPPLY ORIGINATES, AND THE SYSTEM VOLTAGE,
AND SYSTEM AT ALL TERMINATION, CONNECTION AND SPLICING POINTS. FOR
ER POWER SUPPLY FOR PANEL "XX" ORIGINATES AT PANEL "XX" (OR
"XX", TRANSFORMER "XX", SWITCH "XX", ETC.); 120/208 VOLTS, 3-PHASE, PHASE
CATION (OR 120/240, 277/480, ETC.).


PANELBOARD INDEXES AS EACH PANELBOARD. FILL OUT PANELBOARD'S
DRY CARD UPON COMPLETION OF INSTALLATION WORK. UTILIZE ACTUAL FINAL
NUMBERS, NOT ARCHITECTURAL NUMBERS USED ON DRAWINGS. IDENTIFY
TING CIRCUITS, INDIVIDUAL RECEPTACLE CIRCUITS BY ROOM SERVED, AND
PMENT, ETC. LABEL CIRCUIT BREAKERS TO IDENTIFY LOCATION OF SUBPANEL
SUPPLIED USING ROOM NUMBERS AND EQUIPMENT NAMES. INCLUDE ROOM
QUIPMENT CIRCUIT DESIGNATIONS. ALL DIRECTORIES TO BE TYPEWRITTEN.

0 ARC-FLASH HAZARD LABELS PER THE SPECIFICATIONS AND NEC.

.. AND KITCHEN EQUIPMENT BREAKERS TO BE SIZED PER THE MECHANICAL
E SCHEDULE AND KITCHEN EQUIPMENT SCHEDULE.

QUIRED LUG ADAPTERS, PIN REDUCERS, POLARIS LUG KITS, ETC. AS
IDE NEC SIZED JUNCTION BOX AHEAD OF PANELBOARD/GEAR AS NEEDED TO
TERMINATE CONDUCTORS ON POLARIS LUG ADAPTERS (<10' FROM FINAL
PANELBOARD). SIZE DOWN TO CONDUCTORS THAT FIT THE AVAILABLE LUGS
RS WHERE CONDUCTORS HAVE BEEN UPSIZED FOR VOLTAGE DROP.





KEYNOTES

P1 FACTORY PROVIDED OUTLET. CONTRACTOR TO EXTEND 120V POWER FROM NEAREST AVAILABLE CIRCUIT.
P10 EXTEND NEAREST AVAILABLE 120V CIRCUIT TO MECHANICAL UNIT.

POWER GENERAL SHEET NOTES

- COORDINATE PLACEMENT OF ELECTRICAL DEVICES WITH ARCHITECT PRIOR TO ROUGH-IN. WHERE DEVICES ARE SHOWN IN SAME WALL SPACE, ALIGN VERTICALLY AND HORIZONTALLY.
- ALL THE LOW VOLTAGE WIRE/CABLE FOR LIGHTING SENSORS, AUDIOVISUAL EQUIPMENT, SOUND AMPLIFICATION, ETC. TO BE PROPERLY SUPPORTED PER THE TELEDATA, TELEVISION, AND LOW VOLTAGE SYSTEMS AND NOT PULLED THROUGH STRUCTURAL LINES. PULLING WIRE DIAGONALLY ACROSS ROOMS IS NOT ALLOWED. USING CEILING SYSTEM OR LIGHT FIXTURE SUPPORT/SEISMIC WIRES FOR SUPPORT IS NOT ALLOWED.
- ALL LOW VOLTAGE WIRE/CABLE FOR LIGHTING SENSORS, AUDIOVISUAL EQUIPMENT, GLASSROOM SOUND AMPLIFICATION, ETC. TO BE PROPERLY SUPPORTED PER THE TELEDATA, TELEVISION, AND LOW VOLTAGE SYSTEMS AND NOT PULLED THROUGH STRUCTURAL LINES. PULLING WIRE DIAGONALLY ACROSS ROOMS IS NOT ALLOWED. USING CEILING SYSTEM OR LIGHT FIXTURE SUPPORT/SEISMIC WIRES FOR SUPPORT IS NOT ALLOWED.
- PROVIDE GFCI PROTECTION ON ALL DEVICES AND EQUIPMENT PER THE NEC REQUIREMENTS. DEVICES SHALL BE READILY ACCESSIBLE. IF ANY OUTLET IS INSTALLED WITHIN 6 FEET OF OUTSIDE EDGE OF SINK, CONTRACTOR SHALL PROVIDE GFCI RECEPTACLE PER NEC, WHETHER SHOWN OR NOT.
- ALL RECEPTACLES LOCATED THROUGHOUT THE BUILDING SHALL BE TAMPER RESISTANT PER NEC.
- ELECTRICAL CONTRACTOR SHALL COORDINATE EXACT LOCATION OF ALL MECHANICAL UNITS WITH MECHANICAL CONTRACTOR. CIRCUITS TO ALL MECHANICAL EQUIPMENT SHALL BE DEDICATED UNLESS NOTED OTHERWISE.
- FOR VAV POWER, PROVIDE A DEDICATED 120/208 CIRCUIT FROM A PANEL LOCATED IN THE ELECTRICAL ROOM OF THE ASSOCIATED QUADRANT. COORDINATE EXACT LOCATION OF ALL VAV BOXES WITH MECHANICAL CONTRACTOR PRIOR TO ROUGH-IN.
- PROVIDE 120V CIRCUIT FROM NEAREST PROVIDED CIRCUIT FOR FIRESMOKE DAMPER RELAYS. PROVIDE FIRE ALARM MODULES AND RELAYS AS NECESSARY FOR ALL FIRESMOKE DAMPERS DRAWN ON THIS DRAWING. ALL FIRESMOKE DAMPERS SHALL HAVE A MANUAL OVERRIDE SWITCH. PROVIDE DUCT DETECTOR WITHIN 4 FEET OF EACH FIRESMOKE DAMPER.
- CONTRACTOR TO COORDINATE ALL LOCATIONS OF FIRESMOKE AND SMOKE DAMPERS WITH MECHANICAL CONTRACTOR. CONTRACTOR TO PROVIDE POWER, MONITOR MODULES, AND RELAYS AS REQUIRED FOR A COMPLETE SYSTEM.
- DIVISION 26 IS RESPONSIBLE TO PROVIDE CONDUIT AND ROUGH-IN FOR ALL THERMOSTAT CONTROLS LOCATED WITHIN WALLS. COORDINATE WITH THE CONTROLS CONTRACTOR AND VERIFY EXACT LOCATION OF ALL THERMOSTATS.

PROJECT TITLE: CLEVELAND ELEMENTARY SCHOOL
EMERY SCHOOL DISTRICT
CLEVELAND, UTAH
MECHANICAL UPGRADE


170 NORTH MAIN STREET
SPANISH FORK, UTAH 84660
www.kmaarchitects.com

KMA
ARCHITECTS




REVISIONS:


RESOLUT
40 W Cache Valley Blvd, Bldg 1, Suite B
info@resolutgroup.com



EP112




AREA B MAIN FLOOR POWER PLAN
SCALE = 1/8" = 1'-0"



PROJECT TITLE: CLEVELAND ELEMENTARY SCHOOL
EMERY SCHOOL DISTRICT
CLEVELAND, UTAH
MECHANICAL UPGRADE
CLEVELAND, UTAH

KMA
ARCHITECTS



REVISIONS:

RESOLUT
40 W Cache Valley Blvd, Bldg 1, Suite B
info@resolutgroup.com

EP113

KEYNOTES

P3 PROVIDE 110 VAC DROP TO NEAREST RECEPTACLE. CONTRACTOR IS RESPONSIBLE FOR FIELD VERIFYING ROUTING AND DATA ROOM/RACK LOCATION.
 P4 DISCONNECT EXISTING FAN COIL UNIT. RE-USE CIRCUIT FOR NEW FAN COIL UNIT. COORDINATE FINAL CONNECTION LOCATION WITH MECHANICAL CONTRACTOR AND REWORK EXISTING CIRCUITS AS NECESSARY.
 P6 EXISTING 40A 208V 3PH SQUARE D TYPE NOQ PANELBOARD. CONTRACTOR TO PROVIDE NEW BREAKERS WITHIN AS INDICATED.
 P7 REMOVE EXISTING 50A 3P SPARE BREAKER AND RETURN TO OWNER. PROVIDE NEW 40A 3P BREAKER FOR P-1.
 P8 UTILIZE SPARE 20A 1P BREAKER WITHIN PANELBOARD.
 P9 REMOVE EXISTING 50A 3P AND 100A 3P SPARE BREAKERS ON 25.27.29 AND 32.34.36 AND RETURN TO OWNER. PROVIDE NEW 30A 3P BREAKERS FOR P-2 AND P-3.

POWER GENERAL SHEET NOTES

1. COORDINATE PLACEMENT OF ELECTRICAL DEVICES WITH ARCHITECT PRIOR TO ROUGH-IN. WHERE DEVICES ARE SHOWN IN SAME WALL SPACE, ALIGN VERTICALLY AND HORIZONTALLY.
2. ALL THE LOW VOLTAGE WIRE/CABLE FOR LIGHTING SENSORS, AUDIOVISUAL EQUIPMENT, SOUND AMPLIFICATION, ETC. TO BE ROUTED THROUGH CONDUIT IN EXPOSED AND CLODED CEILING AREAS.
3. ALL LOW VOLTAGE WIRE/CABLE FOR LIGHTING SENSORS, AUDIOVISUAL EQUIPMENT, GLASSROOM SOUND AMPLIFICATION, ETC. TO BE PROPERLY SUPPORTED PER THE TELEDATA, GLASSROOM, AND LIGHTING DRAWINGS AND NOT TO OVERSTRAIN STRUCTURAL LINES. PULLING WIRE DIAGONALLY ACROSS ROOMS IS NOT ALLOWED. USING CEILING SYSTEM OR LIGHT FIXTURE SUPPORT/SEISMIC WIRES FOR SUPPORT IS NOT ALLOWED.
4. PROVIDE GFCI PROTECTION ON ALL DEVICES AND EQUIPMENT PER THE NEC REQUIREMENTS. DEVICES SHALL BE READILY ACCESSIBLE IF ANY OUTLET IS INSTALLED WITHIN 6 FEET OF OUTSIDE EDGE OF SINK. CONTRACTOR SHALL PROVIDE GFCI RECEPTACLE PER NEC, WHETHER SHOWN OR NOT.
5. ALL RECEPTACLES LOCATED THROUGHOUT THE BUILDING SHALL BE TAMPER RESISTANT PER NEC.
6. ELECTRICAL CONTRACTOR SHALL COORDINATE EXACT LOCATION OF ALL MECHANICAL UNITS WITH MECHANICAL CONTRACTOR. CIRCUITS TO ALL MECHANICAL EQUIPMENT SHALL BE DEDICATED UNLESS NOTED OTHERWISE.
7. FOR VAV POWER, PROVIDE A DEDICATED 120V/20A CIRCUIT FROM A PANEL LOCATED IN THE ELECTRICAL ROOM OF THE ASSOCIATED QUADRANT. COORDINATE EXACT LOCATION OF ALL VAV BOXES WITH MECHANICAL CONTRACTOR PRIOR TO ROUGH-IN.
8. PROVIDE 120V CIRCUIT FROM NEAREST PROVIDED CIRCUIT FOR FIRESMOKE DAMPER RELAYS. PROVIDE FIRE ALARM MODULES AND RELAYS AS NECESSARY FOR ALL FIRESMOKE DAMPERS DRAWN ON ECR 23 DRAWINGS. ALL FIRESMOKE DAMPERS SHALL HAVE A MANUAL OVERRIDE SWITCH. PROVIDE DUCT DETECTOR WITHIN 4 FEET OF EACH FIRESMOKE DAMPER.
9. CONTRACTOR TO COORDINATE ALL LOCATIONS OF FIRESMOKE AND SMOKE DAMPERS WITH MECHANICAL CONTRACTOR. CONTRACTOR TO PROVIDE POWER, MONITOR MODULES, AND RELAYS AS REQUIRED FOR A COMPLETE SYSTEM.
10. DIVISION 26 IS RESPONSIBLE TO PROVIDE CONDUIT AND ROUGH-IN FOR ALL THERMOSTAT CONTROLS LOCATED WITHIN WALLS. COORDINATE WITH THE CONTROLS CONTRACTOR AND VERIFY EXACT LOCATION OF ALL THERMOSTATS.

