



## SCOTT-LITE CONTRACTOR



## SCOTT-LITE CONTRACTOR PRO



### Standard lengths 8'– 12'

- Knocked down for economical shipping
- 80" and 94" widths available
- 3" aluminum I-beam Crossmembers, 16" standard crossmember spacing
- 6" aluminum channel long sills
- 7/8" extruded aluminum floor with 4 3/4" extruded aluminum front and side rails
- 36" standard contoured bulkhead with integrated punched window
- 16" double walled (1/8") fold down sides and rear
- 1/8" double walled permanent rear corner posts
- Lighting and marking to FMVSS #108 Standard
- LED body marker lights

### Options

- Rear skirt with LED stop, turn, tail, and back-up light package

Try our new  
hoist calculator.



### Standard lengths 8'6" x Width 80"

- Knocked down for economical shipping
- 4 3/4" extruded aluminum front and side rails
- 3" aluminum channel long sills – 38" and 42" OD
- 3" aluminum I-beam crossmembers, 16" standard crossmember spacing
- 7/8" extruded aluminum floor
- 38" formed bulkhead with integrated punched window
- Removable bulkhead goal posts
- 18" double walled (1/8") fold down sides and rear
- Single lever tailgate release or double latch release
- 6 contractor D-rings
- Pre-wired for ease of installation
- LED Lighting and marking to FMVSS #108 Standard

### Options

- Current model Ram, Ford, and GM mounting kits available.

