

- SINGLE CYLINDER HOIST AVAILABLE
- DUAL CYLINDER HOIST AVAILABLE



SCAN TO VISIT  
TAFCOEQUIP.COM



# ALUMINUM TRUCK BODIES



## SCOTT HAULER

**Standard Lengths**  
8'-12'  
**Available Widths**  
80"-94"

**Crossmembers**  
3" Al. I-Beam  
12" Crossmember  
Spacing

**Longsills**  
4" Al. Channel  
Longsills

**Flooring**  
7/8" Extruded  
Smooth Al. Floor



## SCOTT-LITE PLATFORM

**Standard Lengths**  
7'-12'  
**Available Widths**  
80"-94"

**Crossmembers**  
3" Al. I-Beam  
24" Crossmember  
Spacing

**Longsills**  
4" Al. I-Beam  
Longsills. Other  
Options Available

**Flooring**  
7/8" Extruded  
Smooth Al. or T&G  
Douglas Fir



## SCOTT-LITE CONTRACTOR

**Standard Lengths**  
8'-12'  
**Available Widths**  
80" & 94"

**Crossmembers**  
3" Al. I-Beam  
16" Crossmember  
Spacing

**Longsills**  
6" Al. Channel  
Longsills

**Flooring**  
7/8" Extruded Al.  
Floor



## SCOTT-LITE CONTRACTOR PRO

**Standard Lengths/Widths**  
8'6" L x 80" W

**Crossmembers**  
3" Al. I-Beam  
16" Crossmember  
Spacing

**Longsills**  
3" Al. Channel w/  
38" & 42" OD

**Flooring**  
7/8" Extruded Al.  
Floor



## CONVENTIONAL LANDSCAPER

**Standard Lengths**  
9'-16'  
**Available Widths**  
96" W w/ 50" H Wall

**Crossmembers**  
(9'-12') 3" Al. I-Beam  
(14'-16') 4" I-Beam  
w/ 16" Spacing

**Longsills**  
(9'-12') 6" Al. or  
(14'-16') 7" Steel

**Sides**  
.125" Smooth Al.,  
Smooth Exterior &  
Smooth Interior



## BULK/ENSILAGE DUMP BODIES

**Standard Lengths**  
14'-26'  
**Available Widths**  
96" W w/ 62" H Wall

**Crossmembers**  
4" Al. Channel  
16" Standard  
Spacing

**Longsills**  
14', 16' & 18' w/ 7"  
Steel Channel or  
20'-26' w/ 8" Steel

**Flooring**  
1 1/4" Al. Extruded Floor  
w/ 6.85" Extruded Front  
& Side Rails



## GRAIN BODIES

**Standard Lengths**  
14'-26'  
**Available Widths**  
96" or 102"

**Crossmembers**  
4" Al. Channel or  
4" I-Beam w/ 16"  
Standard Spacing

**Longsills**  
14', 16' & 18' w/ 7"  
Steel Channel or  
20'-26' w/ 8" Steel

**Flooring**  
1 1/4" Al. Extruded Floor  
w/ 6.85" Extruded Front  
& Side Rails



## SCOTT CHIPPER

**NEW**

**Standard Lengths**  
14'-26'  
**Available Widths**  
96" or 102"

**Crossmembers**  
4" Al. Channel  
16" Standard  
Spacing

**Longsills**  
14', 16' & 18' w/ 7"  
Steel Channel or  
20'-26' w/ 8" Steel

**Flooring**  
1 1/4" Al. Extruded Floor  
w/ 6.85" Extruded Front  
& Side Rails



## SMOOTH-SIDED LANDSCAPER

**Standard Lengths**  
9'-16'  
**Available Widths**  
96" W w/ 50" H Wall

**Crossmembers**  
(9'-12') 3" Al. I-Beam  
(14'-16') 4" I-Beam  
w/ 16" Spacing

**Longsills**  
(9'-12') 6" Al. or  
(14'-16') 7" Steel

**Sides**  
.125" Smooth Al.,  
"Formed" Smooth Exterior  
& Smooth Interior



## MAGNUM CONTRACTOR DUMP

**Standard Lengths/Widths**  
9'-18' x 96" W

**Crossmembers**  
3" Al. I-Beam  
12" Crossmember  
Spacing

**Longsills**  
6" Al. Channel /  
14' or Longer Built  
w/ 7" Steel Channel

**Flooring**  
1 1/4" Extruded Al.  
Floor



## MAGNUM DUMP BODY

**Standard Lengths/Widths**  
8'10", 9'8" 10'6" &  
11'4 x 96" W

**Crossmembers**  
No Crossmembers  
To Allow For Low  
Mounting Height

**Longsills**  
6" Al. Channel  
Longsills

**Flooring**  
1 1/4" Al. Extruded floor  
w/ 6.85" Extruded Al.  
Side Rails



## MEGA MAGNUM

**NEW**

**Standard Lengths/Widths**  
9' 6" or 11'6" x 96"  
W 5-7 Yard Capacity

**Crossmembers**  
3" Al. I-Beam  
12" Crossmember  
Spacing

**Longsills**  
6" Aluminum  
Channel Longsills

**Flooring**  
1 1/4" Extruded  
Smooth Al. w/ 6.85"  
Extruded Al. Sides




## MAGNUM PLATFORMS

**Standard Lengths**  
9'-30'  
**Available Widths**  
91 1/2" or 97 1/2"

**Crossmembers**  
4" Al. Channel  
16" Standard  
Spacing

**Longsills**  
4" Al. I-Beam  
Longsills. Other  
Options Available

**Flooring**  
1 1/4" Extruded Smooth  
Al. Or Grip Type T&G  
Douglas Fir



**Apitong Upgrade Available**