

- SINGLE CYLINDER HOIST AVAILABLE
- DUAL CYLINDER HOIST AVAILABLE



SCAN TO VISIT
TAFCOEQUIP.COM



ALUMINUM TRUCK BODIES



SCOTT HAULER

Standard Lengths
8'-12'
Available Widths
80"-94"

Crossmembers
3" Al. I-Beam
12" Crossmember
Spacing

Longsills
4" Al. Channel
Longsills

Flooring
7/8" Extruded
Smooth Al. Floor



SCOTT-LITE PLATFORM

Standard Lengths
7'-12'
Available Widths
80"-94"

Crossmembers
3" Al. I-Beam
24" Crossmember
Spacing

Longsills
4" Al. I-Beam
Longsills. Other
Options Available

Flooring
7/8" Extruded
Smooth Al. or T&G
Douglas Fir



SCOTT-LITE CONTRACTOR

Standard Lengths
8'-12'
Available Widths
80" & 94"

Crossmembers
3" Al. I-Beam
16" Crossmember
Spacing

Longsills
6" Al. Channel
Longsills

Flooring
7/8" Extruded Al.
Floor



SCOTT-LITE CONTRACTOR PRO

Standard Lengths/Widths
8'6" L x 80" W

Crossmembers
3" Al. I-Beam
16" Crossmember
Spacing

Longsills
3" Al. Channel w/
38" & 42" OD

Flooring
7/8" Extruded Al.
Floor



CONVENTIONAL LANDSCAPER

Standard Lengths
9'-16'
Available Widths
96" W w/ 50" H Wall

Crossmembers
(9'-12') 3" Al. I-Beam
(14'-16') 4" I-Beam
w/ 16" Spacing

Longsills
(9'-12') 6" Al. or
(14'-16') 7" Steel

Sides
.125" Smooth Al.,
Smooth Exterior &
Smooth Interior



BULK/ENSILAGE DUMP BODIES

Standard Lengths
14'-26'
Available Widths
96" W w/ 62" H Wall

Crossmembers
4" Al. Channel
16" Standard
Spacing

Longsills
14', 16' & 18' w/ 7"
Steel Channel or
20'-26' w/ 8" Steel

Flooring
1 1/4" Al. Extruded Floor
w/ 6.85" Extruded Front
& Side Rails



GRAIN BODIES

Standard Lengths
14'-26'
Available Widths
96" or 102"

Crossmembers
4" Al. Channel or
4" I-Beam w/ 16"
Standard Spacing

Longsills
14', 16' & 18' w/ 7"
Steel Channel or
20'-26' w/ 8" Steel

Flooring
1 1/4" Al. Extruded Floor
w/ 6.85" Extruded Front
& Side Rails



SCOTT CHIPPER

NEW

Standard Lengths
14'-26'
Available Widths
96" or 102"

Crossmembers
4" Al. Channel
16" Standard
Spacing

Longsills
14', 16' & 18' w/ 7"
Steel Channel or
20'-26' w/ 8" Steel

Flooring
1 1/4" Al. Extruded Floor
w/ 6.85" Extruded Front
& Side Rails



SMOOTH-SIDED LANDSCAPER

Standard Lengths
9'-16'
Available Widths
96" W w/ 50" H Wall

Crossmembers
(9'-12') 3" Al. I-Beam
(14'-16') 4" I-Beam
w/ 16" Spacing

Longsills
(9'-12') 6" Al. or
(14'-16') 7" Steel

Sides
.125" Smooth Al.,
"Formed" Smooth Exterior
& Smooth Interior



MAGNUM CONTRACTOR DUMP

Standard Lengths/Widths
9'-18' x 96" W

Crossmembers
3" Al. I-Beam
12" Crossmember
Spacing

Longsills
6" Al. Channel /
14' or Longer Built
w/ 7" Steel Channel

Flooring
1 1/4" Extruded Al.
Floor



MAGNUM DUMP BODY

Standard Lengths/Widths
8'10", 9'8" 10'6" &
11'4 x 96" W

Crossmembers
No Crossmembers
To Allow For Low
Mounting Height

Longsills
6" Al. Channel
Longsills

Flooring
1 1/4" Al. Extruded floor
w/ 6.85" Extruded Al.
Side Rails



MEGA MAGNUM

NEW

Standard Lengths/Widths
9' 6" or 11'6" x 96"
W 5-7 Yard Capacity

Crossmembers
3" Al. I-Beam
12" Crossmember
Spacing

Longsills
6" Aluminum
Channel Longsills

Flooring
1 1/4" Extruded
Smooth Al. w/ 6.85"
Extruded Al. Sides



MAGNUM PLATFORMS

Standard Lengths
9'-30'
Available Widths
91 1/2" or 97 1/2"

Crossmembers
4" Al. Channel
16" Standard
Spacing

Longsills
4" Al. I-Beam
Longsills. Other
Options Available

Flooring
1 1/4" Extruded Smooth
Al. Or Grip Type T&G
Douglas Fir



Apitong Upgrade Available

- SINGLE CYLINDER HOIST AVAILABLE
- DUAL CYLINDER HOIST AVAILABLE



STEEL TRUCK BODIES



SCAN TO VISIT
TAFCOEQUIP.COM



STEEL CONTRACTOR

Standard Lengths/Widths
8'-18' x 96" W

Crossmembers
4 1/2" Formed
Crossmembers w/
12" Standard Spacing

Longsills
(8'-12') 6" steel
(14' or longer) 7"
Steel Channel

Flooring
10-Gauge Smooth
Steel Floor



DUMP BODY

Standard Lengths/Widths
Dependant On
Dump Body Model

Crossmembers
Dependant On
Dump Body Model

Longsills
Dependant On
Dump Body Model

Flooring
Dependant On
Dump Body Model



SMOOTH-SIDED LANDSCAPER

Standard Lengths
12'
Available Widths
96" W w/ 50" H Wall

Crossmembers
4 1/2" Steel Formed
Crossmembers w/
12" Spacing

Longsills
6" Steel Channel
Longsills

Flooring
10-Gauge Smooth
Steel Floor



CONVENTIONAL LANDSCAPER

Standard Lengths
9'-16'
Available Widths
96" W w/ 50" H Wall

Crossmembers
(9'-12') 4 1/2" Steel
w/ 16" Spacing or
(14'-16') 4 1/2" Steel
w/ 12" Spacing

Longsills
(9'-12') 6" Steel or
(14'-16') 7" Steel

Flooring
(9'-12') 12 Gauge Or
(14'-16') 10 Gauge
Smooth Steel Floors



TEAR OFF BODY

Standard Lengths
12'-16'
Available Widths
96" W w/ 50" H

Crossmembers
6" Steel Formed
Crossmembers w/
12" Spacing

Longsills
(12') 6" Steel Or
(14'-16') 7" Steel
Channel Longsills

Flooring
10-Gauge Smooth
Steel Floor



STRUCTURAL PLATFORM

Standard Lengths
12'-30'
Available Widths
97 1/2", 102" OD W

Crossmembers
4" Structural Steel
Channel w/ 12"
Standard Spacing

Longsills
6"-8" Steel Channel
Longsills (Based On
Body Length)

Flooring
Variety Of Steel
& Wood Flooring
Options



STANDARD DUTY CITY STAKE

Standard Lengths
9'-30'
Available Widths
96" or 102" OD W

Crossmembers
Crossmember
Options Dependant
On Flooring Options

Longsills
5" Structural Steel
Channel Longsills.
Options Available

Flooring
Variety Of Steel
& Wood Flooring
Options



BULK/ENSILAGE DUMP BODIES

Standard Lengths
14'-24'
Available Widths
96" W w/ 62" H Wall

Crossmembers
Steel Formed w/ 12"
Spacing

Longsills
(14'-18') 7"
(19'-24') 8"

Flooring
10-Gauge Smooth
Steel Flooring



GRAIN BODY


Standard Lengths
9'-16'
Available Widths
96" W w/ 50"/62" H

Crossmembers
12', 14'-24'
Steel Formed
Crossmembers

Longsills
(12') 6" Channel
(14'-18') 7" Channel
(19'-24') 8" Channel

Flooring
10-Gauge Smooth
Steel Or T&G
Douglas Fir

+
Apitong
Upgrade
Available



SCOTT LEVEL-LIFT HOISTS



DUAL PIN
INTERLOCK
U.S. Patent No.
12,404,156



CONTROL
OPTIONS

Gear Pump
Operation

SINGLE CYLINDER LL400-LL800 | DOUBLE ACTING

Our LL-400 through LL-800 model hoists for Class B through Class F applications. All models are distinctively engineered for lift stability and installation versatility.

DUAL CYLINDER LL1000-LL3000 | SINGLE ACTING

Models LL-1000 through LL-3000 employ a unique combination of twin telescopic cylinders, mounted within a superior-designed scissor frame and built to give maximum torsional strength to handle uneven loads.



POWER PACKAGES

FOR LL400-LL800

- With Standard Electric Pump
- With Twin-Motor Electric Pump
- With Double-Valve Electric Pump
- With Gear Pump & Double Valve Reservoir (Cable Op.)
- With Gear Pump & 12 Volt Valve Reservoir
- With Gear Pump & 12 Volt Premium Valve Reservoir



FOR LL1000-LL3000

- With Gear Pump & 50 Quart Reservoir/Single Valve
- With Gear Pump & 60 Quart Reservoir/Single Valve

