



## QUOTE REQUEST

GH Alaska, LLC has over 29 years' experience installing epoxy floors in Alaska.

www.ghalaska.com • (907) 414-4941 • ghakmngr@gmail.com

NAME: \_\_\_\_\_ DATE: \_\_\_\_\_

PHONE: \_\_\_\_\_ BEST TIMES TO CALL: \_\_\_\_\_ ☐ TEXTS OK

EMAIL: \_\_\_\_\_

PROJECT ADDRESS: \_\_\_\_\_ CITY: \_\_\_\_\_ STATE: \_\_\_\_\_ ZIP: \_\_\_\_\_

☐ Commercial ☐ Residential

<b>PROJECT TYPE</b>	<input type="checkbox"/> Hangar* <input type="checkbox"/> Kitchen <input type="checkbox"/> Basement	<b>DIMENSIONS:</b> Length x Width _____ x _____	<b>COMPLETION DATE DESIRED:</b> _____
	<input type="checkbox"/> Garage* <input type="checkbox"/> _____	<b>TOTAL Square Feet (SF):</b> _____	
	<input type="checkbox"/> Shop*    _____	<b>TYPE OF HEAT:</b> <input type="checkbox"/> In-Floor <input type="checkbox"/> Overhead <input type="checkbox"/> Baseboard	
	* Number of overhead doors _____		

### FLOORING OPTIONS DESIRED:

<input type="checkbox"/> <b>Flake</b> (Includes solid color base coat) Flake Colors: 1. _____ 2. _____ 3. _____ <input type="checkbox"/> Special Order Flake Blend: _____ Flake Design Tool: <a href="https://www.chipsunlimited.com">https://www.chipsunlimited.com</a>	Flake Broadcast: <input type="checkbox"/> Full <input type="checkbox"/> Medium <input type="checkbox"/> Light Flake Size: <input type="checkbox"/> 1/4" <input type="checkbox"/> 1/8" <input type="checkbox"/> 1/16"	<input type="checkbox"/> <b>Metallic</b> (Includes solid color base coat) Metallic Colors: 1. _____ 2. _____ Metallic info: <a href="https://torginol.com/floors/products/pigment">https://torginol.com/floors/products/pigment</a>
<input type="checkbox"/> <b>Single Solid Color</b> (Does not include flake or metallic) Color Chart: _____ <a href="https://smithpaints.com/color-charts-all-charts/industrial-coating/color-charts-isc/">https://smithpaints.com/color-charts-all-charts/industrial-coating/color-charts-isc/</a>	<input type="checkbox"/> <b>Quartz</b> (Usually used on commercial floors) Color: _____ Granule Size: <input type="checkbox"/> 25A <input type="checkbox"/> 40S	
<input type="checkbox"/> <b>Coating Foundation Block or Wood Base</b> to match floor Height: <input type="checkbox"/> 4" <input type="checkbox"/> 6" Total Linear Feet: _____ Flake or solid color only.	<input type="checkbox"/> <b>Joint Filling</b> (Describe extent) _____	
<input type="checkbox"/> <b>Polished &amp; Sealed Concrete*</b>	<input type="checkbox"/> <b>Stained &amp; Sealed Concrete*</b>	

\* NOTE: Sealing concrete does not prevent stains and must be re-sealed periodically, requiring greater maintenance than epoxy coatings. Seamless epoxy coatings won't collect dirt, moisture or germs and provide greater protection, sanitation and durability.

**SUBSTRATE:** ☐ Concrete: Date/Year installed \_\_\_\_\_ ☐ Slab-on-grade ☐ Over a crawl space ☐ Has cracks ☐ Has saw-cut joints

☐ Gypcrete ☐ Wood ☐ Tile ☐ Other \_\_\_\_\_

☐ Sealer, coating or paint on floor: ☐ Yes ☐ No If yes, describe: Manufacturer/Product: \_\_\_\_\_

☐ Grease or oil spots—describe extent: \_\_\_\_\_

☐ Known moisture issues with flooring or foundation—describe: \_\_\_\_\_

72-hour moisture testing is conducted prior to installation to determine if a moisture vapor transmission primer is required.

**SITE VISIT CONSULTING FEE:** \$150 – credited at time of invoicing on projects

Samples of flooring options may be seen at our office: 201 E. Swanson Ave., Suite 1, Wasilla, AK • M-F, 9-12:30, 2-5

How did you learn about GH Alaska? \_\_\_\_\_