

Smith's

EPOXY ADDITIVE

U.V. ABSORBER

Product Data Sheet

UVA-PDS-031121

DESCRIPTION: Smith's Epoxy U.V. Absorber additive enhances the durability and extends the service life of the epoxy film by absorbing UVA radiation thus lessening U.V. light degradation (i.e. Yellowing, Chalking, Cracking, etc.). For use in 100% Solids Epoxy, such as Smith's Epoxy UCE200 or Smith's Epoxy U100.

RECOMMENDED USES:

- Residential, Retail & light Commercial applications
- Matrix for Metallic & Luster coatings
- Matrix for broadcast systems - Vinyl Chip or Color Quartz
- Matrix for solid colors (optional for high natural light exposure)

HIGHLIGHTS:

- Absorbs UVA Rays
 - Slows epoxy degradation caused by Ultra Violet light radiation
- Extends service life of decorative epoxy
- Improves clarity of clear & metallic epoxy coatings

STORAGE: Indoors between 40°F (4.4°C) to 100°F (37.7°C)

SUBSTRATE APPLICATION TEMPERATURE:

60°F (15.5°C) to 95°F (35°C)

SHELF LIFE:

Original, unopened containers = 2 Years
Opened Containers = 30 Days

PACKAGE SIZE:

SCS-EUVA-0004 4 fl.oz. Bottle

PROPERTIES:

Property	Test Method	Results
U.V. Exposure Unit	ASTM G154-1	*Results in photo
Color		Yellow
VOC's	ASTM D3960	Zero (0) g/L
Volume Mix Ratio		Add 1% by Volume to mixed 100% solids epoxy



LIMITATIONS:

- Smith's Epoxy U.V. Absorber additive (sold separately) can be used to lessen U.V. damage / discoloration but not completely eliminate epoxy damage discoloration over time
- For use in 100% solids epoxy only

MIXING:

Add 1 bottle (4 fl.oz.) to 3 gallons of 100% solids epoxy while mixing Part A with Part B using a low speed (<450 RPM) drill with paint mixing paddle attached for 2 to 3 minutes. *"Stick" mixing is not recommended.*

If part mixing by volume, add 1% of Smith's Epoxy U.V. Absorber to total volume of mixed liquid epoxy product. For example:

- $\frac{3}{4}$ gallons epoxy = 1 oz. of Smith's Epoxy U.V. Absorber
- 1 $\frac{1}{2}$ gallons epoxy = 2 oz. of Smith's Epoxy U.V. Absorber

For use in the following Smith Paint's epoxy products:

[Smith's Epoxy UCE200](#) [Smith's Epoxy GEL150](#)
[Smith's Epoxy U100](#) [Smith's Epoxy GEL150/FC](#)
[Smith's Epoxy FC125](#) [Smith's Epoxy SLS100](#)

Smith's Epoxy HD-100 Color Quartz Mortar system

Application method varies depending on the coating system. See epoxy product data sheet for detailed instructions.

NOTE:

- **DO NOT TURN THE MIXING VESSEL UPSIDE DOWN ON THE SUBSTRATE TO ALLOW THE RESIDUAL PRODUCT TO DRAIN ONTO THE FLOOR TO AVOID THE RISK OF ANY UNMIXED OR NON-THOROUGHLY CATALYZED PRODUCT FROM THE SIDES AND BOTTOM OF THE MIXING VESSEL FROM REACHING THE FINISHED FLOOR.** Best practice, pour contents of mixing vessel into a new container, mechanically stir to ensure thorough blending then transport to the floor for application
- It is best practice to "box" color packs, especially if using color packs from multiple batches, to ensure consistent solid colors

LIMITED LIABILITY: Upon information, belief and to the best of our knowledge, the information contained herein is true accurate as of the date of issuance of this particular document and any and all information conveyed, whether expressed or implied is subject to change without prior notice. We guarantee our products to conform to Smith Paint Products quality control standards, but not to any other standards unless specifically stated in written documentation. Smith Paint Products assumes no liability for coverage, performance, injury results from use, misuse or usage not described in any promotional materials or regulatory infraction determined by using our products. The applicator assumes all liability for use and local regulatory compliance. Promotional materials are not a supplementation to any product purchase agreement, nor should such documents be considered a type of contract, if any is reduce to writing.

Liability is limited to replacement of defectively manufactured product of the same type and cost of the originally purchased product upon presentation of a valid, fully paid invoice at the time of a claim. No warranty shall be granted for outstanding invoices or for accounts with unpaid balances until paid in full. No damages, whether consequential, liquidated or other, shall be provided under this Limitation of Liability and Limited Warranty. Should a product defect be suspected at the time of application, cease use of the product immediately and notify Smith Paint Products for investigation as you will be responsible for the cost to repair or replace any work performed with product(s) suspected of defect. Record batch codes and save all products you purchased in order for any warranty to occur along with the invoice that matches said quantity.

NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY SMITH PAINT PRODUCTS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. DO NOT PURCHASE AND USE THIS PRODUCT IF YOU HAVE NOT AGREED TO THE ABOVE TERMS.



Smith Paint Products® • 2200 Paxton Street • Harrisburg, PA 17111 • 800-466-8781 • www.smithpaints.com