ENGINE DETAILS

Controls

Delivers the ultimate in compact versatility. Great for aluminum console, bass, offshore fishing,

inflatable rigid hull (RIB), fish & ski, and runabout boats, pontoons and tritoons.
SPECIFICATIONS - 135
HP / kW
135 / 101
Engine type
8-valve single overhead cam (SOHC)
Inline 4
Displacement (L)
3.0
Full throttle RPM
4800-5300
Air induction
Performance-Tuned Scroll Intake Manifold
Fuel induction system
Computer Controlled Multi-Port Electronic Fuel Injection (EFI)
Alternator amp / Watt
60 amp / 756 watt (Belt-Driven)
Recommended fuel
Unleaded 91 RON Minimum
Recommended oil
Mercury FourStroke Oil 10W-30
Engine protection operator warning system
SmartCraft Engine Guardian
Compatible with SmartCraft digital technology
Yes
Starting
Electric (turn-key)
Smart Start Electric

Mechanical throttle & shift
Steering
Big Tiller Compatible
Dual cable mechanical
Electro-Hydraulic Power Steering Optional on Duals
Hydraulic power steering
Shaft length
20" / 508 mm
25" / 635 mm
Gearcase ratio
1.92:1
Dry weight *Lightest model available
455 lbs / 206 kg
Emissions Star Rating
3
Bore and stroke
4.0 x 3.6" / 102 x 92 mm
Ignition
SmartCraft ECM 70 Digital Inductive
Fuel system
Electronic Fuel Injection (EFI)
Cooling system
Water-cooled with thermostat
Gear shift
F-N-R
Gearcase options
Standard
Trim system
Power Tilt
Power Trim
Exhaust system

Through prop
Counter Rotation
Available
Color
Phantom Black
Lubrication system
Wet sump
Oil Capacity
6.3 qts / 6.0l
Maximum Trim Range
22° (-6° to 16°)
Maximum Tilt Range

73° (-6° to 67°)

SEE ALL SPECS