# GENERAL PROTECTION MAT PRODUCT SHEET



### PRODUCT DESCRIPTION

The Honcho General Protection Mat is an innovative surface protection solution, suitable for a range of substrates. The General Protection Mat offers protection under foot traffic, building materials, stains, such as paint, and ladders.

Suitable for use for up to 6 months on <u>internal</u> <u>projects only.</u>



- Ideal for end of project finishes
- Protects surfaces from scratches, stains and provides light impact protection
- Ideal for use under foot traffic, ladders and small trolleys
- · Easy to install & remove
- Can be used on vertical surfaces (in combination with tape), such as doors
- Great for counter tops, joinery & more
- Prevents stains, such as paints & oils


#### **USES & LIMITATIONS**

- Timber & engineered floors
- Porcelain & ceramic tile
- Marble & stone\*
- Cured concrete\*
- Carpet
- Sheet vinyl & laminate
- Glass, epoxy, metal, bathtubs, sinks & counter tops
- · Ideal for light commercial and residential projects

### **SPECIFICATIONS**

Roll Size: 1m x 50mSquare Meterage: 50mColour: Light GreyRoll Weight: 11.67kg

• Product Code: GPMLD20







**Prevents Stains** 



oot Traffic





Prevents Scratches





**UV** Resistant



Easy Application & Removal

Disclaimer: Customers are advised to consider the information in this data sheet in the context of how the product will be used, including surfaces and any other products used. The information provided in this guide represents our best scientific and practical knowledge. Any advice, information or assistance provided by Honcho Supplies in relation to its products is given in good faith, however is provided without liability or responsibility. Due to the wide variety of site conditions we are unable to assume liability for any loss that may arise from the use of ourproducts. The user is responsible for checking the suitability of products for their intended use.

# GENERAL PROTECTION MAT INSTALLATION GUIDE



#### INSTALLING THE MATS

- **1.** Ensure surface is clean and dry prior to installing <u>It is important to have the logo side facing up</u>
- **2.** Kick the roll out in a straight line to create your first row
- **3.** When starting the second row, overlap the first roll of the matting by approximately 3cm
- **4.** Tape along the seams to secure the mat to itself, preventing dust, dirt and debris from getting in underneath. This will also reduce movement of the mat
- **5.** Complete each row as above until your surface is covered
- **6.** We recommend covering the whole surface to reduce the risk of uneven UV exposure
- **7.** The mat can be lifted to inspect the substrate at any time or re-adjusted as needed

<u>Always consult with your Honcho rep to ensure substrate</u> <u>suitability</u>



## TAPING/SECURING THE MAT

We recommend using Gorilla Tape to secure the mat rows together. Gorilla Tape should **not** be applied directly to the surface as it can leave residue.

Gorilla Tape is available for purchase through Honcho Supplies.





Disclaimer: Customers are advised to consider the information in this data sheet in the context of how the product will be used, including surfaces and any other products used. The information provided in this guide represents our best scientific and practical knowledge. Any advice, information or assistance provided by Honcho Supplies in relation to its products is given in good faith, however is provided without liability or responsibility. Due to the wide variety of site conditions we areunable to assume liability for any loss that may arise from the use of our products. The user is responsible for checking the suitability of products for their intended use.