

# HT COMMERCIAL MATS (LOOSE LAID) MAINTENANCE GUIDE



## MAINTAINING THE HT COMMERCIAL (LOOSE-LAID) MATS AFTER INSTALLATION

1. If tape comes loose in certain areas, we recommend re-taping with fresh tape
2. Should you encounter any tears in the HT Commercial Mat, we recommend taping in those areas. Alternatively, you can cut a piece of the matting from any leftovers and patch over the tear with tape
3. If significant rainfall occurs and pooling of water is evident on the matting, we recommend using a broom or squeegee to remove the excess water
4. Should you need to re-lay a new section of the matting, please refer to the Product & Application Sheet for installation steps
5. One of the main benefits with loose laying the mats is that you can peel up the matting every so often to check the slab
6. We recommend using a good quality cloth tape (e.g. Nashua 357 Gaffer Tape) to secure the seams of the mats together. Nashua Tape is available for purchase through Honcho Supplies.
7. We also recommend sufficiently weighing down/securing the mats when used externally to minimise risk of displacement due to wind and extreme weather events



Disclaimer: Customers are advised to consider the information in this data sheet in the context of how the product will be used, including surfaces and any other products used. The information provided in this guide represents our best scientific and practical knowledge. Any advice, information or assistance provided by Honcho Supplies in relation to its products is given in good faith, however, is provided without liability or responsibility. Due to the wide variety of site conditions, we are unable to assume liability for any loss that may arise from the use of our products. The user is responsible for checking the suitability of products for their intended use.