

Safety Data Sheet – Uni-CA-892 Argon/C02 Mixture

WARNING




Safety Data Sheet (SDS)

Argon/C02 Uni-CA-892

1 PRODUCT AND COMPANY DETAILS	
1.1 Product Identifier	
Product Name	Uni-CA-892
Proper Shipping Name	UN Number: 1956 Proper Shipping Name: COMPRESSED GAS, N.O.S (CONTAINS ARGON,AND CARBON DIOXIDE)
Chemical Formula	Argon / C02
1.2 Recommended use and restrictions on use	
Use(s)	Industrial and professional. Perform risk assessment prior to use. Test gas/Calibration gas. Purge gas, diluting gas, inerting gas. Purging. Use for manufacture of electronic/photovoltaic components. Shield gas for welding processes. Laboratory use. Food applications. Contact supplier for more information on uses.
Restrictions	Asphyxiant in high concentrations.
1.3 Supplier details	
Supply Company	Agas National PTY Ltd. PO Box 6063 Riverview Qld 4303
General Enquiries	TEL (07) 3282 5783

Safety Data Sheet – Uni-CA-892 Argon/CO2 Mixture

Technical Enquiries Specific to product	Agasnational.com.au 07 32825783
Emergency Telephone 0449252427 all hours	
2 HAZARDS IDENTIFICATION	
2.1 Classification of the substance or mixture	
Classification according to WHS Regulation Physical hazards Gases under pressure : Compressed gas H280	
GHS Classification	Flammable Gases: Category 1 Gases under pressure: Liquefied gas
2.2 Label Elements	
Signal word	Warning
Pictogram	
Hazard statement(s)	H280 - Contains gas under pressure; may explode if heated.
Prevention Statement(s)	Asphyxiant in high concentrations.
Response Statement(s)	Water spray or fog. Do not use water jet to extinguish.
Storage statement	Storage : P403 - Store in a well-ventilated place.
Disposal Statement	None allocated
2.3 Other Hazards	
Asphyxiant in high concentrations.	

Safety Data Sheet – Uni-CA-892 Argon/CO2 Mixture

3 COMPOSITION AND INFORMATION ON INGREDIENTS			
3.1 Substances / Mixtures			
Name	Product Identifier	%	Classification according to WHS Regulation
Ingredients Chemical Entity Argon	(CAS-No.) 7440-37-1	90-94	Press. Gas (Comp.), H280
Carbon Dioxide	(CAS-No.) 124-38-9	6-10	
4 FIRST AID			
4.1 Description of first aid measures			
Eye	Adverse effects not expected from this product.		
Inhalation	Remove victim to uncontaminated area wearing self-contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.		
Skin	Adverse effects not expected from this product.		
Ingestion	Ingestion is not considered a potential route of exposure.		
4.2 Most important symptoms and effects, both acute and delayed			
In high concentrations may cause asphyxiation. Symptoms may include loss of Mobility / consciousness. Victim may not be aware of asphyxiation. Refer to section 11.			
4.3 Immediate medical attention and special treatment needed			
None.			
5 FIRE FIGHTING MEASURES			
5.1 Extinguishing media			
- Suitable extinguishing media	Water spray or fog.		
- Unsuitable extinguishing media	Do not use water jet to extinguish.		
5.2 Special hazards arising from the substance or mixture			

Safety Data Sheet – Uni-CA-892 Argon/C02 Mixture

Specific hazards Hazardous combustion products	Exposure to fire may cause containers to rupture/explode. None.
5.3 Advice for fire-fighters	
Specific methods	Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.
Special protective equipment for fire fighters	In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.
5.4 Hazchem code	
2T	
6 ACCIDENTAL RELEASE MEASURES	
6.1 Personal precautions, protective equipment and emergency procedures	
Try to stop release. Evacuate area. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Act in accordance with local emergency plan. Stay upwind. Oxygen detectors should be used when asphyxiating gases may be released.	
6.2 Environmental precautions	
Try to stop release.	

Safety Data Sheet – Uni-CA-892 Argon/CO2 Mixture

6.3 Methods of cleaning up
Ventilate area.
6.4 Reference to other sections
See sections 8 and 13 for exposure controls and disposal.
7 HANDLING AND STORAGE
7.1 Precautions for safe handling
Safe use of the product The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularly) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid suck back of water, acid and alkalis. Do not breathe gas. Avoid release of product into atmosphere.
Safe handling of the gas receptacle Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the

Safety Data Sheet – Uni-CA-892 Argon/CO2 Mixture

<p>cylinder contents. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock.</p>	
<p>7.2 Conditions for safe storage, including any incompatibilities</p>	
<p>Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.</p>	
<p>7.3 Specific end use(s)</p>	
<p>No information provided.</p>	
<p>8 EXPOSURE CONTROLS AND PERSONAL PROTECTION</p>	
<p>8.1 Control parameters</p>	
<p>OEL (Occupational Exposure Limits) : No data available. DNEL (Derived-No Effect Level) : No data available. PNEC (Predicted No-Effect Concentration) : No data available.</p>	
<p>8.2 Exposure Controls</p>	
<p>8.2.1. Appropriate engineering controls Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Oxygen detectors should be used when asphyxiating gases may be released. Consider the use of a work permit system e.g. for maintenance activities.</p>	
<p>8.2.2. Individual protection measures, e.g. personal protective equipment A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.</p>	
Respiratory protection	<p>Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.</p>
Thermal hazards	<p>None in addition to the above sections</p>
Eye / Face	<p>Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications</p>
Hands	<p>Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk.</p>


Safety Data Sheet – Uni-CA-892 Argon/C02 Mixture

Body	Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.	
8.2.3. Environmental exposure controls None necessary.		
9 PHYSICAL AND CHEMICAL PROPERTIES		
9.1 Physical Description/Properties		
Appearance	Physical state at 20 °C / 101.3kPa Colourless gas.	
Odour	Odour threshold is subjective and inadequate to warn of overexposure.	
Flammability	Non-flammable.	
Boiling Point = -186 °C	Flash Point = Not applicable for gases and gas mixtures.	
Melting Point = -189 °C	Auto Ignition Temperature = Non-flammable.	
Evaporation Rate: Not applicable	pH: Not applicable	
Specific Gravity Liquid = 1.38 (water = 1)	Relative Vapour Density = Not applicable.	
Solubility (water): 67.3 mg/l	Partition coefficient: Not applicable	
Vapour Pressure (at 40°C) Not applicable	Vapour Pressure (at 20°C) Not applicable	
Decomposition temperature: Not available	Viscosity: Not available	
Oxidising properties: Not available	Molar mass = 40 g/mol	
9.2 Other Information		
Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.		
10 STABILITY AND REACTIVITY		
10.1 Reactivity		
No reactivity hazard other than the effects described in sub-sections below.		
10.2 Chemical stability		
Stable under normal conditions.		
10.3 Possibility of hazardous reactions		
None.		

Safety Data Sheet – Uni-CA-892 Argon/CO2 Mixture

10.4 Conditions to avoid	
Avoid moisture in installation systems.	
10.5 Incompatible materials	
None. For additional information on compatibility refer to ISO 11114.	
10.6 Hazardous decomposition products	
None.	
11 TOXICOLOGICAL INFORMATION	
11.1 Information on toxicological effects	
Acute toxicity	No known toxicological effects form this product.
Skin	No known toxicological effects form this product.
Eyes	No known toxicological effects form this product.
Sensitisation	No known toxicological effects form this product.
Mutagenicity	No known toxicological effects form this product.
Carcinogenicity	No known toxicological effects form this product.
Reproductive	No known toxicological effects form this product.
STOT - single exposure	No known toxicological effects form this product.
Aspiration	Not applicable for gases and gas mixtures.
12 ECOLOGICAL INFORMATION	
12.1 Toxicity	
No ecological damage caused by this product.	
12.2 Persistence and degradability	
No ecological damage caused by this product.	
12.3 Bio-accumulative potential	
No information provided.	

Safety Data Sheet – Uni-CA-892 Argon/C02 Mixture

12.4 Mobility in soil	
Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.	
12.5. Results of PBT and vPvB assessment	
No data available.	
12.5 Other adverse effects	
No known effects from this product.	
13 DISPOSAL CONSIDERATIONS	
13.1 Waste treatment methods	
Waste disposal	May be vented to atmosphere in a well ventilated place. Do not discharge into any place where its accumulation could be dangerous. Return unused product in original cylinder to supplier.
Legislation	16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.
13.2. Additional information	
External treatment and disposal of waste should comply with applicable local and/or national regulations	
14 TRANSPORT INFORMATION	
14.1. UN number	1006
14.2. UN proper shipping name	
Transport by road/rail (ADG) :	ARGON, COMPRESSED
Transport by air (ICAO-TI / IATA-DGR) :	Argon, compressed
Transport by sea (IMDG) :	ARGON, COMPRESSED
14.3. Transport hazard class(es)	
Labelling	
	2.2 : Non-flammable, non-toxic gases
Transport by road/rail (ADG)	
Class : 2	

Safety Data Sheet – Uni-CA-892 Argon/CO2 Mixture

Hazchem code : 2T Hazard identification number : 20 Tunnel Restriction : E - Passage forbidden through tunnels of category E	
Transport by air (ICAO-TI / IATA-DGR) Class / Div. (Sub. risk(s)) : 2.2 Transport by sea (IMDG) Class / Div. (Sub. risk(s)) : 2.2 Emergency Schedule (EmS) - Fire : F-C Emergency Schedule (EmS) - Spillage : S-V	
14.4. Packing group Transport by road/rail (ADR/RID) : Not applicable Transport by air (ICAO-TI / IATA-DGR) : Not applicable Transport by sea (IMDG) : Not applicable	
14.5 Environmental hazards Transport by road/rail (ADR/RID) : None. Transport by air (ICAO-TI / IATA-DGR) : None. Transport by sea (IMDG) : None.	
14.6 Special precautions for user	
Hazchem Code	2T.
Packing Instruction(s)	Transport by road/rail (ADR/RID) : P200 Transport by air (ICAO-TI / IATA-DGR) Passenger and Cargo Aircraft : 200 Cargo Aircraft only : 200 Transport by sea (IMDG) : P200
Special transport precautions	Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.	
15 REGULATORY INFORMATION	
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	

Safety Data Sheet – Uni-CA-892 Argon/CO2 Mixture

National regulations

Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

16 OTHER INFORMATION

Indication of changes

Revised safety data sheet in accordance with commission regulation (EU) No 453/2010

Abbreviations and acronyms

Compressed Argon is supplied in high pressure cylinders.

Cylinder Colour: AS 4484-2004 Peacock Blue PMS 5473C / Green Grey PMS 415C

Cylinder Valve Outlet: AS 2473 Type 10

Safety Data Sheet – Uni-CA-892 Argon/C02 Mixture

ATE - Acute Toxicity Estimate. CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008. REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. EINECS - European Inventory of Existing Commercial Chemical Substances. CAS# - Chemical Abstract Service number. PPE - Personal Protection Equipment. LC50 - Lethal Concentration to 50 % of a test population. RMM - Risk Management Measures. PBT - Persistent, Bioaccumulative and Toxic. vPvB - Very Persistent and Very Bioaccumulative. STOT- SE : Specific Target Organ Toxicity - Single Exposure. CSA - Chemical Safety Assessment. EN - European Standard. UN - United Nations. ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road.
IATA - International Air Transport Association. IMDG code - International Maritime Dangerous Goods. RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.
WGK - Water Hazard Class. STOT - RE : Specific Target Organ Toxicity - Repeated Exposure.

Training advice

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Full text of H-statements

Press. Gas (Comp.)	Gases under pressure : Compressed gas
H280	Contains gas under pressure; may explode if heated.

DISCLAIMER OF LIABILITY

Before using this product in any new process or experiment, a thorough material compatibility

and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Safety Data Sheet Receipt Form

**I hereby acknowledge that I have been provided with a copy of the
AGas National Pty Ltd, Safety Data Sheet for Argon**

Issue 1 dated March 2018.

To be returned to Agas National Pty Ltd. at

Safety Data Sheet – Uni-CA-892 Argon/CO2 Mixture

7 Monigold Place, Dinmore, Qld, 4303

Name	
Title	
Company	
Signed	Dated