







Safety Data Sheet (SDS)

Oxygen Uni-O-100

1 PRODUCT AND COMPANY DETAILS		
1.1 Product Identifier		
Product Name	Uni-0-100	
Proper Shipping Name	OXYGEN	
Chemical Formula	02	
1.2 Recommended use and re	estrictions on use	
Use(s)	Industrial and professional. Perform risk assessment prior to use. Test gas/Calibration gas. Welding, cutting, heating and brazing. Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Water treatment. Laser gas. Laboratory use. Food applications. Contact supplier for more information on uses.	
Restrictions	Consumer use.	
1.3 Supplier details	1	
Supply Company	Agas National PTY Ltd. PO Box 6063 Riverview Qld 4303	
General Enquiries	TEL (07) 3282 5783	

Technical Enquiries Specific to product	Agasnational.com.au
	07 32825783

Emergency Telephone 0449252427 all hours

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to WHS Regulation

Physical hazards Oxidising Gases, Category 1 H270 Gases under pressure: Compressed gas H280

Danger

2.2 Label Elements

Signal word

Jigilat Word	
Pictogram	GHS03 GHS04
Hazard statement(s)	H270 - May cause or intensify fire; oxidiser. H280 - Contains gas under pressure; may explode if heated.
Prevention Statement(s)	P220 - Keep away from combustible materials. P244 - Keep valves and fittings free from oil and grease
Response Statement(s)	P370+P376 - In case of fire: stop leak if safe to do so
Storage statement	P403 - Store in a well-ventilated place.
Disposal Statement	None allocated

2.3 Other Hazards

None

3 COMPOSITION AND INFORMATION ON INGREDIENTS

3.1 Substances

Name	Product Identifier	%	Classification according to WHS Regulation
Oxygen	(CAS-No.) 7782-44-7 (EC-No.) 231-956-9 (EC Index-No.) 008-001- 00-8 (Registration-No.) *1	100	Ox. Gas 1, H270 Press. Gas (Comp.), H280

Contains no other components or impurities which will influence the classification of the product.

- *1: Listed in Annex IV / V REACH, exempted from registration.
- *2: Registration deadline not expired.
- *3: Registration not required: Substance manufactured or imported < 1t/y. Full text of R-phrases see section 16. Full text of H-statements see section 16.

3.2 Mixtures

Not applicable

4 FIRST AID

4.1 Description of first aid measures

Eye	Adverse effects not expected from this product.
Inhalation	Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped. Remove victim to uncontaminated area.
Skin	Adverse effects not expected from this product.
Ingestion	Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed

Continuous inhalation of concentrations higher than 75% may cause nausea, dizziness, respiratory difficulty and convulsion.

Refer to section 11.

4.3 Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

5 FIRE FIGHTING MEASURES

5.1 Extinguishing media

- Suitable extinguishing media - Unsuitable extinguishing media		Water spray or fog. Do not use water jet to extinguish.
5.2 Special hazards arising	from t	he substance or mixture
Specific hazards Hazardous combustion produ	ıcts	Exposure to fire may cause containers to rupture/explode. Supports combustion. None.
5.3 Advice for fire-fighters		
Specific methods	cause recep positi enter If pos Use v possib Move	unding fire. Exposure to fire and heat radiation may gas receptacles to rupture. Cool endangered tacles with water spray jet from a protected on. Prevent water used in emergency cases from ing sewers and drainage systems. sible, stop flow of product. water spray or fog to knock down fire fumes if
Special protective equipment for fire fighters	Stand	ard protective clothing and equipment (Self ined Breathing Apparatus) for fire fighters. ard EN 469 - Protective clothing for firefighters. ard - EN 659: Protective gloves for firefighters.

5.4 Hazchem code

2S

6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Try to stop release.

Evacuate area.

Consider the risk of potentially explosive atmospheres.

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

Eliminate ignition sources.

Ensure adequate air ventilation.

Act in accordance with local emergency plan.

Stay upwind.

6.2 Environmental precautions

Try to stop release.

6.3 Methods and material for containment and cleaning up

Ventilate area.

6.4 Reference to other sections

See sections 8 and 13 for exposure controls and disposal.

7 HANDLING AND STORAGE

7.1 Precautions for safe handling

7.1.1 Safe use of the product

The product must be handled in accordance with good industrial hygiene and safety procedures.

Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations.

Ensure the complete gas system was (or is regularly) checked for leaks before use.

Do not smoke while handling product.

Keep equipment free from oil and grease.

Use no oil or grease.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.

Use only oxygen approved lubricants and oxygen approved seals.

Use only with equipment cleaned for oxygen service and rated for cylinder pressure.

Avoid suck back of water, acid and alkalis.

Do not breathe gas.

7.1.2 Safe handling of the gas receptacle

Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Protect cylinders from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating cylinder valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

7.2 Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from falling over.

Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place.

Segregate from flammable gases and other flammable materials in store.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

7.3 Specific end use(s)

No information provided.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1 Control parameters

OEL (Occupational Exposure Limits):

No data available.

No data available.

PNEC (Predicted No-Effect Concentration):

No data available.

8.2 Exposure Controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Systems under pressure should be regularly checked for leakages.

Avoid oxygen rich (>23,5%) atmospheres.

Gas detectors should be used when oxidising gases may be released.

Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

Respiratory protection	None necessary.
Thermal hazards	None in addition to below.
Eye / Face	Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications
Hands	Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk.
Body	Consider the use of flame resistant safety clothing. Standard EN ISO 14116 - Limited flame spread materials. Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Description/Properties

Appearance	Physical state at 20°C / 101.3kPa Colourless gas.	
Odour	No odour warning properties.	
Flammability	Non flammable	
Boiling Point = -183 °C		Flash Point = Not applicable for gases and gas mixtures.
Melting Point = -219 °C		Auto Ignition Temperature Non flammable
Critical Temperature -118 °C		pH: Not applicable
Specific Gravity Liquid		Relative Vapour Density = 0.9.
Solubility (water): 1185 mg/l		Partition coefficient: 0.37
Vapour Pressure (at 50°C) Not applicable		Vapour Pressure (at 20°C) Not applicable
Decomposition temperature Not applicable		Viscosity: Not available
Oxidising properties: O	xidiser - Coefficient o	of oxygen equivalency (Ci): 1
Explosive properties: Not applicable		Molar mass = 32 g/mol
D	. 14 . 51 14	

Partition coefficient n-octanol/water [log Kow]: Not applicable for inorganic gases.

9.2 Other Information

None

10 STABILITY AND REACTIVITY

10.1 Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Violently oxidises organic material.

10.4 Conditions to avoid

Avoid moisture in installation systems.

10.5 Incompatible materials

May react violently with combustible materials.

May react violently with reducing agents.

Keep equipment free from oil and grease.

Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers in high pressure (> 30 bar) oxygen lines in case of combustion. For additional information on compatibility refer to ISO 11114.

10.6 Hazardous decomposition products

None

11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity	Classification criteria are not met. Acetylene has low inhalation toxicity, the LOAEC for mild intoxication in humans with no residual effects is 100 000ppm (107,000 mg/m3). There are no data on oral and dermal toxicity (studies are not technically feasible as the substance is a gas at room temperature.)
Skin corrosion/irritation	No known toxicological effects form this product.
Serious eye damage/irritation	No known toxicological effects form this product.
Respiratory or skin sensitisation	No known toxicological effects form this product.
Germ cell mutagenicity	No known toxicological effects form this product.
Carcinogenicity	No known toxicological effects form this product.
Toxic for reproduction : Fertility	No known toxicological effects form this product.
Toxic for reproduction: unborn child	No known toxicological effects form this product.
STOT - single exposure	No known toxicological effects form this product.
STOT - repeated exposure	No known toxicological effects form this product.

Aspiration hazard	Not applicable for gases and gas mixtures.
12 ECOLOGICAL INF	FORMATION
12.1 Toxicity	
No ecological dama	ge caused by this product.
12.2 Persistence ar	nd degradability
No ecological dama	ge caused by this product.
12.3 Bio-accumulat	tive potential
No data available.	
12.4 Mobility in soi	l
Because of its high valuation. Partition	volatility, the product is unlikely to cause ground or water into soil is unlikely.
12.5. Results of PB	T and vPvB assessment
No data available.	
12.5 Other adverse	e effects
Effect on the ozone Effect on global war	•
13 DISPOSAL CONSI	DERATIONS
13.1 Waste treatme	ent methods
Waste disposal	Contact supplier if guidance is required. May be vented to atmosphere in a well ventilated place. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.org for more guidance on

13.2. Additional information

Legislation

External treatment and disposal of waste should comply with applicable local and/or national regulations.

containing dangerous substances.

Return unused product in original cylinder to supplier.

16 05 04 *: Gases in pressure containers (including halons)

suitable disposal methods.

14 TRANSPORT INFORMATION

14.1. UN number 1072

14.2. UN proper shipping name

Transport by road/rail (ADG):

OXYGEN, COMPRESSED
OXYGEN, COMPRESSED
OXYGEN, COMPRESSED
OXYGEN, COMPRESSED
OXYGEN, COMPRESSED

14.3. Transport hazard class(es)

Labelling



2.2 : Non-flammable, non-toxic gases

5.1: Oxidizing substances

Transport by road/rail (ADG)

Class: 2

Hazchem code: 2S

Hazard identification number: 25

Tunnel Restriction: E - Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)): 2.2(5.1)

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2(5.1) Emergency Schedule (EmS) - Fire : F-C Emergency Schedule (EmS) - Spillage : S-W

14.4. Packing group

Transport by road/rail (ADR/RID):

Transport by air (ICAO-TI / IATA-DGR):

Not applicable

Not applicable

Not applicable

14.5 Environmental hazards

Transport by road/rail (ADR/RID): None.
Transport by air (ICAO-TI / IATA-DGR): None.
Transport by sea (IMDG): None.

14.6 Special precautions for user

Hazchem Code	2S.
--------------	------------

	Transport by rodd/rait (Abit/itib):	1 200
	Transport by air (ICAO-TI / IATA-DGR)	
Packing Instruction(s)	Passenger and Cargo Aircraft:	200
- , ,	Cargo Aircraft only:	200
	Transport by sea (IMDG):	P200

Transport by road/rail (ADR/RID)

P200

Special transport precautions	Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation Ensure that containers are firmly secured Ensure cylinder valve is closed and not leaking Ensure valve outlet cap nut or plug (where provided) is correctly fitted Ensure valve protection device (where provided) is correctly fitted.
-------------------------------	---

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

16 OTHER INFORMATION

Indication of changes

Revised safety data sheet in accordance with commission regulation (EU) No 453/2010

Abbreviations and acronyms

ATE - Acute Toxicity Estimate. CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008. REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. EINECS - European Inventory of Existing Commercial Chemical Substances. CAS# - Chemical Abstract Service number. PPE - Personal Protection Equipment. LC50 - Lethal Concentration to 50 % of a test population. RMM - Risk Management Measures. PBT - Persistent, Bioaccumulative and Toxic. vPvB - Very Persistent and Very Bioaccumulative. STOT- SE: Specific Target Organ Toxicity - Single Exposure. CSA - Chemical Safety Assessment. EN - European Standard. UN - United Nations. ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road.

IATA - International Air Transport Association. IMDG code - International Maritime Dangerous Goods. RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.

WGK - Water Hazard Class. STOT - RE: Specific Target Organ Toxicity - Repeated Exposure.

Training advice

Ensure operators understand the hazard of oxygen enrichment.

Full text of H-statements

Ox. Gas 1	Oxidising Gases, Category 1		
Press. Gas (Comp.)	Gases under pressure : Compressed gas		
H270	May cause or intensify fire; oxidiser.		
H280	Contains gas under pressure; may explode if heated.		

DISCLAIMER OF LIABILITY

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

		_		
Catati		Chast	Receipt	Earm
SAIPIV	11212	311661	RACHIN	

I hereby acknowledge that I have been provided with a copy of the AGas National Pty Ltd, Safety Data Sheet for Oxygen

Issue 1 dated March 2018.

To be returned to Agas National Pty Ltd. at

7 Monigold Place, Dinmore, Qld, 4303

Name		
Title		
Company		
Signed	Dated	