

LISTINO 2025

Febbraio 2025





SC 125 LX Nero – Grigio - Bianco



2.790 € f.c.



Scan to access media files and press releases in English, Spanish and Italian.



Model	Model Name	SC125LX
Information	Category	Scooter
	Displacement (cm³)	125
Engine	Туре	1-cylinder / 4-stroke / 2-valve / SOHC
	Bore x stroke (mm)	52.4×57.8
	Max.power (Hp/rpm)	11.13/8500
	Max.torque (N·m/rpm)	11.2/6500
	Cooling system	Lateral-mounted-liquid-cooled
Transmission	Clutch / Gear / Transmission	Automatic, CVT, V-Belt
Chassis	Front suspension	Telescopic forks
	Front suspension travel (mm)	90
	Rear suspension	Dual shock-absorber, 5-stage adjustable preload
	Rear suspension travel (mm)	76
	Front Brake	Disc, 2-piston caliper
	Front brake Disc(s) diameter (mm)	260
	Rear Brake	Disc, 1-piston caliper
	Rear brake Disc(s) diameter (mm)	240
	Wheels Type	Aluminum allov
	Front tyre	100/80-16, CST
	Rear tyre	120/70-14, CST
	Rear swing arm type	
Active/Passive	CBS	
safety features	ABS	Yes
	ABS off function	
	Cornering anti-lock braking system (ABS PR	RO) -
	Tire pressure monitoring system (TPMS)	
	Traction control system (TCS)	Yes
Assistive/Control	Ride Modes selection	
configurations	Throttle configuration	Single cable throttle control
	Cruise control system (CCS)	_
Multimedia &	Dashboard type	LCD
comfort features		Yes
	Keyless start system	Yes
	Heated grips	
	Heated seat	
	Handle switch with illumination	
	Connect (GPS; APP) / Navigation	
	Automatic lighting system	
Dimension and	Seat height (mm)	800
Weights	Fuel capacity (L)	9.5
	Curb Weight (kg)	
	Max. loadage (kg)	180
	Maximum speed (km/h)	95
	Maximum-speed (kill/11)	93





(eewa) GROU



SC 125 RE

Grigio - Bianco



2.890 € f.c.




Scan to access media files and press releases in English, Spanish, and Italian.



Model	Model Name	SC125RE
Information	Category	Scooter
	Displacement (cm³)	125
Engine	Туре	1-cylinder / 4-stroke / 2-valve / SOHC
	Bore x stroke (mm)	52.4×57.8
	Max.power (Hp/rpm)	11.0/7500
	Max.torque (N·m/rpm)	11.2/5500
	Cooling system	Lateral-mounted-liquid-cooled
Transmission	Clutch / Gear / Transmission	Automatic, CVT, V-Belt
Chassis	Front suspension	Telescopic forks
	Front suspension travel (mm)	85
	Rear suspension	Shock-absorber,5-stage adjustable preload
	Rear suspension travel (mm)	88
	Front Brake	Disc, 2-piston caliper
	Front brake Disc(s) diameter (mm)	200
	Rear Brake	Disc, 1-piston caliper
	Rear brake Disc(s) diameter (mm)	190
	Wheels Type	Aluminum alloy
	Front tyre	120/70-12, CST
	Rear tyre	120/70-12, CST
	Rear swing arm type	
Active/Passive	CBS	
safety features	ABS	Yes
	ABS off function	
	Cornering anti-lock braking system (ABS PRO)	
	Tire pressure monitoring system (TPMS)	
	Traction control system (TCS)	
Assistive/Control	Ride Modes selection	
configurations	Throttle configuration	Single cable throttle control
	Cruise control system (CCS)	-
Multimedia &	Dashboard type	LCD
comfort features	USB charging port	Yes
	Keyless start system	Yes
	Heated grips	
	Heated seat	
	Handle switch with illumination	
	Connect (GPS; APP) / Navigation	
	Automatic lighting system	-
Dimension and	Seat height (mm)	785
Weights	Fuel capacity (L)	7
	Curb Weight (kg)	139
	Max. loadage (kg)	151
	Maximum speed (km/h)	92





Keeway GROUP



SC 125 Nero - Bianco



2.990 € f.c.




Scan to access media files and press releases in English, Spanish and Italian.



Model	Model Name	SC125
Information	Category	Scooter
	Displacement (cm³)	124.9
Engine	Туре	1-cylinder / 4-stroke / 2-valve / SOHC
	Bore x stroke (mm)	52.4×57.9
	Max.power (Hp/rpm)	10.46/8250
	Max.torque (N·m/rpm)	10.0/6350
	Cooling system	11.0:1
Transmission	Clutch / Gear / Transmission	Automatic, CVT, V-Belt
Chassis	Front suspension	Telescopic forks
	Front suspension travel (mm)	90
	Rear suspension	Dual shock-absorber, 5-stage adjustable preload
	Rear suspension travel (mm)	70
	Front Brake	Disc, 2-piston caliper
	Front brake Disc(s) diameter (mm)	240
	Rear Brake	Disc, 2-piston caliper
	Rear brake Disc(s) diameter (mm)	220
	Wheels Type	Aluminum alloy
	Front tyre	110/70-13
	Rear tyre	130/70-13
	Rear swing arm type	
Active/Passive	CBS	
safety features	ABS	Yes
	ABS off function	
	Cornering anti-lock braking system (ABS PRO	
	Tire pressure monitoring system (TPMS)	
	Traction control system (TCS)	
Assistive/Control	Ride Modes selection	
configurations	Throttle configuration	Dual cable throttle control
	Cruise control system (CCS)	
Multimedia &	Dashboard type	LCD
comfort features	USB charging port	Yes
	Keyless start system	Yes
	Heated grips	
	Heated seat	
	Handle switch with illumination	Yes
	Connect (GPS; APP) / Navigation	
	Automatic lighting system	
Dimension and	Seat height (mm)	790
Weights	Fuel capacity (L)	11.5
	Curb Weight (kg)	148
	Max. loadage (kg)	160
	Maximum speed (km/h)	90





Seeway GROUF



SC 300 Nero – Bianco - Grigio



3.990 € f.c.




Scan to access media files and press releases in English, Spanish and Italian.



Model	Model Name	SC300
Information	Category	Scooter
	Displacement (cm³)	278
Engine	Туре	1-cylinder / 4-stroke / 4-valve / SOHC
	Bore x stroke (mm)	75×63
	Max.power (Hp/rpm)	24.27/8000
	Max.torque (N·m/rpm)	25.0/5750
	Cooling system	Liquid-cooled
Transmission	Clutch / Gear / Transmission	Automatic, CVT, V-Belt
Chassis	Front suspension	Telescopic forks, KYB
	Front suspension travel (mm)	90
	Rear suspension	Dual shock-absorber, 7-stage adjustable preload, KYB
	Rear suspension travel (mm)	65
	Front Brake	Disc, 4-piston caliper, J.Juan
	Front brake Disc(s) diameter (mm)	240
	Rear Brake	Disc, 2-piston caliper, J. Juan
	Rear brake Disc(s) diameter (mm)	220
	Wheels Type	Aluminum alloy
	Front tyre	110/70-13
	Rear tyre	130/70-13
	Rear swing arm type	
Active/Passive	CBS	
safety features	ABS	Yes
	ABS off function	
	Cornering anti-lock braking system (ABS	PRO) -
	Tire pressure monitoring system (TPMS)	Yes
	Traction control system (TCS)	Yes
Assistive/Control	Ride Modes selection	
configurations	Throttle configuration	Dual cable throttle control
	Cruise control system (CCS)	
Multimedia &	Dashboard type	TFT, 5 inch
comfort features	USB charging port	Yes
	Keyless start system	Yes
	Heated grips	Yes
	Heated seat	
	Handle switch with illumination	Yes
	Connect (GPS; APP) / Navigation	
	Automatic lighting system	
Dimension and	Seat height (mm)	790
Weights	Fuel capacity (L)	11.5
	Curb Weight (kg)	164
	Max. loadage (kg)	160
	Maximum speed (km/h)	120





GROUP



F 125 Nero – Bianco - Rosso





2.790 € f.c.



Scan to access media files and press releases in English, Spanisl and Italian.



Model	Model Name	F125
Information	Category	Street Fighter
	Displacement (cm³)	125
Engine	Туре	1-cylinder / 4-stroke / 4-valve / DOHC
	Bore x stroke (mm)	54×54.5
	Max.power (Hp/rpm)	14.48/9500
	Max.torque (N·m/rpm)	11.5/8000
	Cooling system	Liquid-cooled
Transmission	Clutch / Gear / Transmission	Slipper clutch, 6-speed, Chain
Chassis	Front suspension	33mm upside-down telescopic forks
	Front suspension travel (mm)	130
	Rear suspension	Multi-link shock-absorber, preload adjustable
	Rear suspension travel (mm)	30
	Front Brake	Floating disc, 2-piston caliper
	Front brake Disc(s) diameter (mm)	260
	Rear Brake	Disc, 1-piston caliper
	Rear brake Disc(s) diameter (mm)	220
	Wheels Type	Aluminum alloy
	Front tyre	100/80-17, CST
	Rear tyre	130/70-17, CST
	Rear swing arm type	Steel double-sided swingarm
Active/Passive	CBS	
safety features	ABS	Yes
	ABS off function	
	Cornering anti-lock braking system (ABS PRO)	
	Tire pressure monitoring system (TPMS)	-
	Traction control system (TCS)	-
Assistive/Control	Ride Modes selection	
configurations	Throttle configuration	Dual cable throttle control
	Cruise control system (CCS)	
Multimedia &	Dashboard type	LCD
comfort features	USB charging port	Yes
	Keyless start system	-
	Heated grips	-
	Heated seat	
	Handle switch with illumination	
	Connect (GPS; APP) / Navigation	
	Automatic lighting system	-
Dimension and	Seat height (mm)	795
Weights	Fuel capacity (L)	14
	Curb Weight (kg)	143
	Max. loadage (kg)	150
	Maximum speed (km/h)	102





GROUF



M 502 N Nero – Bianco



5.990 € f.c.




Scan to access media files and press releases in English, Spanish, and Italian.



Model Name	M502N
Category	Naked
Displacement (cm³)	486
Туре	2-cylinder inline / 4-stroke / 8-valve / DOHC
Bore x stroke (mm)	68×67
Max.power (Hp/rpm)	46.94/8500
Max.torque (N·m/rpm)	45.0/6750
Cooling system	Liquid-cooled
Clutch / Gear / Transmission	Wet multi-plate, 6-speed, Chain
Front suspension	41mm upside-down telescopic forks, KYB
Front suspension travel (mm)	119.5
Rear suspension	Multi-link shock-absorber, preload adjustable, KYB
Rear suspension travel (mm)	55
Front Brake	Double floating discs, 2-piston caliper, J.Juan
Front brake Disc(s) diameter (mm)	300
Rear Brake	Disc, 1-piston caliper, J.Juan
Rear brake Disc(s) diameter (mm)	240
Wheels Type	Aluminum alloy
Front tyre	120/70ZR17, PIRELLI
	160/60ZR17, PIRELLI
Rear swing arm type	Aluminium double-sided swingarm
CBS	_
ABS	Yes, Bosch
ABS off function	
Cornering anti-lock braking system (ABS PR	RO) -
	Yes
Traction control system (TCS)	
Throttle configuration	Dual cable throttle control
	TFT, 5 inch
	Yes
	Yes
	Yes
	790
	17
	208
	185
3 1 3	160
	Displacement (cm³) Type Bore x stroke (mm) Max.power (Hp/rpm) Max.torque (N·m/rpm) Cooling system Clutch / Gear / Transmission Front suspension Front suspension travel (mm) Rear suspension Rear suspension travel (mm) Front Brake Front brake Disc(s) diameter (mm) Rear Brake Rear brake Disc(s) diameter (mm) Wheels Type Front tyre Rear tyre Rear swing arm type CBS ABS ABS off function Cornering anti-lock braking system (ABS Plating Time pressure monitoring system (TPMS)





(eewa) GROUE



C1002 V Nero – Argento





10390 € f.c.




Scan to access media files and press releases in English, Spanish and Italian.



Model	Model Name	C1002V
Information	Category	Cruiser
	Displacement (cm³)	997
Engine	Туре	V-2-cylinder / 4-stroke / 8-valve / SOHC
	Bore x stroke (mm)	92×75
	Max.power (Hp/rpm)	87.17/7200
	Max.torque (N·m/rpm)	89.0/5250
	Cooling system	Liquid-cooled
Transmission	Clutch / Gear / Transmission	Wet multi-plate, 6-speed, Belt
Chassis	Front suspension	43mm upside-down telescopic forks, KYB
	Front suspension travel (mm)	137
	Rear suspension	Multi-link shock-absorber, preload adjustable, KYB
	Rear suspension travel (mm)	41.6
	Front Brake	Double floating discs, 2-piston caliper, J.Juan
	Front brake Disc(s) diameter (mm)	320
	Rear Brake	Disc, 1-piston caliper, J.Juan
	Rear brake Disc(s) diameter (mm)	300
	Wheels Type	Aluminum alloy
	Front tyre	130/70R18, METZELER
	Rear tyre	240/40VR18, METZELER
	Rear swing arm type	Aluminium double-sided swingarm
Active/Passive	CBS	
safety features	ABS	Yes, Bosch
	ABS off function	
	Cornering anti-lock braking system (ABS F	PRO) -
	Tire pressure monitoring system (TPMS)	Yes
	Traction control system (TCS)	
Assistive/Control	Ride Modes selection	Yes
configurations	Throttle configuration	Electronic throttle control (ETC), Ride by wire
	Cruise control system (CCS)	
Multimedia &	Dashboard type	TFT, 5 inch
comfort features	USB charging port	Yes
	Keyless start system	
	Heated grips	
	Heated seat	
	Handle switch with illumination	
	Connect (GPS; APP) / Navigation	
	Automatic lighting system	Yes
Dimension and	Seat height (mm)	680
Weights	Fuel capacity (L)	22
	Curb Weight (kg)	282
	Max. loadage (kg)	180
	Maximum speed (km/h)	198
	Maximani Speed (kill) II)	190





GROUF



T1002 VX Nero – Bianco





9.990 € f.c.




Scan to access media files and press releases in English, Spanish and Italian.



Model	Model Name	T1002VX
Information	Category	Trail
	Displacement (cm³)	997
Engine	Туре	V-2-cylinder / 4-stroke / 8-valve / SOHC
	Bore x stroke (mm)	92×75
	Max.power (Hp/rpm)	88.51/7750
	Max.torque (N·m/rpm)	95.0/5000
	Cooling system	Liquid-cooled
Transmission	Clutch / Gear / Transmission	Slipper clutch, 6-speed, Chain
Chassis		telescopic forks, restore damping adjustable, KYB
	Front suspension travel (mm)	183.8
	Rear suspension Multi-link shock absorber, pre	eload adjustable, Restore damping adjustable, KYB
	Rear suspension travel (mm)	77.4
	Front Brake	Double floating discs, 4-piston caliper, J.Juan
	Front brake Disc(s) diameter (mm)	320
	Rear Brake	Disc, 1-piston caliper, J.Juan
	Rear brake Disc(s) diameter (mm)	260
	Wheels Type	Spokes Tubeless
	Front tyre	120/70-19
	Rear tyre	170/60-17
	Rear swing arm type	Aluminium double-sided swingarm
Active/Passive	CBS	-
safety features	ABS	Yes, Bosch
	ABS off function	Yes
	Cornering anti-lock braking system (ABS PRO	
	Tire pressure monitoring system (TPMS)	Yes
	Traction control system (TCS)	Yes
Assistive/Control	Ride Modes selection	Yes
configurations	Throttle configuration	Electronic throttle control (ETC), Ride by wire
3	Cruise control system (CCS)	-
Multimedia &	Dashboard type	TFT, 7 inch
comfort features		Yes
	Keyless start system	
	Heated grips	Yes
	Heated seat	Yes
	Handle switch with illumination	Yes
	Connect (GPS; APP) / Navigation	1-Year Data
	Automatic lighting system	
Dimension and	Seat height (mm)	820
Weights	Fuel capacity (L)	20
3	Curb Weight (kg)	265
	Max. loadage (kg)	190
	Maximum speed (km/h)	198
	mammam-spood (Mill) Hy	150





GROU



T125X Nero – Bianco





3.490 € f.c.




Scan to access media files and press releases in English, Spanish, and Italian.



Model Name	T125X
Category	Trail
Displacement (cm³)	124
Туре	1-cylinder / 4-stroke / 4-valve / DOHC
Bore x stroke (mm)	58×47
Max.power (Hp/rpm)	14.21/9500
Max.torque (N·m/rpm)	11.0/7600
Cooling system	Liquid-cooled
Clutch / Gear / Transmission	Wet multi-plate, 6-speed, Chain
Front suspension	41mm upside-down telescopic forks
Front suspension travel (mm)	177
Rear suspension	Shock-absorber, preload adjustable
Rear suspension travel (mm)	55
Front Brake	Disc, 2-piston caliper
Front brake Disc(s) diameter (mm)	265
Rear Brake	Disc, 2-piston caliper
Rear brake Disc(s) diameter (mm)	220
Wheels Type	Spokes
Front tyre	90/90-19
Rear tyre	110/90-17
Rear swing arm type	Steel double-sided swingarm
CBS	
ABS	Yes
ABS off function	
Cornering anti-lock braking system (ABS PRO)	
Tire pressure monitoring system (TPMS)	
Traction control system (TCS)	
Ride Modes selection	
Throttle configuration	Single cable throttle control
Cruise control system (CCS)	
Dashboard type	LCD
USB charging port	Yes
Heated grips	
Heated seat	
Handle switch with illumination	Yes
Connect (GPS; APP) / Navigation	
Automatic lighting system	Yes
Seat height (mm)	820
	11.7
	148
Max. loadage (kg)	105
	Category Displacement (cm³) Type Bore x stroke (mm) Max.power (Hp/rpm) Max.torque (N·m/rpm) Cooling system Clutch / Gear / Transmission Front suspension Front suspension travel (mm) Rear suspension travel (mm) Front Brake Front brake Disc(s) diameter (mm) Rear Brake Rear brake Disc(s) diameter (mm) Wheels Type Front tyre Rear swing arm type CBS ABS ABS ABS ABS of function Cornering anti-lock braking system (ABS PRO) Tire pressure monitoring system (TPMS) Traction control system (TCS) Ride Modes selection Throttle configuration Cruise control system (CCS) Dashboard type USB charging port Keyless start system Heated grips Heated seat Handle switch with illumination Connect (GFS; APP) / Navigation Automatic lighting system Seat height (mm) Fuel capacity (L) Curb Weight (kg)





GROUF



Prezzo da confermare




Scan to access media files and press releases in English, Spanish, and Italian.



m) m) rpm) /rpm) Transmission i travel (mm) travel (mm) (s) diameter (mm)	Street Fighter 349.2 2-cylinder inline / 4-stroke / 8-valve / DOHC 71.0×44.1 40.9/10500 31.5/8500 Liquid-cooled Slipper clutch, 6-speed, Chain 41mm upside-down telescopic forks 120 Multi-link shock-absorber, preload adjustable 52 Double floating discs, 4-piston caliper 300 Disc, 1-piston caliper 240 Aluminum alloy
m) rpm) //rpm) Transmission o travel (mm) travel (mm)	2-cylinder inline / 4-stroke / 8-valve / DOHC 71.0x44.1 40.9/10500 31.5/8500 Liquid-cooled Slipper clutch, 6-speed, Chain 41mm upside-down telescopic forks 120 Multi-link shock-absorber, preload adjustable 52 Double floating discs, 4-piston caliper 300 Disc, 1-piston caliper 240
rpm) fransmission a travel (mm) travel (mm) (s) diameter (mm)	71.0×44.1 40.9/10500 31.5/8500 Liquid-cooled Slipper clutch, 6-speed, Chain 41mm upside-down telescopic forks 120 Multi-link shock-absorber, preload adjustable 52 Double floating discs, 4-piston calliper 300 Disc, 1-piston caliper
rpm) fransmission a travel (mm) travel (mm) (s) diameter (mm)	40.9/10500 31.5/8500 Liquid-cooled Slipper clutch, 6-speed, Chain 41mm upside-down telescopic forks 120 Multi-link shock-absorber, preload adjustable 52 Double floating discs, 4-piston caliper 300 Disc, 1-piston caliper
/rpm) fransmission i travel (mm) travel (mm) (s) diameter (mm)	31.5/8500 Liquid-cooled Slipper clutch, 6-speed, Chain 41mm upside-down telescopic forks 120 Multi-link shock-absorber, preload adjustable 52 Double floating discs, 4-piston caliper 300 Disc, 1-piston caliper
Transmission Itravel (mm) Travel (mm) (s) diameter (mm)	Liquid-cooled Slipper clutch, 6-speed, Chain 41mm upside-down telescopic forks 120 Multi-link shock-absorber, preload adjustable 52 Double floating discs, 4-piston caliper 300 Disc, 1-piston caliper 240
travel (mm) travel (mm) (s) diameter (mm)	Slipper clutch, 6-speed, Chain 41mm upside-down telescopic forks 120 Multi-link shock-absorber, preload adjustable 52 Double floating discs, 4-piston caliper 300 Disc, 1-piston caliper 240
travel (mm) travel (mm) (s) diameter (mm)	41mm upside-down telescopic forks 120 Multi-link shock-absorber, preload adjustable 52 Double floating discs, 4-piston caliper 300 Disc, 1-piston caliper 240
travel (mm) travel (mm) (s) diameter (mm)	120 Multi-link shock-absorber, preload adjustable 52 Double floating discs, 4-piston caliper 300 Disc, 1-piston caliper 240
travel (mm) (s) diameter (mm)	Multi-link shock-absorber, preload adjustable 52 Double floating discs, 4-piston caliper 300 Disc, 1-piston caliper 240
(s) diameter (mm)	52 Double floating discs, 4-piston caliper 300 Disc, 1-piston caliper 240
(s) diameter (mm)	Double floating discs, 4-piston caliper 300 Disc, 1-piston caliper 240
	300 Disc, 1-piston caliper 240
	Disc, 1-piston caliper 240
s) diameter (mm)	240
s) diameter (mm)	
	Aluminum alloy
	110/70-17, MAXXIS
	150/60-17, MAXXIS
уре	Steel double-sided swingarm
	Yes, Bosch
	Yes
ock braking system (ABS PRO)	-
nitoring system (TPMS)	-
system (TCS)	Yes
ction	Yes
ation	Dual cable throttle control
stem (CCS)	-
	TFT, 5 inch
rt	Yes
tem	-
th illumination	Yes
PP) / Navigation	4G, 1-Year Data
ig system	-
	790
)	15
	170
i A	ort stem ith illumination APP) / Navigation ng system n)





GROUF



T352X Nero – Bianco





Prezzo da confermare




Scan to access media files and press releases in English, Spanish and Italian.



Model	Model Name	T352X
Information	Category	Trail
	Displacement (cm³)	349.2
Engine	Туре	2-cylinder inline / 4-stroke / 8-valve / DOHC
	Bore x stroke (mm)	71.0×44.1
	Max.power (Hp/rpm)	40.9/10500
	Max.torque (N·m/rpm)	31.5/8500
	Cooling system	Liquid-cooled
Transmission	Clutch / Gear / Transmission	Slipper clutch, 6-speed, Chain
Chassis	Front suspension	41mm upside-down telescopic forks
	Front suspension travel (mm)	160
	Rear suspension	Multi-link shock absorber, preload adjustable
	Rear suspension travel (mm)	56
	Front Brake	Floating disc, 4-piston caliper
	Front brake Disc(s) diameter (mm)	300
	Rear Brake	Disc, 1-piston caliper
	Rear brake Disc(s) diameter (mm)	240
	Wheels Type	Spokes Tubeless
	Front tyre	110/80-19, PIRELLI
	Rear tyre	150/60-17, PIRELLI
	Rear swing arm type	Steel double-sided swingarm
Active/Passive	CBS	
safety features	ABS	Yes, Bosch
	ABS off function	Yes
	Cornering anti-lock braking system (ABS PRO)	
	Tire pressure monitoring system (TPMS)	Yes
	Traction control system (TCS)	Yes
Assistive/Control	Ride Modes selection	Yes
configurations	Throttle configuration	Dual cable throttle control
	Cruise control system (CCS)	
Multimedia &	Dashboard type	TFT, 7 inch
comfort features	USB charging port	Yes
	Keyless start system	
	Heated grips	
	Heated seat	
	Handle switch with illumination	Yes
	Connect (GPS; APP) / Navigation	1-Year Data / Navigation Mirroring system
	Automatic lighting system	
Dimension and	Seat height (mm)	820
Weights	Fuel capacity (L)	18
	Curb Weight (kg)	180
	Max. loadage (kg)	190
	Maximum speed (km/h)	140





(eewa) GROUF



T502X

Nero – Bianco - Azzuro chiaro





Prezzo da confermare




Scan to access media files and press releases in English, Spanish, and Italian.



Model	Model Name	T502X
Information	Category	Trail
	Displacement (cm³)	486
Engine	Туре	2-cylinder inline / 4-stroke / 8-valve / DOHC
	Bore x stroke (mm)	68×67
	Max.power (Hp/rpm)	46.94/8500
	Max.torque (N·m/rpm)	45.0/6750
	Cooling system	Liquid-cooled
Transmission	Clutch / Gear / Transmission	Slipper clutch, 6-speed, Chain
Chassis	Front suspension	43mm upside-down telescopic forks, preload adjustable
	Front suspension travel (mm)	180
	Rear suspension	Multi-link shock-absorber, preload adjustable
	Rear suspension travel (mm)	69
	Front Brake	Double floating discs, 2-piston caliper, J.Juan
	Front brake Disc(s) diameter (mm)	300
	Rear Brake	Disc, 1-piston caliper, J.Juan
	Rear brake Disc(s) diameter (mm)	240
	Wheels Type	Spokes Tubeless
	Front tyre	110/80-19, PIRELLI
	Rear tyre	150/70-17, PIRELLI
	Rear swing arm type	Aluminium double-sided swingarm
Active/Passive	CBS	
safety features	ABS	Yes, Bosch
	ABS off function	Yes, rear
	Cornering anti-lock braking system (AB	SS PRO) -
	Tire pressure monitoring system (TPM	S) Yes
	Traction control system (TCS)	
Assistive/Control	Ride Modes selection	Yes
configurations	Throttle configuration	Dual cable throttle control
	Cruise control system (CCS)	
Multimedia &	Dashboard type	TFT, 7 inch
comfort features		Yes
	Keyless start system	
	Heated grips	
	Heated seat	
	Handle switch with illumination	Yes
	Connect (GPS; APP) / Navigation	1-Year Data / Navigation Mirroring system
	Automatic lighting system	Yes
Dimension and	Seat height (mm)	830
Weights	Fuel capacity (L)	18
	Curb Weight (kg)	210
	Max. loadage (kg)	185
	Maximum speed (km/h)	160





GROUF