

| | |
|---|------------------------------|
| Basket capacity | 250 kg (2 op.) |
| Max working height | 7.8 m |
| Max height basket floor | 5.8 m |
| Moving height | 4.0 m |
| Lateral levelling for moving at heights | - |
| Powered (option) | - |
| Powered Standard | Petrol Honda iGX390 |
| Powered (option) Bi energy | - |
| Accelerator | Manual |
| Undercarriage | Retractable |
| Basket levelling | Automatic |
| Longitudinal levelling front | +/- 13° |
| Longitudinal levelling rear | Rear +/- 14° |
| Lateral levelling | +/- 23° |
| Power generator (option) | 220V-1kW (iGX390, 1B40) |
| Electric motor | 220V-2kW |
| Hydraulic commands | Proportionals |
| Direction-control system | Yes |
| Easy-drive system | No |
| Kit for high speed | Max 2.20 km/h |
| Ground emergency | Yes |
| Control of inclination | Automatic |
| Gradeability | 25° |
| Side slope | 21° |
| Length | 2.14 m |
| Width | 0.80 ÷ 1.24 m |
| Minimum machine height with folded railings | 1.88 m |
| Total weight | 1730 kg |
| Compliance | EN 280, ANSI, CSA, ASNZS1418 |



ATHENA HE

The ATHENA HE is so named due to its compact dimensions and reduced weight compared to the ATHENA 850. For those requiring confidence and stability on slopes and the ability to go through a single standard door, the ATHENA HE is the ideal machine on site.

- Automatic stabilisation outriggers
- Single door access
- Suitable for inclines up to 23 degrees
- Extremely light and compact
- Reduces unsafe work practices
- Track widening
- Suitable for indoors or outdoors



ATHENA HE

DIMENSIONS

