

| PART NUMBER | PACKAGING | |
|-----------------|-----------------------------------|--|
| ERTS8052A102B-B | BULK | |
| ERTS8052A102B-D | TAPE & REEL (SENSOR SIDE DOWN) | |
| | | |

| 0 | INITIAL RELEASE | 02/19/2020 | DD | |
|------------------|-----------------|------------|-----|--|
| REV | DESCRIPTION | DATE | APP | |
| REVISION HISTORY | | | | |

| EI SENSOR TECHNOLOGIES | RTD ELEMENT | | |
|----------------------------------|-----------------------|------------------|--|
| www.ei-sensor.com C COPYRIGHT | DRAWN BY: DAN DANKERT | | |
| | | LAYER: 0 OF 2 | |
| P/N ERTS8052A102B- | REV: 0 | DATE: 02/19/2020 | |

This PROPRIETARY document is the property of El Sensor Technologies. It is confidential in nature, non-transferrable and issued with the understanding that it is not to be traced or copied without permission, and is returnable on demand. RESISTANCE @ 0°C = 1,000 Ω ± 0.06%

ACCURACY @ 0°C = \pm 0.15°C

ACCURACY CLASS = IEC 60751 F 0.15

TCR = 3,850 ppm/°C

DISSIPATION CONSTANT = 4 mW/'C NOMINAL (AIR)

MAXIMUM APPLIED CURRENT = 0.3 mA

THERMAL TIME CONSTANT = 3 SECONDS NOMINAL (AIR @ 1m/SECOND)

TEMPERATURE RATING = $-50 \text{ TO } +250^{\circ}\text{C}$

ROHS COMPLIANT

PACKAGING: SEE TABLE