

FRAMER'S CHOICE



SYNTHETIC ROOFING UNDERLAYMENT

Whether you're stocking warehouses or supplying crews across multiple regions, we deliver the materials you rely on at the scale your business demands

SYNTHETIC ROOFING UNDERLAYMENT

Key Benefits

- Lightweight and easy to handle
- High tear strength and fastener pull-through resistance
- Water-resistant barrier against wind-driven rain
- Slip-resistant surface for improved worker safety
- UV-resistant for extended exposure before roofing installation

Product Specifications

- Material Composition: Polypropylene composite
- Basis Weight: 180 GSM
- Thickness: 8 mil
- Tear Strength: 25 lb/inch ASTM D4533
- Tensile Strength: 152 lb/inch ASTM D4533
- Water Resistance: >1,000cm = Water resistant
- Water Vapor Transmission: .6 perms
- UV Exposure Rating: 120 days
- Service Temperature Range: -40°F - 175°F
- Roll Dimensions: 48"x250'
- Coverage Area: 1,000 sq. ft. or 10 roofing square
- Applicable Standards (ASTM): D1970 - D4869 - D226 CSA-A1233.3-05
- Warranty: 20 years
- Custom Logo Available



Our Mission

To provide distributors and contractors with reliable, high-quality building materials at competitive bulk rates.

Backed by decades of construction industry experience, our team understands what it takes to keep projects moving forward - on time and on budget.