

## **TUFFLIFT – TLR4.0OH**

*FEATURES UP TOP NEAR PICS TABS BELOW TO BE*

*DESCRIPTION / SPECIFICATIONS / DOWNLOADS*

### **Features**

- 4.0 Ton lifting capacity
- Single lock release
- Designed for low ceiling clearance
- Asymmetric arms
- Available in single or three phase power
- 110mm concrete requirement

### **DESCRIPTION**

#### **2 Post Car Hoist | 4 Ton Clear Floor – TLR4.0OH**

#### **Includes:**

- Hydraulic oil
- Screw pads
- 4 piece pad adapter set
- Anchor bolts

#### **Options:**

- EV Charge Station

#### **Warranty**

- 5 years (structure) + 1 year electrical, mechanical, hydraulics. Parts & labour
- Certification
- Engineer Certified
- Design Registered with Worksafe

## Specifications

<b>Capacity:</b>	4000Kg
<b>Minimum Concrete Requirement:</b>	110mm
<b>Recommended Ceiling Height:</b>	3.7m
<b>Overall Height:</b>	3607mm
<b>Overall Floor Width (without motor):</b>	3334mm
<b>Max lift Height (with out adaptors):</b>	1822mm
<b>Max lift Height (with adaptors):</b>	1923mm
<b>Min Pad Height:</b>	95mm
<b>Width Between Columns:</b>	2764mm
<b>Drive Through:</b>	2506mm
<b>Column thickness of steel:</b>	5 Gauge (5.08mm)
<b>Power:</b>	240v: 2.2kw 15 amps   3 phase: 2.2kw 7 amps
<b>Freight Dimensions:</b>	L 2900mm W 480mm H 1100mm W 680KG