

Zero Emissions | Field Repairable | Standardized Motors



Table of Sizes and Specifications

MODEL Pump Size	ANSI-B73.1 Frame Size	RPM 50/60 Hz	SUCTION FLANGE 150#, 300#, 600#	DISCHARGE FLANGE 150#, 300#, 600#	IMPELLER INCHES Full Size
1.5x1x8	AA	1500/1800	1.5" or 2"	1"	8.25"
1.5x1x8	AA	3000/3600	1.5" or 2"	1"	8.25"
3x2x9	A60	1500/1800	3"	2"	9.25"
3x2x9	A60	3000/3600	3"	2"	9.25"

WMCA Conditions and Specifications

Max. Flow	350 GPM
Max. Head	300 Feet
Max. Allowable Working Pressure	40 BAR/600 PSI Standard
Max. Allowable Working Pressure	100 BAR/1500 PSI Built-to-Spec
Specific Gravity	0.15 - 2.0
Max. Viscosity	3500/1750 RPM
Liquid Temperture Range	-139 °F to +600 °F
Pump Material	304-SS, Hastelloy C, Duplex-SS
Motor Horsepower Range	2-30 HP



Hydrodynamically Balanced Impeller

Performance Guarantee for Approved Applications



Seal-Less Mag-Drive Pumps
From Stock or Built-to-Spec™

High Pressure,
Low NPSH
Process Pumps

Low NPSH - High Pressure

Our company goals are to provide the solutions that protect our surroundings, raise the environmental awareness, and promote the growth of the community.

Services

API & CPI Processes


- Chemical Processing
- Petrochemicals
- Petroleum By-Products
- Hydrocarbons
- Liquified Gases

Refrigeration Systems

- Ammonia, CO2
- Fluorocarbon Refrigerants

Thermal Transfer Systems

- High-temp Synthetic Oils
- Low-temp Synthetic Oils
- Super Heated Water



High Pressure | Low NPSH | Meets ANSI-B73.1

WARRENDER SEAL-LESS MAG-DRIVE PUMPS

Warrender mag-drive seal-less pumps meet EPA zero emissions regulations with versatile magnetic coupling technology. Minimal heat loads, field serviceability and lower installation costs are significant process advantages. Solve your most challenging pumping problems with reliable and cost effective solutions.

Zero Emissions and Maximum Safety

Benefit from a process free of leakage, contamination or toxic releases while avoiding constant monitoring and potential environmental fines. Eliminate all toxic and dangerous chemical releases including volatile and toxic liquids that can react with atmospheric contact.

Advanced Technology and the Highest Quality for Long Pump Life

WARRENDER pump designs are built to the highest quality standards to protect your process, preventing costly maintenance and lost production time.


- Robust, high thickness pump casings
- High efficiency impellers with low NPSH requirements
- High strength, rare earth magnetic couplings suitable for extreme temperatures
- Heavy duty rear casings
- Rugged internal bearing system withstands process upsets

Performance to the Extreme

- Flows from 5 to 350 GPM
- Pressures up to 1500 PSIG
- Heads to 300 feet
- Temperatures from -139°F to +600°F
- Pump liquefied gases or liquids with low NPSH
- Compatible with VFD control systems
- NPSH down to 1 foot

Series WMCA - Process Centrifugal - Low NPSH Seal-Less Centrifugal

Series WMCA-LN ANSI mag-drive centrifugal pumps are engineered for long-life, zero emissions pumping in the most arduous process conditions. Low heat induction avoids costly down-time and repairs due to flashing, including chemical, hydrocarbon, ammonia, CO₂, and fluorocarbon processes.




WMCA-LN Features

- Low heat load avoids flashing
- Seal-less design free of mechanical seal maintenance
- Magnetic coupling design for process & inventory flexibility
- Standard NEMA motors meet UL and EXP requirements

WMCA Performance Range

- Flows from 5 to 350 GPM (1-80 m³/h)
- Heads to 1000 feet (227 m)
- System Pressures to 1,450 psig (100 bar)
- Temperatures from -139 to +600°F (-95 to +315°C)

Epoxy primer and polyacrylic enamel water based paint system for a corrosion resistant coating, yet environmentally friendly.



WARRENDER
warrender.com

Seal-Less Pumps | Low NPSH | High System Pressure

Field assembling of the product lubricated bearing arrangement does not require special tools. The bearing materials available in three different materials to provide the best solution for each application: Silicon Carbide (SSIC), Tungsten Carbide (TC), and Carbon

The use of tolerance rings reduces the sleeve and thrust bearing loads to guarantee many years of maintenance-free operation.

CF8M pump casing & impeller
High quality casting components

REAR CARTRIDGE KIT
For quick retrofits

Closed impeller statically and dynamically balanced. The axial thrust loads are balanced by back vanes.

Confined casing gaskets prevent leakage to the atmosphere – optional materials available:

- PTFE
- Graphoil type
- Garlock type
- Gylon type
- Flexitallic type