

THE ZERO-EMISSION HYDROGEN POWER GENERATOR

Produce your own emission-free electricity at an affordable cost.

With the GEH₂ and its record energy density, instantly get power from 100kVA to 1MVA.











Performance

Output power	Cos phi = 1	Cos phi = 0.8
Prime Running Power (PRP)	80kW	100kVA
Emergency Stand-by Power (ESP) 1h	88kW	110kVA
Life span	13 000 hours	
Autonomy at 50% PRP (one V18 rack)	About 8 h	
Output voltage	230/400 V-50 Hz	
Neutral point	П	

Easy to use

Connected and monitored	Included
Predictive maintenance and remote support	Included
HMI	Touch interface + optional remote interface
Operational continuity with double H ₂ adduction	Possibility to switch from one storage to the other while in operation
Ingress Protection	IP43
Operating temperature	- 5 to + 45°C
Frost protection	Integrated 230V plug
Handling/Lifting	Lifting eyes + forklift space
Idling and low load operation	No minimum operating power required
Compliance	ISO/CE Standards






GEH₂ Applications

Isolated sites

(Scientific bases, living quarters, refuges, islands, relay antennas)

Sensitive or confined environments

(Tunnels, mines, confined spaces)






Protected and regulated areas

(Zero-emission zones)

Construction

(Off-grid or in city centers)





Events

(Concerts and temporary or sporting events)

Emergency applications
(Data centers, hospitals, airports, ports, banks)









Energy Designer

STSH₂

GEH₂

REXH₂



The energy mix optimization experts



The hydrogen refueling mobile station



The zero-emission hydrogen power generator



The on-board solution for zero-emission navigation

FOR MORE INFORMATION

www.eo.dev

business@eo.dev